


# ALLOY/STRUCTURAL — MACHINE SCREWS

## NAS600 - NAS603 MACHINE SCREWS



| Thread | Length     | Part No.   | Price Ea.  |
|--------|------------|------------|------------|
| 4-40   | .188       | NAS600-3P  | \$0.11     |
|        | .250       | NAS600-4P  | \$0.06     |
|        | .312       | NAS600-5P  | \$0.09     |
|        | .375       | NAS600-6P  | \$0.09     |
|        | .438       | NAS600-7P  | \$0.08     |
|        | .500       | NAS600-8P  | \$0.07     |
| 6-32   | .188       | NAS601-3P  | \$0.12     |
|        | .250       | NAS601-4P  | \$0.07     |
|        | .312       | NAS601-5P  | \$0.08     |
|        | .375       | NAS601-6P  | \$0.09     |
|        | .438       | NAS601-7P  | \$0.08     |
|        | .500       | NAS601-8P  | \$0.09     |
|        | .562       | NAS601-9P  | \$0.09     |
|        | .625       | NAS601-10P | \$0.10     |
|        | .750       | NAS601-12P | \$0.14     |
| 8-32   | .188       | NAS602-3P  | \$0.15     |
|        | .250       | NAS602-4P  | \$0.11     |
|        | .312       | NAS602-5P  | \$0.11     |
|        | .375       | NAS602-6P  | \$0.14     |
|        | .438       | NAS602-7P  | \$0.11     |
|        | .500       | NAS602-8P  | \$0.15     |
|        | .562       | NAS602-9P  | \$0.14     |
|        | .625       | NAS602-10P | \$0.12     |
|        | .688       | NAS602-11P | \$0.13     |
|        | .750       | NAS602-12P | \$0.13     |
|        | .813       | NAS602-13P | \$0.14     |
|        | .875       | NAS602-14P | \$0.15     |
|        | 10-32      | 1.00       | NAS602-16P |
| .250   |            | NAS603-4P  | \$0.17     |
| .312   |            | NAS603-5P  | \$0.14     |
| .375   |            | NAS603-6P  | \$0.14     |
| .438   |            | NAS603-7P  | \$0.18     |
| .500   |            | NAS603-8P  | \$0.14     |
| .562   |            | NAS603-9P  | \$0.21     |
| .625   |            | NAS603-10P | \$0.16     |
| .688   |            | NAS603-11P | \$0.19     |
| .750   |            | NAS603-12P | \$0.18     |
| .813   |            | NAS603-13P | \$0.17     |
| .875   |            | NAS603-14P | \$0.28     |
| .938   |            | NAS603-15P | \$0.16     |
| 1.00   |            | NAS603-16P | \$0.21     |
| 1.125  | NAS603-18P | \$0.23     |            |
| 1.25   | NAS603-20P | \$0.39     |            |

- Phillips Pan Head
- Alloy Steel (8740)
- Finish - Cadmium per QQ-P-416
- Tensile -160,000 - 180,000 PSI




HA

## NAS1096 HEX HEAD SCREWS



| Thread | Length       | Part No.     | Price Ea. |
|--------|--------------|--------------|-----------|
| 6-32   | .375         | NAS1096-1-6  | \$0.14    |
|        | .438         | NAS1096-1-7  | \$0.11    |
|        | .500         | NAS1096-1-8  | \$0.19    |
|        | .562         | NAS1096-1-9  | \$0.16    |
|        | .625         | NAS1096-1-10 | \$0.15    |
|        | .750         | NAS1096-1-12 | \$0.18    |
| 8-32   | .312         | NAS1096-2-5  | \$0.10    |
|        | .375         | NAS1096-2-6  | \$0.13    |
|        | .438         | NAS1096-2-7  | \$0.13    |
|        | .500         | NAS1096-2-8  | \$0.13    |
|        | .562         | NAS1096-2-9  | \$0.18    |
|        | .625         | NAS1096-2-10 | \$0.17    |
| 10-32  | .750         | NAS1096-2-12 | \$0.17    |
|        | .312         | NAS1096-3-5  | \$0.09    |
|        | .375         | NAS1096-3-6  | \$0.18    |
|        | .438         | NAS1096-3-7  | \$0.18    |
|        | .500         | NAS1096-3-8  | \$0.17    |
|        | .562         | NAS1096-3-9  | \$0.16    |
|        | .625         | NAS1096-3-10 | \$0.18    |
|        | .750         | NAS1096-3-12 | \$0.23    |
|        | .875         | NAS1096-3-14 | \$0.26    |
|        | 1.00         | NAS1096-3-16 | \$0.28    |
| 1.25   | NAS1096-3-20 | \$0.23       |           |




- Phillips Hex Head
- Alloy Steel per MIL-S-6049
- Finish - Cadmium per QQ-P-416 Type II
- Tensile - 125,000-145,000 PSI

## NAS1801 HEX HEAD SCREWS



| Thread | Length | Part No.      | Price Ea.   |
|--------|--------|---------------|-------------|
| 8-32   | .250   | NAS1801-08-4  | \$0.15      |
|        | .312   | NAS1801-08-5  | \$0.17      |
|        | .375   | NAS1801-08-6  | \$0.16      |
|        | .438   | NAS1801-08-7  | \$0.14      |
|        | .500   | NAS1801-08-8  | \$0.19      |
|        | .562   | NAS1801-08-9  | \$0.22      |
|        | .625   | NAS1801-08-10 | \$0.18      |
|        | .750   | NAS1801-08-12 | \$0.22      |
|        | .875   | NAS1801-08-14 | \$0.22      |
|        | 1.00   | NAS1801-08-16 | \$0.21      |
|        | 1.125  | NAS1801-08-18 | \$0.21      |
|        | 1.25   | NAS1801-08-20 | \$0.21      |
|        | 1.375  | NAS1801-08-22 | \$0.45      |
|        | 10-32  | .312          | NAS1801-3-5 |
| .375   |        | NAS1801-3-6   | \$0.19      |
| .438   |        | NAS1801-3-7   | \$0.19      |
| .500   |        | NAS1801-3-8   | \$0.21      |
| .562   |        | NAS1801-3-9   | \$0.26      |
| .625   |        | NAS1801-3-10  | \$0.24      |
| .750   |        | NAS1801-3-12  | \$0.26      |
| .875   |        | NAS1801-3-14  | \$0.24      |
| 1.00   |        | NAS1801-3-16  | \$0.34      |
| 1.125  |        | NAS1801-3-18  | \$0.27      |
| 1.25   |        | NAS1801-3-20  | \$0.28      |
| 1.375  |        | NAS1801-3-22  | \$0.48      |
| 1.50   |        | NAS1801-3-24  | \$0.51      |





- Phillips Hex Head
- Alloy Steel Per MIL-S-6049
- Finish - Cad Plate per QQ-P-416, Type II
- Tensile - 160,000-185,000 PSI

## NAS1202 / NAS1203 FLUSH HEAD SCREWS

- Phillips 100° Flat Head
- Tensile - 160,000 - 180,000 PSI
- Alloy Steel Per MIL-S-6049
- Finish - Cadmium per QQ-P-416, Type II



| Thrd. | Grip | Lgth. | Part No.  | Price Ea. |
|-------|------|-------|-----------|-----------|
| 8-32  | .125 | .401  | NAS1202-2 | \$0.12    |
|       | .188 | .464  | NAS1202-3 | \$0.16    |
|       | .250 | .526  | NAS1202-4 | \$0.13    |
|       | .312 | .588  | NAS1202-5 | \$0.13    |
|       | .375 | .651  | NAS1202-6 | \$0.14    |
|       | .438 | .714  | NAS1202-7 | \$0.15    |
| 10-32 | .125 | .401  | NAS1203-2 | \$0.15    |
|       | .188 | .464  | NAS1203-3 | \$0.14    |
|       | .250 | .526  | NAS1203-4 | \$0.15    |
|       | .312 | .588  | NAS1203-5 | \$0.17    |
|       | .375 | .651  | NAS1203-6 | \$0.18    |
|       | .438 | .714  | NAS1203-7 | \$0.15    |
|       | .500 | .776  | NAS1203-8 | \$0.18    |



## MS5199 MACHINE SCREWS

- Phillips 82° Flat Head
- Stainless Steel

| Thrd. | Lgth. | Part No.   | Each   | Thrd. | Lgth. | Part No.   | Each   |
|-------|-------|------------|--------|-------|-------|------------|--------|
| 2-56  | .188  | MS51959-2  | \$0.04 | 6-32  | .312  | MS51959-27 | \$0.07 |
|       | .250  | MS51959-3  | \$0.04 |       | .375  | MS51959-28 | \$0.07 |
|       | .312  | MS51959-4  | \$0.04 |       | .438  | MS51959-29 | \$0.07 |
|       | .375  | MS51959-5  | \$0.04 |       | .500  | MS51959-30 | \$0.07 |
|       | .250  | MS51959-13 | \$0.04 |       | .625  | MS51959-31 | \$0.07 |
| 4-40  | .312  | MS51959-14 | \$0.05 | 8-32  | .375  | MS51959-43 | \$0.09 |
|       | .375  | MS51959-15 | \$0.05 |       | .438  | MS51959-44 | \$0.09 |
|       | .438  | MS51959-16 | \$0.07 |       | .500  | MS51959-45 | \$0.09 |
|       | .500  | MS51959-17 | \$0.06 |       | .625  | MS51959-46 | \$0.09 |
|       |       |            |        |       | .750  | MS51959-47 | \$0.11 |

## NAS623 PAN HEAD SCREWS

- Phillips Pan Head
- Alloy Steel per MIL-S-6049
- Finish: Cadmium per QQ-P-416, Type II
- Tensile: 160,000-180,000 PSI



| Thrd. | Lgth.      | Part No.    | Each   | Thrd. | Lgth. | Part No.    | Each   |
|-------|------------|-------------|--------|-------|-------|-------------|--------|
| 8-32  | .338       | NAS623-2-1  | \$0.14 | 10-32 | .588  | NAS623-3-5  | \$0.17 |
|       | .401       | NAS623-2-2  | \$0.15 |       | .651  | NAS623-3-6  | \$0.18 |
|       | .464       | NAS623-2-3  | \$0.16 |       | .714  | NAS623-3-7  | \$0.22 |
|       | .526       | NAS623-2-4  | \$0.14 |       | .776  | NAS623-3-8  | \$0.19 |
|       | .588       | NAS623-2-5  | \$0.19 |       | .838  | NAS623-3-9  | \$0.22 |
|       | .651       | NAS623-2-6  | \$0.21 |       | .901  | NAS623-3-10 | \$0.17 |
|       | .714       | NAS623-2-7  | \$0.19 |       | .964  | NAS623-3-11 | \$0.19 |
|       | .776       | NAS623-2-8  | \$0.21 |       | 1.026 | NAS623-3-12 | \$0.21 |
|       | .838       | NAS623-2-9  | \$0.20 |       | 1.088 | NAS623-3-13 | \$0.18 |
|       | .901       | NAS623-2-10 | \$0.17 |       | 1.151 | NAS623-3-14 | \$0.21 |
|       | .964       | NAS623-2-11 | \$0.21 |       | 1.214 | NAS623-3-15 | \$0.24 |
|       | 1.026      | NAS623-2-12 | \$0.20 |       | 1.276 | NAS623-3-16 | \$0.21 |
|       | .401       | NAS623-3-2  | \$0.16 |       | 1.338 | NAS623-3-17 | \$0.24 |
|       | .464       | NAS623-3-3  | \$0.18 |       | 1.401 | NAS623-3-18 | \$0.32 |
| .526  | NAS623-3-4 | \$0.15      |        |       |       |             |        |