

Safety Data Sheet

According to OSHA HCS 2012 (29 CFR 1910.1200); Health Canada HPR (SOR/2015-17), and Mexico NOM-018-STPS-2015



SECTION 1: Identification

Product Identifier **X/C® Aviation Hydraulic Fluid**
Other means of identification Phillips 66® X/C® Aviation Hydraulic Fluid 5606A
Phillips 66® X/C® Aviation Hydraulic Fluid 5606H
Phillips 66® X/C® Aviation Hydraulic Fluid 5606J
Code **LBP778520**
Issue date 28-Feb-2019
Relevant identified uses Hydraulic Fluid
Uses advised against All others
24 Hour Emergency Phone Number CHEMTREC: 1-800-424-9300

Manufacturer/Supplier	SDS Information	Customer Service
Phillips 66 Lubricants A Division of Phillips 66 Company P.O. Box 421959 Houston, Texas 77242-1959	URL: www.phillips66.com/SDS Phone: 800-762-0942 Email: SDS@P66.com	U.S.: 800-368-7128 or International: 1-832-765-2500 Technical Information 1-877-445-9198

Initial supplier identifier (Canada)
Phillips 66 Canada Ltd.
PO Box 258, Station M
Calgary, AB T2P 2H9
Telephone: 587-233-6600
Customer Service: 800-633-0383

SECTION 2: Hazard identification

Classified Hazards	Hazards Not Otherwise Classified (HNOC)
H227 - Flammable liquids -- Category 4 H304 -- Aspiration Hazard -- Category 1 H315 -- Skin corrosion/irritation -- Category 2 H336 -- Specific target organ toxicity (single exposure) -- Category 3 H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2	PHNOC: None known HHNOC: None known

Label elements

DANGER

Combustible liquid
May be fatal if swallowed and enters airways
Causes skin irritation
May cause drowsiness or dizziness
Toxic to aquatic life with long lasting effects



Keep away from heat/sparks/open flames/hot surfaces. - No smoking; Avoid breathing dust/fume/gas/mist/vapours/spray; Wash skin thoroughly after handling; Use only outdoors or in a well-ventilated area; Avoid release to the environment; Wear protective gloves/protective clothing and eye/face protection; IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician; Do NOT induce vomiting; IF ON SKIN: Wash with plenty of soap and water; If skin irritation occurs: Get medical advice/attention; IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing; Call a POISON CENTER or doctor/physician if you feel unwell; Take off contaminated clothing and wash before reuse; In case of fire: Use CO2, dry chemical, or foam for extinction; Collect spillage; Store in a well-ventilated place. Keep container tightly closed; Keep cool; Store locked up; Dispose of contents/container to an approved waste disposal plant

SECTION 3: Composition/information on ingredients

Chemical Name	CASRN	Concentration
Petroleum distillates, hydrotreated light	64742-47-8	<70
Distillates, petroleum, hydrotreated light naphthenic	64742-53-6	<20
Distillates, petroleum, hydrotreated heavy paraffinic	64742-54-7	<10
Distillates, petroleum, hydrotreated light paraffinic	64742-55-8	<10
Triphenyl phosphate	115-86-6	<1

¹ All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

Eye Contact: If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

Skin Contact: Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops, seek medical attention. Wash contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician. (see Note to Physician)

Inhalation: First aid is not normally required. If breathing difficulties develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. Seek immediate medical attention.

Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with the head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.

Most important symptoms and effects, both acute and delayed: While significant vapor concentrations are not likely, high concentrations can cause minor respiratory irritation, headache, drowsiness, dizziness, loss of coordination, disorientation and fatigue. Ingestion can cause irritation of the digestive tract, nausea, diarrhea, and vomiting. Prolonged or repeated contact may dry skin and cause irritation.


Notes to Physician: Acute aspirations of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

When using high-pressure equipment, injection of product under the skin can occur. In this case, the casualty should be sent immediately to the hospital. Do not wait for symptoms to develop. High-pressure hydrocarbon injection injuries may produce substantial necrosis of underlying tissue despite an innocuous appearing external wound. These injuries often require extensive emergency surgical debridement and all injuries should be evaluated by a specialist in order to assess the extent of injury. Early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

SECTION 5: Firefighting measures

NFPA 704: National Fire Protection Association

Health: 1 Flammability: 2 Instability: 0



0 = minimal hazard
1 = slight hazard
2 = moderate hazard
3 = severe hazard
4 = extreme hazard

Extinguishing Media: Dry chemical, carbon dioxide, foam, or water spray is recommended. Water or foam may cause frothing of materials heated above 212°F / 100°C. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Specific hazards arising from the chemical

Unusual Fire & Explosion Hazards: Combustible. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, or mechanical/electrical equipment). May create vapor/air explosion hazard if heated. This product will float and can be reignited on surface water. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion. Oxides of sulfur, nitrogen or phosphorus may also be formed.

Special protective actions for fire-fighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purposes.

See Section 9 for Flammable Properties including Flash Point and Flammable (Explosive) Limits

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures: Combustible. Keep all sources of ignition away from spill/release. The use of explosion-proof electrical equipment is recommended. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant (see Section 8). See Sections 2 and 7 for additional information on hazards and precautionary measures.

Environmental Precautions: Stop and contain spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard. Spills into or upon navigable waters, the contiguous zone, or adjoining shorelines that cause a sheen or discoloration on the surface of the water, may require notification of the National Response Center (phone number 800-424-8802).

Methods and material for containment and cleaning up: Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations.

Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken. See Section 13 for information on appropriate disposal.

SECTION 7: Handling and storage

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Use only non-sparking tools. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Use good personal hygiene practices and wear appropriate personal protective equipment (see section 8). Spills will produce very slippery surfaces.

High pressure injection of hydrocarbon fuels, hydraulic oils or greases under the skin may have serious consequences even though no symptoms or injury may be apparent. This can happen accidentally when using high pressure equipment such as high pressure grease guns, fuel injection apparatus or from pinhole leaks in tubing of high pressure hydraulic oil equipment.

Open container slowly to relieve any pressure. Do not wear contaminated clothing or shoes. Keep contaminated clothing away from sources of ignition such as sparks or open flames. The use of explosion-proof electrical equipment is recommended and may be required (see appropriate fire codes). Refer to NFPA-70 and/or API RP 2003 for specific bonding/grounding requirements. Do not enter confined spaces such as tanks or pits without following proper entry procedures such as ASTM D-4276 and 29CFR 1910.146.

Conditions for safe storage: Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated area away from heat and all sources of ignition. Post area "No Smoking or Open Flame." Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Outdoor or

detached storage is preferred. Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1, and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

"Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 8: Exposure controls/personal protection

Occupational exposure limits				
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.				
Chemical Name	ACGIH	OSHA	Mexico	Phillips 66
Petroleum distillates, hydrotreated light	---	---	---	TWA-8hr: 200 mg/m ³ Skin
Distillates, petroleum, hydrotreated light naphthenic	TWA: 5mg/m ³ STEL: 10 mg/m ³ as Oil Mist, if Generated	---	---	---
Distillates, petroleum, hydrotreated heavy paraffinic	TWA: 5mg/m ³ STEL: 10 mg/m ³ as Oil Mist, if Generated	---	---	---
Distillates, petroleum, hydrotreated light paraffinic	TWA: 5mg/m ³ STEL: 10 mg/m ³ as Oil Mist, if Generated	---	---	---
Triphenyl phosphate	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA-8hr: 3 mg/m ³ (VLE-PPT) STEL: 6 mg/m ³ (PPT-CT)) carcinogen	---

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Biological occupational exposure limits

Note: None

Engineering controls: If current ventilation practices are not adequate to maintain airborne concentrations below the established exposure limits, additional engineering controls may be required.

Eye/Face Protection: The use of eye protection that meets or exceeds ANSI Z.87.1 is recommended to protect against potential eye contact, irritation, or injury. Depending on conditions of use, a face shield may be necessary.

Skin/Hand Protection: The use of gloves impervious to the specific material handled is advised to prevent skin contact. Users should check with manufacturers to confirm the breakthrough performance of their products. Depending on exposure and use conditions, additional protection may be necessary to prevent skin contact including use of items such as chemical resistant boots, aprons, arm covers, hoods, coveralls, or encapsulated suits. Suggested protective materials: Nitrile rubber

Respiratory Protection: Where there is potential for airborne exposure above the exposure limit a NIOSH certified air purifying respirator equipped with organic vapor cartridges/canisters with R or P95 filters may be used.

A respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed whenever workplace conditions warrant a respirator's use. Air purifying respirators provide limited protection and cannot be used in atmospheres that exceed the maximum use concentration (as directed by regulation or the manufacturer's instructions), in oxygen deficient (less than 19.5 percent oxygen) situations, or under conditions that are immediately dangerous to life and health (IDLH).

Other Protective Equipment: Eye wash and quick-drench shower facilities should be available in the work area. Thoroughly clean shoes and wash contaminated clothing before reuse.

Suggestions provided in this section for exposure control and specific types of protective equipment are based on readily available information. Users should consult with the specific manufacturer to confirm the performance of their protective equipment. Specific situations may require consultation with industrial hygiene, safety, or engineering professionals.

SECTION 9: Physical and chemical properties

Note: Unless otherwise stated, values are determined at 20°C (68°F) and 760 mm Hg (1 atm). Data represent typical values and are not intended

to be specifications.

<p>Appearance: Red Physical Form: Liquid Odor: Petroleum Odor Threshold: No data pH: Not applicable Vapor Density (air=1): >1 Upper Explosive Limits (vol % in air): Not determined Lower Explosive Limits (vol % in air): Not determined Evaporation Rate (nBuAc=1): No data Particle Size: Not applicable Percent Volatile: Negligible Flammability (solid, gas): Not applicable Solubility in Water: Negligible</p>	<p>Flash Point: 180 °F / 82 °C (ASTM D93) Test Method: Pensky-Martens Closed Cup (PMCC), ASTM D93, EPA 1010 Initial Boiling Point/Range: No data Vapor Pressure: <0.01 mm Hg Partition Coefficient (n-octanol/water) (Kow): No data Melting/Freezing Point: No data Auto-ignition Temperature: No data Decomposition Temperature: No data Specific Gravity (water=1): 0.8708 @ 60°F (15.6°C) Bulk Density: No data Viscosity: 4.9 cSt @ 100°C; 13.5 cSt @ 40°C Pour Point: < -76 °F / < -60 °C VOC Content (%): 53</p>
--	--

SECTION 10: Stability and reactivity

Reactivity: Not chemically reactive.

Chemical stability: Stable under normal ambient and anticipated conditions of use.

Possibility of hazardous reactions: Hazardous reactions not anticipated.

Conditions to avoid: Extended exposure to high temperatures can cause decomposition. Avoid all possible sources of ignition.

Incompatible materials: Avoid contact with strong oxidizing agents and strong reducing agents.

Hazardous decomposition products: Not anticipated under normal conditions of use.

SECTION 11: Toxicological information

Information on Toxicological Effects

Substance / Mixture			
Acute Toxicity	Hazard	Additional Information	LC50/LD50 Data
Inhalation	Unlikely to be harmful		>5 mg/L (mist, estimated)
Dermal	Unlikely to be harmful		> 2 g/kg (estimated)
Oral	Unlikely to be harmful		> 5 g/kg (estimated)

Likely Routes of Exposure: Inhalation, eye contact, skin contact

Aspiration Hazard: May be fatal if swallowed and enters airways

Skin Corrosion/Irritation: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

Serious Eye Damage/Irritation: Causes mild eye irritation.

Skin Sensitization: Not expected to be a skin sensitizer.

Respiratory Sensitization: No information available.

Specific Target Organ Toxicity (Single Exposure): May cause drowsiness and dizziness. Based on component information

Specific Target Organ Toxicity (Repeated Exposure): Not expected to cause organ effects from repeated exposure.

Carcinogenicity: Not expected to cause cancer.

Germ Cell Mutagenicity: Not expected to cause heritable genetic effects.

Reproductive Toxicity: Not expected to cause reproductive toxicity.

Information on Toxicological Effects of Components

Petroleum distillates, hydrotreated light

Reproductive Toxicity: Hydrosulfurized kerosene applied to the skin of female rats at 494, 330, or 165 mg/kg daily for 7 consecutive weeks (pre-mating, mating, and gestation), or for 8 consecutive weeks in males did not result in systemic, reproductive, or developmental toxicity.

Lubricant Base Oil (Petroleum)

Carcinogenicity: The petroleum base oils contained in this product have been highly refined by a variety of processes including severe hydrocracking/hydroprocessing to reduce aromatics and improve performance characteristics. All of the oils meet the IP-346 criteria of less than 3 percent PAH's and are not considered carcinogens by NTP, IARC, or OSHA.

SECTION 12: Ecological information



GHS Classification:

H411 -- Hazardous to the aquatic environment, chronic toxicity -- Category 2

Toxic to aquatic life with long lasting effects.

Toxicity: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

Persistence and Degradability: The hydrocarbons in this material are not readily biodegradable but are regarded as inherently biodegradable since their hydrocarbon components can be degraded by microorganisms.

Bioaccumulative Potential: Hydrocarbon constituents of kerosene show measured or predicted Log Kow values ranging from 3 to 6 and above and therefore would be regarded as having the potential to bioaccumulate. In practice, metabolic processes may reduce bioconcentration.

Mobility in Soil: On release to water, hydrocarbons will float on the surface and since they are sparingly soluble, the only significant loss is volatilization to air. It is possible that some of the higher molecular weight hydrocarbons will be adsorbed on sediment. Biodegradation in water is a minor loss process. In air, these hydrocarbons are photodegraded by reaction with hydroxyl radicals with half lives varying from 0.1 to 0.7 days.

Other adverse effects: None anticipated.

SECTION 13: Disposal considerations

The generator of a waste is always responsible for making proper hazardous waste determinations and needs to consider state and local requirements in addition to federal regulations. This material, if discarded as produced, would not be a federally regulated RCRA "listed" hazardous waste and is not believed to exhibit characteristics of hazardous waste. See Sections 7 and 8 for information on handling, storage and personal protection and Section 9 for physical/chemical properties. It is possible that the material as produced contains constituents which are not required to be listed in the SDS but could affect the hazardous waste determination. Additionally, use which results in chemical or physical change of this material could subject it to regulation as a hazardous waste. This material under most intended uses would become "Used Oil" due to contamination by physical or chemical impurities. Whenever possible, Recycle used oil in accordance with applicable federal and state or local regulations. Container contents should be completely used and containers should be emptied prior to discard.

SECTION 14: Transport information

The following description is for container(s) larger than 5 liters (liquids) or 5 kilograms (solids) and bulk packages, shipped by water mode. Other shipments are not regulated.

UN Number: UN3082

UN proper shipping name: Environmentally hazardous substances, liquid, n.o.s (Petroleum distillates, Triphenyl Phosphate)

Transport hazard class(es): 9

Packing Group: III

Environmental Hazards: Marine pollutant - Environmentally Hazardous

Special precautions for user: None

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

SECTION 15: Regulatory information

CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs (in pounds)

This material does not contain any chemicals subject to the reporting requirements of SARA 302 and 40 CFR 372.

CERCLA/SARA - Section 311/312 (Title III Hazard Categories)

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CERCLA/SARA - Section 313 and 40 CFR 372

This material does not contain any chemicals subject to the reporting requirements of SARA 313 and 40 CFR 372.

EPA (CERCLA) Reportable Quantity (in pounds)

This material does not contain any chemicals with CERCLA Reportable Quantities.

California Proposition 65

This material does not contain any chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm at concentrations that trigger the warning requirements of California Proposition 65.

International Inventories

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA.
All components are either on the DSL, or are exempt from DSL listing requirements.

SECTION 16: Other information

Issue date	Previous Issue Date:	SDS Number	Status:
28-Feb-2019	02-Mar-2018	LBPH778520	FINAL

Revised Sections or Basis for Revision:

Periodic review and update

Mexican NOM-018-STPS-2015:

The information within is considered correct but is not exhaustive and will be used for guidance only, which is based on the current knowledge of the substance or mixture and is applicable to the appropriate safety precautions for the product.

Precautionary Statements:

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
- P264 - Wash skin thoroughly after handling
- P271 - Use only outdoors or in a well-ventilated area
- P273 - Avoid release to the environment
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P235 - Keep cool
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- P331 - Do NOT induce vomiting
- P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
- P332 + P313 - If skin irritation occurs: Get medical advice/attention
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P312 - Call a POISON CENTER or doctor if you feel unwell
- P362 - Take off contaminated clothing and wash before reuse
- P370 + P378 - In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish
- P391 - Collect spillage
- P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
- P405 - Store locked up
- P501 - Dispose of contents/ container to an approved waste disposal plant

Guide to Abbreviations:

ACGIH = American Conference of Governmental Industrial Hygienists; CASRN = Chemical Abstracts Service Registry Number; CEILING = Ceiling Limit (15 minutes); CERCLA = The Comprehensive Environmental Response, Compensation, and Liability Act; EPA = Environmental Protection Agency; GHS = Globally Harmonized System; HPR = Hazardous Products Regulations; IARC = International Agency for Research on Cancer; INSHT = National Institute for Health and Safety at Work; IOPC = International Oil Pollution Compensation; LEL = Lower Explosive Limit; NE = Not Established; NFPA = National Fire Protection Association; NTP = National Toxicology Program; OSHA = Occupational Safety and Health

Administration; PEL = Permissible Exposure Limit (OSHA); SARA = Superfund Amendments and Reauthorization Act; STEL = Short Term Exposure Limit (15 minutes); TLV = Threshold Limit Value (ACGIH); TWA = Time Weighted Average (8 hours); UEL = Upper Explosive Limit; WHMIS = Worker Hazardous Materials Information System (Canada)

Disclaimer of Expressed and implied Warranties:

The information presented in this Safety Data Sheet is based on data believed to be accurate as of the date this Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.