



UNDERCOATINGS

Easy to use, non-sag formulas
Exceptional coverage
Outstanding final appearance

UNDERCOATING

- Asphalt based formula
- Non-paintable

RUBBERIZED UNDERCOATING

- No asphalt
- Fast drying
- Paintable in 30 minutes without bleed through



39463 UNDERCOATING

39523 RUBBERIZED UNDERCOATING

40463 LOW VOC UNDERCOATING 🌱

40523 LOW VOC RUBBERIZED UNDERCOATING 🌱

NOW OFFERING

40524 LOW VOC RUBBERIZED UNDERCOATING 🌱

SAME GREAT PRODUCT IN A QUART CONTAINER!

UNDERCOATINGS

39463 UNDERCOATING and **40463 LOW VOC UNDERCOATING** are non-paintable, asphalt based products that provide sound-deadening properties, excellent chip resistance and outstanding corrosion protection. **40463** is below 40% VOC.

39523 RUBBERIZED UNDERCOATING and **4052() LOW VOC RUBBERIZED UNDERCOATING** are paintable, fast-drying, asphalt-free coatings for rust proofing, sound deadening, chip resistance and corrosion protection. **40523** and **40524** are below 40% VOC.

PREPARATION



Clean surface with **38373 SEM SOLVE** or **38381 WORLD CLASS™ SURFACE CLEANER**. Remove any loose paint, rust, oil and grease. Blow off and clean again with **38373** or **38381**.

APPLICATION



39463 and 40463

Distance: 8-12"
Coats: 2-3 medium wet
Flash time: 3-5 minutes

39523 and 40523

Distance: 6-8"
Coats: 2-3 medium wet
Flash time: 3-5 minutes
Paintable: 30 minutes @ 70°F



40524

Attach **40524** to **71101 ECONOMY COATING GUN**.

Air pressure: 35-40 psi
Coats: 2-3 medium
Flash time: 3-5 minutes
Paintable: 30 minutes @ 70°F

Clean gun immediately after use with solvent compliant in your area.

NOTE: Final texture, flash times, and dry times are affected by gun distance, air pressure, temperature, and humidity.



For additional information, refer to the specific product **TECHNICAL DATA SHEETS** or contact us at www.semproducts.com.



The Right Choice