

# SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

## Product name: MOLYKOTE<sup>™</sup> 55 O-Ring Grease

**Issue Date:** 05/18/2018 **Print Date:** 07/20/2018

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# **1. IDENTIFICATION**

Product name: MOLYKOTE™ 55 O-Ring Grease

Recommended use of the chemical and restrictions on use Identified uses: Lubricants and lubricant additives

COMPANY IDENTIFICATION THE DOW CHEMICAL COMPANY 2030 DOW CENTER MIDLAND MI 48674-0000 UNITED STATES

**Customer Information Number:** 

800-258-2436 SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER 24-Hour Emergency Contact: CHEMTREC +1 800-424-9300 Local Emergency Contact: 800-424-9300

# 2. HAZARDS IDENTIFICATION

## Hazard classification

GHS classification in accordance with 29 CFR 1910.1200 Skin sensitisation - Category 1

Label elements Hazard pictograms



Signal word: WARNING!

Hazards

May cause an allergic skin reaction.

#### **Precautionary statements**

#### Prevention

Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

#### Response

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/ attention. Wash contaminated clothing before reuse.

#### Disposal

Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

No data available

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone grease.

This	product	is a	mixture.	
------	---------	------	----------	--

Component	CASRN	Concentration
Lithium stearate	4485-12-5	>= 17.0 - <= 25.0 %
2,5-Furandione, dihydro-3-(tetrapropenyl)-	26544-38-7	>= 0.37 - <= 0.49 %

# 4. FIRST AID MEASURES

## Description of first aid measures

**General advice:** 

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Wash off with plenty of water.

**Eye contact:** Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

Ingestion: No emergency medical treatment necessary.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and

special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

## Indication of any immediate medical attention and special treatment needed

**Notes to physician:** No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

# **5. FIREFIGHTING MEASURES**

**Suitable extinguishing media:** Water spray Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture Hazardous combustion products: Silicon oxides Carbon oxides

**Unusual Fire and Explosion Hazards:** Exposure to combustion products may be a hazard to health.

# Advice for firefighters

**Fire Fighting Procedures:** Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

# 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:** Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions:** Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up:** Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. See sections: 7, 8, 11, 12 and 13.

# 7. HANDLING AND STORAGE

**Precautions for safe handling:** Do not get on skin or clothing. Do not swallow. Avoid contact with eyes. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice.

Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

**Conditions for safe storage:** Keep in properly labelled containers. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents. Unsuitable materials for containers: None known.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
Lithium stearate	ACGIH	TWA	10 mg/m3
	CAL PEL	PEL	10 mg/m3

# Exposure controls

**Engineering controls:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations.

## Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

## **Skin protection**

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions no respiratory protection should be needed; however, if discomfort is experienced, use an approved air-purifying respirator. The following should be effective types of air-purifying respirators: Organic vapor cartridge.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	
Physical state	Grease
Color	white
Odor	slight
Odor Threshold	No data available
рН	Not applicable
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	closed cup > 101.1 °C ( > 214.0 °F)
Evaporation Rate (Butyl Acetate	Not applicable
= 1)	
Flammability (solid, gas)	Not classified as a flammability hazard
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.1
Water solubility	No data available
Partition coefficient: n-	No data available
octanol/water	
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
•	
Liquid Density	1.1 g/cm3
	1.1 g/cm3 No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

# **10. STABILITY AND REACTIVITY**

**Reactivity:** Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Benzene.

# 11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

## Acute toxicity

## Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 5,000 mg/kg Estimated.

# Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s): LD50, Rat, > 2,000 mg/kg Estimated.

## Acute inhalation toxicity

Vapors are unlikely due to physical properties. As product: The LC50 has not been determined.

## Skin corrosion/irritation

Brief contact is essentially nonirritating to skin.

## Serious eye damage/eye irritation

May cause slight eye irritation. Corneal injury is unlikely.

## Sensitization

For skin sensitization: Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization: No relevant data found.

# Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

# Specific Target Organ Systemic Toxicity (Repeated Exposure)

Based on information for component(s): Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

## Carcinogenicity

No relevant data found.

# Teratogenicity

Based on information for component(s): Did not cause birth defects or other effects in the fetus even at doses which caused toxic effects in the mother.

## **Reproductive toxicity**

Contains component(s) which did not interfere with fertility in animal studies.

## Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies.

# **Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

# COMPONENTS INFLUENCING TOXICOLOGY:

# Lithium stearate

Acute inhalation toxicity The LC50 has not been determined.

# 2,5-Furandione, dihydro-3-(tetrapropenyl)-

Acute inhalation toxicity For similar material(s): LC50, Rat, male and female, 4 Hour, dust/mist, 5.3 mg/l

# 12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

## Toxicity

## Lithium stearate

## Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). Based on data from similar materials LL50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 100 mg/l, OECD Test Guideline 203

## Acute toxicity to aquatic invertebrates

Based on data from similar materials EL50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

## Acute toxicity to algae/aquatic plants

Based on data from similar materials EL50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

## Toxicity to bacteria

Based on data from similar materials NOEC, activated sludge, static test, 28 d, 13 mg/l

# 2,5-Furandione, dihydro-3-(tetrapropenyl)-

## Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested). LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, > 100 mg/l, OECD Test Guideline 203 or Equivalent

# Acute toxicity to aquatic invertebrates

For similar material(s): EC50, Daphnia dubia (water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

# Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), static test, 96 Hour, Growth rate, 110 mg/l

# Toxicity to bacteria

EC50, activated sludge, static test, 3 Hour, Respiration rates., 800 mg/l, OECD Test Guideline 209

# Persistence and degradability

## Lithium stearate

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Based on data from similar materials 10-day Window: Not applicable **Biodegradation:** 78 % **Exposure time:** 28 d **Method:** OECD Test Guideline 301C

## 2,5-Furandione, dihydro-3-(tetrapropenyl)-

**Biodegradability:** Biodegradation under aerobic static laboratory conditions is low (BOD20 or BOD28/ThOD between 2.5 and 10%). 10-day Window: Fail **Biodegradation:** 9.9 % **Exposure time:** 28 d **Method:** OECD Test Guideline 301D

Photodegradation Sensitization: OH radicals Atmospheric half-life: 1.7 - 1.9 Hour Method: Estimated. Photodegradation Sensitization: Ozone. Atmospheric half-life: 1.4 - 2.1 Hour Method: Estimated.

## **Bioaccumulative potential**

## Lithium stearate

**Bioaccumulation:** Based on data from similar materials No relevant data found. **Bioconcentration factor (BCF):** 0.12 Fish

## 2,5-Furandione, dihydro-3-(tetrapropenyl)-

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

Partition coefficient: n-octanol/water(log Pow): > 4.39 OECD Test Guideline 107

# Mobility in soil

## Lithium stearate

No relevant data found.

## 2,5-Furandione, dihydro-3-(tetrapropenyl)-

Potential for mobility in soil is low (Koc between 500 and 2000). **Partition coefficient (Koc):** 825 Measured

# **13. DISPOSAL CONSIDERATIONS**

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section10 Regulatory Information, MSDS Section 15

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

# 14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code

Not regulated for transport Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

# **15. REGULATORY INFORMATION**

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312 Respiratory or skin sensitisation

# Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ. This material does not contain any components with a CERCLA RQ.

# Pennsylvania Right To Know

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
Poly(dimethylsiloxane)copolymer	63148-52-7
Lithium stearate	4485-12-5
Di-2-ethylhexyl sebacate	122-62-3

## California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# **United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

# **16. OTHER INFORMATION**

## Hazard Rating System

NFPA

ſ	Health	Flammability	Instability
	2	1	0

HMIS

Health	Flammability	Physical Hazard
2/	1	0

## Revision

Identification Number: 4000034 / A001 / Issue Date: 05/18/2018 / Version: 4.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

# Legend

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
PEL	Permissible exposure limit
TWA	8-hour, time-weighted average

# Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances: ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA -Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA -Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

# Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version. US