



EP

## LOCTITE® 243 THREADLOCKER BLUE MED STRENGTH



Loctite® Blue Threadlocker 243™ (Aftermarket Only) is designed for the locking and sealing of threaded fasteners between 1/4" and 3/4" (6 to 20 mm), which require normal dis-assembly with standard hand tools. The product cures when confined in the absence of air between close fitting metal surfaces and prevents loosening and leakage from shock and vibration. The thixotropic nature of Loctite 243 reduces the migration of liquid product after application to the substrate. Loctite 243 provides robust curing performance. It not only works on active metals (e.g. brass, copper) but also on passive substrates such as stainless steel and plated surfaces. The product offers high temperature performance and oil tolerance. It tolerates minor surface contaminations from various oils, such as cutting, lubrication, anti-corrosion and protection fluids.

10 ml Bottle..... P/N 15-02562 ..... **\$18.50**

## LOCTITE® 648 GREEN



LOCTITE® 648 Retaining Compound:  
Press Fit / High Strength / Rapid Cure. A retaining compound recommended for continuous working temperatures up to 356°F (180°C). Fills gaps up to 0.006 in. diametral clearance. Fixtures in 10 minutes.

Technical Data:

Strength Required - High

Shear Strength (N / mm<sup>2</sup>) - 4,480 psi (31)

Temperature Resistance - 356°F (180°C)

50 ml Bottle..... P/N 15-02633 ..... **\$21.50**

## LOCTITE 480 INSTANT ADHESIVE TOUGHENED



Henkel Loctite 480 Prism is a low viscosity, rubber toughened instant adhesive with increased flexibility and peel strength along with enhanced resistance to shock. It is designed for bonding OEM assembly metal, rubber and select plastics.

20 g Bottle ..... P/N 15-09283 ..... **\$66.11**

## LOCTITE 574 FLANGE SEALANT



Loctite® 574™ Flange Sealant seals close fitting joints between rigid metal faces and flanges. Because it is fast curing, it provides resistance to low pressures immediately after assembly of flanges.

50 ml Bottle..... P/N 15-02629 ..... **\$24.85**

## LOCTITE 603 RETAINING COMPOUND



LOCTITE ® 603 is for the bonding of cylindrical fitting parts, particularly where consistently clean surfaces cannot be assured. The product cures when confined in the absence of air between close fitting metal surfaces and prevents loosening and leakage from shock and vibration. Typical applications include retaining roller bearings or oil impregnated bushings into housings.

10 ml Bottle..... P/N 15-02634 ..... **\$36.67**



## LOCTITE 8151 ANTI SEIZE

LOCTITE LB 8151 is a heavy-duty anti-seize spray designed to prevent joints from seizing and corroding when exposed to high temperatures such as encountered in the exhaust from combustion engines and in fittings for oil and gas burners. The product is typically used in applications with an operating temperature range of -30 °C to +900 °C.

50 mL Bottle ..... P/N 15-00479 ..... **\$31.17**



## SOFLEX TOPAS NB 5051 GREASE 400 GRAM CARTRIDGE

ISOFLEX TOPAS NB 5051 is a beige-colored, homogeneous, short-fibred long-term grease for a wide service temperature range. It is a dynamically light grease consisting of synthetic hydrocarbon oil and barium complex soap. The barium complex soap used is not classified as harmful under the EU Directives on dangerous substances.

400 Gram Cartridge..... P/N 15-08430 ..... **\$186.75**



## ROTAX 297-433 MOLYKOTE G-N, SLIDE PASTE

297-433 Moly-Kote GN Assembly Paste.

80 g Tube ..... P/N 15-00478 ..... **\$97.56**



## HENKEL LOCTITE 5910

Henkel Loctite 5910 is a one component RTV silicone designed for applications where good oil resistance and ability to withstand high joint-movement is required.

300 mL Cartridge ..... P/N 15-0726 ..... **\$54.95**



## WACKER® SILICON-HEAT COMPOUND P 12

Pure white, soft consistency, heat sink paste with marked thermal conductivity. Electrically insulating tolerance.

P/N 15-02540 ..... **\$164.50**



## ROTAX 297-386 SILASTIC 732 RTV

297-386 RTV 732 Dow Corning Multi Purpose Sealant.

90 ml Tube ..... P/N 15-00475 ..... **\$53.19**



## CRC MULTI-PURPOSE SUPER WHITE GREASE

A high purity, NLGI Grade 2 multi-purpose white lithium grease. Provides superior lubrication & durability in any weather and most temperatures. Bright white in color. Ideal for when appearance is important.

14 Oz Tub ..... P/N 15-06285 ..... **\$9.95**

SEE [WWW.CPS-PARTS.COM](http://WWW.CPS-PARTS.COM) FOR ADDITIONAL LUBRICANTS