

CLAMPS - TUBING - HOSES



MS21919 DG & WDG CLAMPS

Loop-type cushioned aluminum alloy clamp. Cushion (non-fuel resistant) is bonded to inner surface and edges of clamp. WDG clamps are cushion wedge type. Cushion assures tight fit and eliminates vibration, thus preventing line abrasion.

Tube Dia.	Dash No.	Price Each	Dash No.	Price Each	Tube Dia.	Dash No.	Price Each	Dash No.	Price Each
1/8	DG2	\$0.53	WDG2	\$0.47	1-5/16	DG21	\$1.65	WDG21	\$1.71
3/16	DG3	\$0.41	WDG3	\$0.47	1-3/8	DG22	\$1.58	WDG22	\$1.28
1/4	DG4	\$0.25	WDG4	\$0.52	1-7/16	DG23	\$2.73	WDG23	\$1.63
5/16	DG5	\$0.26	WDG5	\$0.52	1-1/2	DG24	\$1.33	WDG24	\$1.23
3/8	DG6	\$0.26	WDG6	\$0.56	1-9/16	DG25	\$2.60	WDG25	\$2.27
7/16	DG7	\$0.52	WDG7	\$0.59	1-5/8	DG26	\$1.99	WDG26	\$1.91
1/2	DG8	\$0.30	WDG8	\$0.56	1-3/4	DG28	\$1.45	WDG28	\$1.89
9/16	DG9	\$0.59	WDG9	\$0.64	1-7/8	DG30	\$1.86		
5/8	DG10	\$0.37	WDG10	\$0.58	1-15/16	DG31	\$2.78		
11/16	DG11	\$0.75	WDG11	\$0.87	2	DG32	\$1.31		
3/4	DG12	\$0.40	WDG12	\$0.80	2-1/16	DG33	\$1.98		
13/16	DG13	\$0.76	WDG13	\$0.90	2-1/8	DG34	\$1.67		
7/8	DG14	\$0.67	WDG14	\$0.89	2-1/4	DG36	\$2.06		
15/16	DG15	\$1.03	WDG15	\$0.94	2-3/8	DG38	\$2.36		
1	DG16	\$0.54	WDG16	\$0.88	2-1/2	DG40	\$1.92		
1-1/16	DG17	\$1.15	WDG17	\$1.29	2-5/8	DG42	\$4.80		
1-1/8	DG18	\$1.12	WDG18	\$1.18	2-3/4	DG44	\$5.35		
1-3/16	DG19	\$1.59	WDG19	\$1.44	2-7/8	DG46	\$5.45		
1-1/4	DG20	\$1.29	WDG20	\$1.11	3	DG48	\$2.53		
-	-	-	-	-	3-1/8	DG50	\$4.75		

Less 15% in lots of 50. May be assorted.



QS 200 HOSE CLAMPS

Aero-Seal stainless steel clamps are for industrial & aircraft applications. This tangential worm-screw type clamp is for use on fuel, oil, air & coolant lines. The worm drive provides uniform clamping pressure without distorting hose. Attach by pushing housing snugly around the hose to desired position on the band—the threads of the worm screw will drop into slots. Tighten slotted head with screwdriver.

QS200 Dash No.	Dia. Range (In.)		Price Each	QS200 Dash No.	Dia. Range (In.)		Price Each
	Min.	Max.			Min.	Max.	
-06H	7/16	25/32	\$1.49	-44H	2-5/16	3-1/4	\$2.15
-08H	1/2	29/32	\$1.54	-48H	2-9/16	3-1/2	\$2.15
-10H	9/16	1-1/16	\$1.55	-52H	2-13/16	3-3/4	\$2.29
-12H	11/16	1-1/4	\$1.54	-56H	3-1/16	4	\$2.25
-16H	13/16	1-1/2	\$1.55	-60H	3-5/16	4-1/4	\$2.37
-20H	13/16	1-3/4	\$1.53	-64H	3-9/16	4-1/2	\$2.34
-24H	1-1/16	2	\$1.60	-72H	4-1/8	5	\$2.55
-28H	1-5/16	2-1/4	\$1.60	-80H	4-5/8	5-1/2	\$2.91
-32H	1-9/16	2-1/2	\$1.60	-88H	5-1/8	6	\$2.96
-36H	1-13/16	2-3/4	\$1.68	-96H	5-5/8	6-1/2	\$2.96
-40H	2-1/16	3	\$2.05	-	-	-	-

Less 15% in lots of 50. May be assorted.



SNAPPER CLAMPS

A quick ratchet closure provides specific take-up, eliminating excessive tightening which may mutilate the hose.

3/8" for 1/4" fuel line ... P/N 05-00940 \$0.29
1", for radiator hose P/N 05-00941 \$0.39

BING ALCOHOL RESISTANT FUEL LINE



This fuel line is blue in color and does not rot or deteriorate from the inside, clogging the carburetor or fuel system. It withstands 50 PSI and tensile strength is 8000 PSI. It is resistant to temperatures of -65° to 220°F without deterioration, features exceptional resistance to gasoline, oil, oxygen, and ozone, and has high elastic memory allowing use of Delrin or nylon barbed fittings in low pressure applications without the need for external clamps.

Description	ID	OD	Part No.	Price Per Ft.
Bing Alcohol Resistant Fuel Line	1/4	3/8	05-00500	\$2.65
Bing Alcohol Resistant Fuel Line	1/8	1/4	05-00560	\$1.98



SUPER HEAVY PULSE LINE

Super heavy wall clear polyurethane pulse line has an extra thick 3/32" wall that will not dampen crankcase pulse even on longer runs. Clear one piece urethane construction is not affected by fuel. Will not harden, crack, or become brittle with age. Can also be used as clear fuel line. Sold by the foot. Outside Diameter: 7/16". Inside Diameter: 1/4". Wall Thickness: 3/32".

P/N 15-06094..... \$4.60/ft.



CLEAR BLUE FUEL LINE

Polyether-based Polyurethane Tubing offers excellent resistance to chemicals, kinking, abrasion, hydrolysis, oxidation, and ozone exposure. Our Polyether-based Polyurethane tubing excels in maintaining exceptional flexibility, high-impact strength, and above average performance in cold temperature.

AP

O.D.	I.D.	Description	Part Number	Price Per Ft.
1/4"	1/8"	Clear Blue Polyurethane Fuel Line	15-04632	\$0.83
5/16"	3/16"	Clear Blue Polyurethane Fuel Line	15-04874	\$0.62
3/8"	1/4"	Clear Blue Polyurethane Fuel Line	15-04818	\$0.85

PARKER SUPER-FLEX FL FUEL LINE HOSE



Parker's fuel line hose includes a new thermoplastic barrier that helps protect our atmosphere from harmful hydrocarbons that escape through the carcass of ordinary fuel hose. This new hose surpasses all of CARB's stringent permeation requirements and is similar to SAE30R7 specifications. The Super-Flex FL hose also features an abrasion and weather resistant cover to help protect from external application abuse.

Approved for biodiesel fuels that meet ASTM D 6751 requirements per UL guidelines for Biodiesel compatibility. 4:1 Design factor

Tube: NBR with a thermoplastic barrier

Cover: Black Hypalon

Reinforcement: Braided Polyester

Temperature Range: -30°F to +257°F (-34°C to +125°C)

Part No.	ID (in.)	Reinf. Braids	OD (in.)	OD (mm)	Approx. wt. per 100 ft.	Min. Bend Rad.	Max Rec. WP	Price Per Ft.
05-03597	1/4	1	0.500	12.7	9.7	-	100	\$2.90
05-03598	3/8	1	0.625	15.9	1.30	-	100	\$4.70
05-07223	5/16	1	0.0562	14.3	11.3	-	100	\$3.50

MIL-DTL 6000D OIL AND COOLANT HOSE



Inside and out, aircraft hose MIL-DTL 6000D is designed to handle the effects of oil, alcohol, coolant, and water. The tube is oil resistant with a black cover reinforced with high strength mildew resistant yarns. It withstands extreme temperature conditions from -40F to +250F. Meets or exceeds U.S. military specs. Lightweight, flexible and easy-to-handle, making it the perfect hose for hard-to-get-to spots in tight engine compartments. Sold in one foot increments.

Max Length:10FT

MIL-DTL-6000C was superceded by this MIL-DTL-6000D

Note: This hose is not recommended for use as fuel lines.

Part No.	Hose Dimensions		Burst Pressure (PSI)	Wt./ Ft. (Lb.)	Price Per Ft.
	I.D. (In.)	O.D. (In.)			
6000-4	1/4	5/8	1,000	.14	\$6.75
6000-5	5/16	11/16	1,000	.16	\$6.90
6000-6	3/8	3/4	1,000	.18	\$7.50
6000-8	1/2	7/8	1,000	.22	\$7.85
6000-10	5/8	1	1,000	.26	\$8.50
6000-12	3/4	1-1/8	1,000	.27	\$9.95
6000-14	7/8	1-1/4	1,000	.32	\$11.50
6000-16	1	1-3/8	1,000	.38	\$10.95

MIL-DTL 6000D HOSE AVAILABLE IN 10 FT MAXIMUM LENGTHS

MIL-H-6000 IS SUPERCEDED BY MIL-DTL-6000C

NOT RECOMMENDED FOR FUEL LINES