



HIGH VISIBILITY CUT LEVEL 1 POLYURETHANE DIPPED GLOVES

BETTER FIT

EN388



3121A



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

**SMARTWIPE™ Touch
Screen Compatible
Palms & Fingertips**

**Polyurethane
Grip**



**High Dexterity
Fingertips**

Breathable Back

**Color-Coded Bands
Easy cut level
identification**

SPECIFICATIONS	
Gauge	15
Liner Material	Polyester Blend Knit
Dip Material	Polyurethane
Cuff Style	Elasticated Knit

RECOMMENDED APPLICATIONS
<ul style="list-style-type: none"> High Dexterity Applications Light Material Handling Finish Carpentry Yard Maintenance Plumbing

CARE INSTRUCTIONS
Machine wash warm water (105°F), mild detergent, no bleach. Line dry.

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-8910	48-73-8910B
M	48-73-8911	48-73-8911B
L	48-73-8912	48-73-8912B
XL	48-73-8913	48-73-8913B
XXL	48-73-8914	48-73-8914B

**SEE
MORE
PPE**



or visit <https://qr.mke.tl/2qm6s>



Milwaukee®

... components.
... connections. Never over-tighten
... may be damaged by contacting products containing
... compatible chemicals. Verify products are chemically compatible
... with ABS/PVC/CPVC.
For important safety and installation information,
call 800 438-6091 or consult 24-hour
fax on demand number 800 745-9382.



9" / L
28-73-85/12

Milwaukee®
CUT LEVEL 1
S1405WPF
CE
EN 388
A
B