

# PRODUCT DATA SHEET

# PTC-2002 ALL PURPOSE CLEANER PTI CLEANER SERIES

### **DESCRIPTION**

Aircraft All Purpose Cleaner (APC) is a versatile cleaner for aircraft exterior and interiors. It is designed to clean and remove traffic film, hydraulic fluid, jet exhaust, oil and grime. Aircraft APC does not contain harsh caustic ingredients or any solvents. It is a zero VOC product is biodegradable and exceeds all environmental regulations in the U.S., European Community and Japan. Aircraft APC uses a unique surfactant technology that cleans the surface, but does not emulsify the grease. This is important for use with water clarifiers and other water treatment equipment.

#### **COLORS**

This cleaner is available in yellow.

## COATING PROPERTIES & CHARACTERISTICS

Odor	None
PH	9-10
Flammable	Non-Flammable
Biodegradable	Yes
Weight (Pounds per gallon)	8.6 lbs
Solvents	No organic or inorganic solvents
Carcinogenic	No
Hazardous Air Pollutants	None
VOC	0 g/l
Specifications	Mil PRF-85570D Type II

## SHELF LIFE

Shelf life is only applicable for materials stored in unopened and undamaged original factory filled containers. 1 year when stored between 50°-85° Fahrenheit.

#### MIXING/APPLICATION INSTRUCTIONS

- 1. Dilute product before use. For heavy duty degreasing / cleaning, dilute 4 parts water to 1 part product.
- 2. For Medium Duty Cleaning, dilute 10 parts water to 1 part product
- 3. For Light Duty Cleaning, dilute up to 30 parts water to 1 part product.
- 4. Product also works great through pressure washers / steam cleaners. Dilute with at least 10 parts water when using with these machines.
- 5. Spray product onto surface. Scrub with a soft brush. Rinse with water

PTC-2002\_PDS\_Rev. 01 11/6/2012



# PRODUCT DATA SHEET

NOTE: Application of PTI products requires the use of all OSHA approved safety equipment, including proper ventilation. Additionally, PTI products require the recommended temperature/humidity conditions and film thickness ranges for optimal performance. The material, hangar, and aircraft skin temperatures should be no lower than 75° F / 25° C before, during and after application.

# HEALTH, SAFETY, & STORAGE REQUIREMENTS

Refer to each individual material SDS (Safety Data Sheet) for specific requirements on the health, safety, storage and handling requirements. Follow all local, state, and national regulations during surface preparation, material application and cleanup.

## **PRODUCT INFORMATION & DISCLAIMER**

Product Data Sheets are periodically updated to reflect new information. It is important to use the latest and most recent revision for the product being used. The foregoing information is accurate to the best of our knowledge. However, due to differences in customer handling, use and method of application which are not known and are beyond our control, Products Techniques, Inc. makes no warranties as to the end result.

PTC-2002\_PDS\_Rev. 01 11/6/2012