




# 85 DZUS® Studs


## H Head Styles - Tool Actuated

Oval Slot




## H Head Styles - Hand Actuated

Wing



## Stud Panel Preparation

Prepare Hole



## Part Number Selection

### H Head style

- 11 Oval slot
- 12 Wing head

### K Length

Enter number from selection table below

85 - H - K - M

### M Material

- 16 Steel, zinc plated
- 20 Stainless steel (not available in tool head recess head style)

Stud Length Table			
C		K	U
TMT Range For: All other receptacles			
Min.	Max.		
2.3 (.090)	2.8 (.110)	100	5.2 (.205)
2.8 (.110)	3.3 (.130)	120	5.7 (.225)
3.3 (.130)	3.8 (.150)	140	6.2 (.245)
3.8 (.150)	4.3 (.170)	160	6.7 (.265)
4.3 (.170)	4.8 (.190)	180	7.2 (.285)
4.8 (.190)	5.3 (.210)	200	7.7 (.305)
5.3 (.210)	5.8 (.230)	220	8.3 (.325)
5.8 (.230)	6.3 (.250)	240	8.8 (.345)
6.4 (.250)	6.9 (.270)	260	9.3 (.365)
6.9 (.270)	7.4 (.290)	280	9.8 (.385)
7.4 (.290)	7.9 (.310)	300	10.3 (.405)
7.9 (.310)	8.4 (.330)	320	10.8 (.425)
8.4 (.330)	8.9 (.350)	340	11.3 (.445)
8.9 (.350)	9.4 (.370)	360	11.8 (.465)
9.4 (.370)	9.9 (.390)	380	12.3 (.485)
9.9 (.390)	10.4 (.410)	400	12.8 (.505)