




10' THROTTLE OR CHOKE INNER WIRE

Measures .064" (1.5mm) diameter 1 x 19 construction. #7417 solder swage factory installed on one end only. Includes 1 @extra #7417 and #7415 swages loose in package. Ideal for Bing or Mikuni Carbs. #7417 swage fits Carb slide or choke plunger perfectly. Length 120".
P/N 7407..... \$4.75



ROTAX 912-914 10' CHOKE WIRE

Measures .064" (1.5mm) diameter 1 x 19 construction. #7416 solder swage factory installed on one end only. Includes 1 @extra #7416 and #7415 swages loose in package. Ideal for Bing Carbs on 912 (order 2). #7416 swage fits 912-914 Carb choke arm perfectly.
P/N 7408..... \$6.50



THROTTLE AND CHOKE WIRE

Measures .064" (1.5mm) diameter 1 x 19 construction. Same as #7407. Ready to accept solder swage #7417. Fits inside either #7403 or #7405 housing. Sold by the foot or in 50' rolls.
P/N 7409..... \$0.45 ft.




THROTTLE HOUSING

For #7407 or #7411 inner wire. Rectangular chrome steel wire core with abrasion resistant black cover. Measures .190" (5mm) od. by .090" i.d. Our most popular housing for throttle and chokes. Sold by the foot.
P/N 7403..... \$0.85 ft.




HEAVY-DUTY THROTTLE HOUSING

For #7407 or #7409 inner wire. Rectangular chrome steel core with nylon inner liner. Abrasion resistant black cover. Measures .215" (5.5mm) od. by .086" i.d. Sold by the foot.
P/N 7405..... \$1.65 ft.



STEEL FERRULE

Slips over #7403 throttle housing. Can be crimped or rolled for a permanent installation. .220" od. by .445" long. Drilled for .064" wire.
P/N 7413..... \$0.75



STEP-DOWN STEEL END FERRULE

For use with #7405 heavy-duty housing. Small end fits all other fittings. Can be crimped or rolled for a permanent installation. Measures .787" long. Drilled for .064" wire.
P/N 7414..... \$0.99




1/16" STOP SWAGE

For use with #7407 or #7411 Control wire. Can be installed with standard swaging tools. Made of a compressible copper alloy. Will not fit Card slide or choke plunger when swaged. See part #7417.
P/N 7415..... \$0.38




SOLDER POT

used for installing #7417 solder swages or any connector that needs to be dipped soldered. Just flux line with swage installed and dip for 10 seconds. Includes 48" 110 volt power cord. Draws under 250 watts. A must for the serious homebuilder.
P/N 7425..... \$249.95




1/16" SOLDER STOP SWAGE

For use with #7407 or #7411 inner control wire. Must be properly peened and dip soldered to create a secure bond. Requires solder pot, etc. for installation. See P/N 7425 above. Fits Mikuni and Bing Carb slides and choke plungers perfectly.
P/N 7417..... \$0.55




582-618 OILER SWAGE

Fits the oil injection pump arm precisely. .250" od. x .360" length. Drilled for #7411 inner wire.
P/N 7416..... \$0.85




503 OILER SWAGE

Fits the oil injection pump arm precisely. 5/16" od. x 3/8" length. Drilled for #7411 inner wire.
P/N 7418..... \$1.39



WIRE STOP

Is ideal for securing cable ends. Removable and completely reusable. For use on any size cable up to 3/32". Measures 1/4" OD x 6x32 threads x 3/8" long.
P/N A2360..... \$0.85



WIRE SWIVEL

The same as above with end collar. Ideal swiveling anchor for brake or throttle cables up to 3/32" Measures 1/4" OD x 6x32 threads x 1/4" long.
P/N A2361..... \$0.75



MIDWAY CABLE ADJUSTER

For use the #7403 cable housing. Measures 2.75" but extends to 3.375" to remove slack from cable housing. Positive locking nut maintains adjustment.
P/N 7421..... \$5.75




CABLE ADJUSTER BULKHEAD

Adjuster accepts either #7403 or #7405 housing with ferrule installed. Used where cable meets oil injection pump or where an adjustable end is needed. Includes extra locking nut. Measures 1.675" long.
P/N 8121..... \$3.85



BAR SOLDER

1 1/2 lbs. of the finest solder available to secure end fittings. Enough to last for years.
P/N 7427..... \$60.00



CABLE FLUX

For soldering cables. 3 oz. bottle enough for up to several hundred cables.
P/N 7429..... \$16.50