

OIL ACCESSORIES – OIL

SPOUT DUST COVERS

Spout Covers for OPW 295 Series. D Spout Cover/Dust Cover. Colors available are red, black and blue.



Round			
Size	Color	Part No.	Price
1"	Red	08-13555	\$18.50
1"	Black	08-13556	\$18.50
1"	Blue	08-13557	\$19.75
1.5"	Red	08-13558	\$18.65
1.5"	Black	08-13559	\$20.50
1.5"	Blue	08-13560	\$20.50
Rectangular			
Size	Color	Part No.	Price
1.5"	Red	08-13552	\$26.50
1.5"	Black	08-13553	\$19.75
1.5"	Blue	08-13554	\$26.50

NO SPILL OIL SPOUT™ WITH ON-OFF VALVE

Patented On/Off valve. Adjustable flow. No-mess... No-spill. Rev. B 3-11 P/N 14-00024 **\$6.95**



SUPER FLEXI-SPOUT

Works great for hard to reach areas. Dual threading fits most sized containers. Perfect for adding motor oil, anti-freeze, transmission and windshield washer fluid.

P/N 14-00707 **\$3.75**

OIL BUDDY (NO SPILL)

For do it yourself oil changes or refilling small tanks in lawn mowers, snowblowers and chainsaws, Oil Buddy is your best tool. Eliminating the messy cleanup and spillage problems, Oil Buddy gets the job done fast and easy without getting your clothes dirty. For small fill ups, the Oil Buddy screws onto the head of the oil container and can be left there for further use if the bottle is still partially full. When the valve is closed, oil can't get out and dirt can't get in. Even if the oil container gets knocked over, no spillage will occur. Fits most 1-Quart /1-Litre bottles. P/N 13-03144 **\$2.75**



EVANS NPG + COOLANT FOR ROTAX ENGINES

NPG+ is new coolant providing dramatic improvements in heat transfer and viscosity that make the new fluid a "pour-in," not requiring changes to cooling system components. NPG+ waterless coolant virtually eliminates boil over in gasoline or diesels - the waterless coolant allows engines to tolerate running hotter, without boiling over, and allows the cooling system to run at very low or no pressure. Because there is no water in the system engines operating with NPG+ will be free from corrosion and electrolysis, and the engines will run well no matter how hard they are driven or how hot or cold the environment is. Specified coolant for Rotax Aircraft Engines, Type 912 and 914 (series). P/N 08-04535 **\$45.52**



EVANS PREP FLUID

Evans Waterless Flush is used when systems cannot be drained properly of all the conventional water and anti-freeze. Suggested to be used with experimental aircraft conversion and all motorcycle, ATV and import cars. Not intended to be used as a coolant.

P/N 08-04534 **\$31.96**

SHELL DEXCOOL® ANTIFREEZE / COOLANT

Single-phase, ethylene glycol based, extended life, universal automotive engine coolant. Suitable for a five year or 150,000 mile service life in automotive applications. It meets GM6277M-General Motor's Extended Life Coolant specification and will provide effective, long term corrosion protection for critical engine metals.

P/N 15-05767 **\$24.50**

NEXT AIRCRAFT SERVICE DUE - STICKERS

Service reminder decal "NEXT AIRCRAFT SERVICE DUE" decal is black text on white semigloss background with "FILL IN" blanks. Removable decal is designed to adhere to any surface and not leave residue behind, perfect for aircraft rentals, owners, CFI's, trainers, service/repair stations, POH, log books, instrument panels, windows. Decal measures 3" x 3".

P/N 09-02137 **\$0.45**



OIL INJECTION / WATER OVERFLOW RESERVOIRS



Constructed of high density polyethylene, these blow molded multi-purpose tanks offer excellent durability and resistance to most chemical and fluids. Express service tanks come with a cap and straight fittings. All tanks come with a 2-1/4" buttress thread cap and a straight fitting which fits a 1/4" hose. All sizes nominal. Height includes neck & fittings. Width includes mounting tabs. Max working temperature is 180-deg F and max working pressure is 5 PSI. 1 Quart 6.21" x 7.74" x 3.62" **Includes 1/4" barb spigot molded on bottom** P/N 15-06828 **\$28.50**
1.5 Quart 7.71" x 7.74" x 3.62" P/N 15-06830 **\$12.75**
2 Quart 7.04" x 8.632" x 4.173" P/N 15-06936 **\$22.85**
4 Quart 11.652" x 8.632" x 4.173" P/N 15-04841 **\$22.00**

Accessories

Reservoir Tank Cap with Seal - 2-1/4" P/N 15-05092 **\$3.65**
Nylon Vented Cap - 2-1/4" P/N 15-06936-1 **\$3.60**
Oil Water Reservoir Only P/N 15-06936-2 **\$19.65**

FORM-A-FUNNEL®

Aviation Funnel, go with the flow. When you need to get into a tight, hard to reach place or require extra length, the Aviation model (29" x 5") is the tool for the job.

Thick, pliable nitrile rubber coating completely encases a thin, bendable layer of aluminum alloy that resists wear.

Reshape and reuse it over and over.

Edges can be molded around filters or drains to create a leak-proof seal.

Keeps oil off of engines, frames and surrounding parts.

Highly compatible with common automotive fluids.

Works in temperatures from -30F° to 425F°.

Cleans easily with cleaners and degreasers.

Aviation Funnel (29" x 5") P/N 12-03148 **\$34.99**
General Purpose Funnel (14.5" x 6.5") P/N 12-03147 **\$21.99**
General Purpose Kit (14.5" x 6.5" & 9" x 4.75") P/N 12-04819 **\$33.00**



ROTELLA OIL 15W-40

Shell ROTELLA® T SAE 15W- 40 is a leader in meeting leading OEM specifications, as well as the enhanced oil performance requirements for API CI - 4 PLUS, Caterpillar ECF-1, Mercedes-Benz 228.3, Cummins CES 20078, Detroit Diesel 93K214, Mack EO-N Premium Plus 03, Mercedes-Benz 228.3, and Volvo VDS-3, and meets the warranty requirement of all major diesel engine manufacturers. P/N 15-05767 **\$24.50**



MOBIL 1 4T MOTORCYCLE OIL

Mobil 1 Racing 4T oil meets all the requirements for Rotax 4 stroke aircraft engines. This is a full synthetic oil designed for motorcycles, however is an excellent choice for Rotax 4 stroke aircraft engines because of the gearbox and close internal tolerances. Mobil 1 Racing 4T has been fully tested, both on laboratory dynamometers and in the field, to help provide optimum horsepower and acceleration.

P/N 08-13892 **\$16.95**



SEAFOAM MOTOR TREATMENT SF-16

Sea Foam 16 oz. motor treatment for gas and diesel engines For use in gas, ethanol, diesel or biodiesel engines. Internal engine use only. Can be used in 2-cycle and 4-cycle engines.

•100% pure petroleum product. Works instantly to clean deposits from internal engine parts and remove moisture from oil crankcases and fuel tanks. As a fuel system additive, and an oil system additive. P/N 09-04615 **\$14.95**

