

FABRIC – TAPES

DACRON TAPE / PEEL PLY



A layer of 2.7 oz. Dacron fabric strips or tape laminated into a layup as if it were an extra ply of glass. The peel coat wets out with epoxy like glass cloth and cures along with the rest of the layup. However, the Dacron does not adhere structurally to the glass and when peeled away it

leaves a surface ready for glass-to-glass bonding without sanding. Requirements for Small Aircraft: For Experimental Aircraft. • 3 Rolls of 1" x 50 Yds. Tape • 2 Rolls of 2" x 50 Yds. Tape • 1 Roll of 3" x 50 Yds. Tape • 1 Roll of 4" x 50 Yds. Tape

Width 50 Yd Roll	Smooth Edge		Pinked	
	P/N 09-	Price/ Roll	P/N 09-	Price/ Roll
1"	15000	\$6.75	15450	\$6.75
2"	15100	\$13.50	15500	\$13.50
3"	15200	\$21.75	15600	\$19.50
4"	15300	\$28.50	15700	\$29.00
6"	15400	\$44.50	15800	\$41.50

Discount Schedule for Dacron Tapes: Less 10% for 12 Rolls (assorted) • Less 15% for 25 Rolls (assorted). Request quote on larger quantities.

DACRON FABRIC / FULL WIDTH PEEL PLY



Poly/Dacron blend is excellent as peel ply for composite lay-ups, and for covering experimental aircraft.

2.7oz. 63-66" #604 ... P/N 09-00300 ... \$5.35/yd.
1.9 oz. X 60-62" #611 P/N 09-00100 ... \$4.35/yd.
2.97 oz. X 62" #605 ... P/N 09-00500 ... \$4.35/yd.

DACRON BIAS TAPE FOR HOMEBUILT AIRCRAFT



Bias-cut tapes (weave 45° to edge) are especially useful for trimming compound curves on components such as wing tips and tail surfaces. Bias tape will stretch to conform to the contour without wrinkles, without heat-shrinking edges or cutting and notching to remove excess fabric. Stretching reduces the width about 35% so 3" tape should be used to finish areas normally covered with 2" tape. 2" Bias tape will pull to about 1-3/8" width.

2" x 50 Yd. Roll P/N 09-16300 \$27.75
3" x 50 Yd. Roll P/N 09-16400 \$59.75

NOT FOR USE ON CERTIFIED AIRCRAFT

COTTON REINFORCING TAPES



Tape	Size	Part No.	Price/Roll
DDD-T-86F	1/2" x 36 Yds.	09-17000	\$15.50

THREADS & CORDS



Only synthetic threads and rib lacing cords should be used with Dacron covering to insure uniform strength. Waxed linen rib cord Conforms to PMA# TQ0075NM and STC# SA1008WE.

Material	Quantity	Part No.	Price
Dacron Machine Sewing Thread	500 Yds.	09-03900	\$15.25
Dacron Hand Sewing Thread	250 Yds.	09-04000	\$12.00

SAIL FABRIC


#1003 Glacier White Sail Fabric. 54" wide. 4.1 oz. Color may vary from sample shown. Sold by the yard. Note: This fabric is for ultralight sails, and will not shrink.

Color	Part No.	Price
1003 Glacier White	15-04587	\$10.85
192 Lime Green	15-04588	\$16.50
196 Deep Purple	15-04589	\$11.95
197 Red	15-04590	\$15.80
201 Jet Black	15-04591	\$16.50
232 Hot Pink	15-04592	\$14.65
309 Emerald Green	15-04593	\$14.65
310 Royal Blue	15-04595	\$16.50
360 Key West Blue	15-04597	\$14.60
566 West Coast Gold	15-04598	\$14.60

FLORIAN PINKER



One continuous pinked edge while being comfortable for either right or left hand use. Light and compact for easy use and easy storage. Gives that "professional look" to your own creations and easily pink the most intricate patterns. Made in U.S.A. P/N 09-01400 \$77.50



DIAMOND BACK TAPE

Advantages: • Save TIME with easy installation • Save OPERATING COSTS with improved energy efficiency • Save REPAIR COSTS with long lasting quality at high temp • Save ON PRICE with quantity discounts

CHARACTERISTICS	
Fibers	Ceramic
Application	Insulation with bolt holes
Weave Style	Drop Warp
Thickness	.125 in
Bolt Diameter	Up to .75 in
Continuous Service	1,800°F
Maximum Use	2,300°F
Durability	High Strength
Coating	Plain or Vermiculite Avail.

Type	Width	Thickness	Roll Length	Part No.	Price
1/8" Thickness - Plain	2"	.125"	100ft.	05-03510	\$113.80
1/8" Thickness - Vermiculite Coated	2"	.125"	100ft.	05-03511	\$162.99

PANASONIC IRON MULTI DIRECTIONAL 360 DEGREE



New Concept 360° Quick Steam/Dry Iron with Curved Non-Stick Coated Titanium Soleplate, Multi-Directional Design with Added Steam Vents, 3-Way Auto Shut-Off, Adjustable Steam, Dial Temperature Control, "Stay Clean" Steam Vents and Anti-Drip System. Maximum Temperature 392F (200C). Controls: Choose Steam or Dry Operation: 4 Button Selector. Select "Extra" Jet-of-Steam: Left Pushbutton. Cool Water Spray or Mist: Right Pushbutton. P/N 09-03785.....\$78.90

FAB-TAC FABRIC CEMENT



A superior quality cement for strong splice joints. Use to cement tapes, rings and grommets to fabric cover.

1 Pint P/N 09-17800 \$12.90
1 Qt P/N 09-17900 \$17.75
1 Gal. P/N 09-18000 \$56.75

CLOTH MASKING TAPE



Has many uses in aircraft maintenance work. Strip over sharp corners under fabric. Strips on parts under doped fabric will prevent fabric from sticking to parts. Pressure-sensitive adhesive backing. Easily applied, easily removed. Leaves no residue. Should not be applied below 32°F.

1" x 60 yds. P/N 09-17100.....\$10.50

SOLDERING IRON



Use to melt drain holes and inspection rings in polyester fabric. 35 Watt, 900°F tip. Tip is replaceable & long life coated. P/N 09-37430 \$84.75

HEAVY-DUTY HEAT GUN



This soft air velocity of this heat gun increases the surface temperature to the required working temperature much faster than conventional heat guns and maintains a higher temperature for faster completion of the application. Features double insulation, two temperature selections of 570°F and 1000°F, and a unique impact resistant heating element. Operates on 120V AC at 11.6 amps. Air volume 14.8 cu. ft. per minute. Wt. 1-1/2 lbs. P/N 09-00354 \$99.75

POCKET THERMOMETER



This Pocket thermometer can eliminate 80% of your iron covering problems. These problems are caused by your iron's temperature varying as much as 60° while in use, which causes bubbles and sags. If you are using an iron other than Black Baron, this thermometer is a must in monitoring iron temperatures.

P/N 09-37500.....\$7.50

MAULE FABRIC TESTER



A fine quality tool to test fabric covered aircraft for minimum FAA requirements without removing or punching holes in fabric. Also used to test struts for inside rusting as required by FAA on all Piper aircraft with struts.

P/N 09-14900 \$449.00