

3M™ ABRASIVES - ADHESIVES



3M™ GREEN CORPS™ CUT OFF WHEEL

Wheel is designed to provide high cut rates and long life on most all materials including fiberglass, stainless steel, mild steel and aerospace alloys. Ideal for use on a wide variety of utility type cut off tools. Do not use on tools without guards.

ID	Size	Part No.	Price
01985	3"x1/32"x3/8"	09-01521	\$6.95
01994	4"x1/32"x3/8"	09-01524	\$5.30
82238	3"x1/32"x1/4"	09-01570	\$6.85
88755	4"x1/32"x1/4"	09-01580	\$5.55
01986 5 Pack	3"x1/16"x3/8"	09-01523	\$32.65

3M™ SCOTCH-BRITE™ DEBURRING WHEEL



Two Styles Available: Cut & Polish/Unitized Wheel-7A Medium grade (harder) Use to radius and deburr edges of aluminum parts. These wheels give a uniform brushed satin finish to parts and deburr quicker and easier than hand finishing. These wheels are discs of Scotch-Brite web compressed and bonded to form a rugged, dense wheel. Wheel size: 6" dia. x 1" wide x 1/2" thru hole.

P/N 12-00875\$88.75

Light Deburring Wheel-7S Fine Grade (Softer)

Light deburring 7S Fin 6 x 1 x 1. This wheel has a 1" thru hole. To fit 1/2" order P/N 12-01585.....P/N 12-00948\$77.75

3M Flange Adapter 3 45035 1/2".....P/N 12-01585\$5.35

3M™ ROLOC™ DISC PAD



3M™ Roloc™ Disc Pad TR 45092, Medium 3" 1/4-20 Internal. 3M™ Roloc™ Disc Pad optimizes the performance of Roloc™ discs and bristle discs by providing the right backup system and a secure attachment for grinding applications. Plus it saves time by eliminating the need to align edges of the disc with the disc

pad—the screw aligns the disc, making disc changes quick and easy. P/N 09-01554\$21.65

3M 5 INCH 80 GRIT SANDING DISC



3M SandBlaster 5" 8 Hole Sanding Disc. 80 grit disc, designed for moderate stripping and surface leveling. Premium Cubitron™ ceramic mineral. Clog-resistant. Designed for use on random orbital sanders. Stays significantly sharper longer to sand faster than 3M conventional sandpaper of comparable grit. Use on wood, oil enamel, latex primer, lacquer, sanding sealer and other coatings.

P/N 09-05427\$1.33

3M™ REPOSITIONABLE 75 SPRAY ADHESIVE



3M™ Repositionable 75 Spray Adhesive is a versatile pressure sensitive adhesive spray, suitable for temporary holding or positioning of lightweight materials for display or prior to final assembly. It adheres in seconds, yet has an extra-long tack range that allows lifting and repositioning of materials.

P/N 09-01377\$22.50

3M™ SCOTCH-WELD™ URETHANE ADHESIVE DP601/ DP601NS



3M™ Scotch-Weld™ DP601 is a self-leveling, gray, rapid setting, two-component polyurethane adhesive. It is packaged as 1:1 ratio liquids in duo-pak cartridges. With the squeeze of the trigger, the components are automatically mixed and easily dispensed as a bubble-free liquid. DP601NS is the same as the DP601 except it is a non-sag, gray, rapid setting, two-component polyurethane adhesive.

Description	Size	Color	Part No.	Price
DP601NS (Non-Sag)	50 mil	Gray	09-01412	\$14.95



3M™ HI-STRENGTH 90 SPRAY ADHESIVE

3M™ Hi-Strength 90 Spray Adhesive is a fast-drying, transparent spray adhesive that bonds on concrete, wood, MDF, laminates, polyethylene and more. Its extremely strong bond gives you fast results to keep projects moving forward. This industrial grade formula is easy to dispense and apply directly to surfaces and materials and provides the added benefit of high heat and moisture resistance.

Size	Part No.	Price
24 oz	09-01376	\$22.50



3M™ SCOTCH-WELD™ EPOXY ADHESIVE DP125 DUO-PAK

Two-part epoxy adhesive with a 1:1 mix ratio, 25 minute work life and exhibits very high peel strength. Moderately flexible and the gray version has exceptional shear adhesion. Use to bond rubber, metal, wood, plastics, and masonry products.

Size	Color	Part No.	Price
1.7 oz	Gray	09-01403	\$26.50
1.7 oz	Translucent	09-01402	\$26.50



3M™ SCOTCH-WELD™ EPOXY ADHESIVE DP100 PLUS

Exhibits much higher shear and peel strengths compared to DP100 Adhesive. It has a 1:1 mix ratio, a 4 minute work life, and is slightly flexible when cured. Clear in color. 1.7 oz. package.

P/N 09-01401\$23.65

3M™ SCOTCH-WELD™ EPOXY ADHESIVE DP190 DUO-PAK



A flexible, two-part adhesive that cures at room temperature and provides high strength bonds with good performance in shear and peel. Can be used to bond rubber, metal, wood, most plastics, and masonry products.

Size	Color	Part No.	Price
1.7 oz	Gray	09-01375	\$23.65

3M™ SCOTCH-WELD™ EPX™ PLUS II APPLICATOR



This Plunger is for the Scotch-Weld™ EPX™ Plus II Applicator. The Scotch-Weld™ EPX™ Plus II Applicator is used to Dispense 3M™ Scotch-Weld™ Adhesives in Duo-Pak Cartridges. The applicator is a low-cost portable, self contained metering, mixing and dispensing machine that simultaneously meters and mixes two-part adhesives as the material is applied.

50 mL Mixing Nozzle 9742 P/N 09-01372\$2.67

3M™ SCOTCH-WELD™ EPX™ APPLICATOR NOZZLE



Applicator nozzle designed for both the 200 mL and 400 mL applicators. P/N 09-01408\$3.70

3M™ HEADLIGHT LENS RESTORATION SYSTEM



With the 3M™ Headlight Lens Restoration System, you will use a 1200-1600 rpm drill equipped with a backup pad and sanding discs to remove the yellowed layer from the headlight lens surface. A higher rpm drill could generate excessive heat and can cause damage to the headlight lens that is difficult to remove. A lower rpm drill does not work efficiently for this process. Two sanding steps will follow to refine or reduce the sand scratches that are made when removing the yellowed layer. Finally, 3M™ Headlight Lens Polish and a foam pad will remove the fine scratches and put the final clarity on the headlight lens. Kit Includes: 1 - Disc Pad Holder 1 - 3M™ Soft Interface Pad 6 - 3M™ Sanding Discs 4 - 3M™ Finishing Discs 1 - 3M™ Trizact™ Disc 1 - 3M™ Headlight Lens Polish, 1oz 1 - Buffing Pad 1 - Step by Step Directions

P/N 09-02109\$19.90

CS