


MACHINE SCREWS

MS24693 & MS24693C MACHINE SCREWS



FORMERLY AN 507) - These non-structural screws have a 100° countersunk flat head. Cadmium plated, Type 2, Class 3. Tensile strength 55,000 PSI. For both CAD plated and Stainless MS24693C are stainless steel.

| Thread | Length | MS24693 Cad Plated P/N | Price Each | MS24693C Stainless P/N | Price Each | |
|--------|--------|---------------------------|-------------|---------------------------|-------------|--------|
| 4-40 | 3/8 | MS24693S4 | \$0.05 | MS24693C4 | \$0.04 | |
| | 7/16 | MS24693S5 | \$0.05 | --- | --- | |
| | 1/2 | MS24693S6 | \$0.05 | MS24693C6 | \$0.05 | |
| | 5/8 | MS24693S7 | --- | MS24693C7 | \$0.06 | |
| | 1 | MS24693S10 | \$0.11 | MS24693C10 | \$0.08 | |
| 6-32 | 1/4 | MS24693S24 | \$0.05 | MS24693C24 | \$0.04 | |
| | 3/8 | MS24693S26 | \$0.05 | MS24693C26 | \$0.06 | |
| | 7/16 | MS24693S27 | --- | MS24693C27 | \$0.05 | |
| | 1/2 | MS24693S28 | \$0.06 | MS24693C28 | \$0.06 | |
| | 5/8 | MS24693S29 | \$0.07 | MS24693C29 | \$0.08 | |
| | 3/4 | MS24693S30 | \$0.06 | MS24693C30 | \$0.08 | |
| | 7/8 | MS24693S31 | \$0.08 | --- | --- | |
| 8-32 | 1 | MS24693S32 | \$0.09 | MS24693C32 | \$0.09 | |
| | 1-1/2 | MS24693S36 | \$0.17 | --- | --- | |
| | 2 | MS24693S40 | \$0.21 | --- | --- | |
| | 1/4 | MS24693S46 | \$0.06 | MS24693C46 | \$0.09 | |
| | 3/8 | MS24693S48 | \$0.06 | MS24693C48 | \$0.09 | |
| | 7/16 | MS24693S49 | --- | MS24693C49 | \$0.09 | |
| | 1/2 | MS24693S50 | \$0.07 | MS24693C50 | \$0.09 | |
| | 5/8 | MS24693S51 | \$0.06 | MS24693C51 | \$0.09 | |
| | 3/4 | MS24693S52 | \$0.06 | MS24693C52 | \$0.10 | |
| | 7/8 | MS24693S53 | \$0.08 | --- | --- | |
| | 1 | MS24693S54 | \$0.09 | MS24693C54 | \$0.13 | |
| | 1-1/4 | MS24693S56 | --- | MS24693C56 | \$0.17 | |
| | 1-1/2 | MS24693S58 | \$0.15 | --- | --- | |
| | 2 | MS24693S62 | \$0.35 | --- | --- | |
| | 10-32 | 1/4 | MS24693S268 | \$0.08 | MS24693C268 | \$0.12 |
| | | 3/8 | MS24693S270 | \$0.07 | MS24693C270 | \$0.09 |
| 7/16 | | MS24693S271 | --- | MS24693C271 | \$0.10 | |
| 1/2 | | MS24693S272 | \$0.09 | MS24693C272 | \$0.12 | |
| 5/8 | | MS24693S273 | \$0.09 | MS24693C273 | \$0.14 | |
| 3/4 | | MS24693S274 | \$0.11 | MS24693C274 | \$0.14 | |
| 1 | | MS24693S276 | \$0.14 | MS24693C276 | \$0.18 | |
| 1-1/4 | | MS24693S278 | --- | MS24693C278 | \$0.22 | |
| 1-1/2 | | MS24693S280 | \$0.16 | --- | --- | |
| 2 | | MS24693S284 | \$0.44 | --- | --- | |
| 2-1/2 | | MS24693-S286 | \$0.60 | --- | --- | |
| 1/4-28 | | 7/16 | --- | --- | MS24693C293 | \$0.26 |
| | 1/2 | MS24693S294 | --- | MS24693C294 | \$0.27 | |
| | 5/8 | MS24693S295 | --- | MS24693C295 | \$0.24 | |
| | 3/4 | MS24693S296 | \$0.16 | --- | --- | |
| 1 | --- | --- | MS24693C298 | \$0.39 | --- | |

AN525 WASHER HEAD SCREWS



High-strength machine screws fabricated from alloy steel per specification AMS6300. Tensile strength 125,000 PSI. Cadmium plated per QQ-P-416, Type II, Class 3. Cross-recessed head.

| Dash No. | Length in. | Grip in. | Thread Size | Price |
|----------------------|------------|----------|-------------|--------|
| AN525-832R4 | 1/4 | 1/32 | 8-32 | \$0.19 |
| AN525-832R5 | 5/16 | --- | 8-32 | \$0.09 |
| AN525-832R6 | 3/8 | 1/32 | 8-32 | \$0.10 |
| AN525-832R7 | 7/16 | 1/16 | 8-32 | \$0.12 |
| AN525-832R8 | 1/2 | 1/8 | 8-32 | \$0.13 |
| AN525-832R9 | 9/16 | 5/32 | 8-32 | \$0.17 |
| AN525-832R10 | 5/8 | 7/32 | 8-32 | \$0.16 |
| AN525-832R11 | 11/16 | 9/32 | 8-32 | \$0.12 |
| AN525-832R12 | 3/4 | 11/32 | 8-32 | \$0.15 |
| AN525-832R14 | 7/8 | 15/32 | 8-32 | \$0.20 |
| AN525-832R16 | 1 | 19/32 | 8-32 | \$0.17 |
| AN525-832R18 | 1-1/8 | 23/32 | 8-32 | \$0.26 |
| AN525-832R20 | 1-1/4 | 27/32 | 8-32 | \$0.24 |
| AN525-832R22 | 1-3/8 | 31/32 | 8-32 | \$0.23 |
| AN525-832R24 | 1-1/2 | 1-3/32 | 8-32 | \$0.35 |
| AN525-8R9 | 9/16 | 5/32 | 8/36 | \$0.17 |
| AN525-10R4 | 1/4 | --- | 10-32 | \$0.12 |
| AN525-10R5 | 5/16 | --- | 10-32 | \$0.13 |
| AN525-10R6 | 3/8 | 1/32 | 10-32 | \$0.14 |
| AN525-10R7 | 7/16 | 1/16 | 10-32 | \$0.12 |
| AN525-10R8 | 1/2 | 1/8 | 10-32 | \$0.16 |
| AN525-10R9 | 9/16 | 5/32 | 10-32 | \$0.15 |
| AN525-10-9 (Slotted) | 9/16 | 5/32 | 10-32 | \$0.17 |
| AN525-10R10 | 5/8 | 7/32 | 10-32 | \$0.16 |
| AN525-10R11 | 11/16 | 9/32 | 10-32 | \$0.16 |
| AN525-10R12 | 3/4 | 11/32 | 10-32 | \$0.15 |
| AN525-10R14 | 7/8 | 15/32 | 10-32 | \$0.23 |
| AN525-10R16 | 1 | 19/32 | 10-32 | \$0.19 |
| AN525-10R18 | 1-1/8 | 23/32 | 10-32 | \$0.34 |
| AN525-10R20 | 1-1/4 | 27/32 | 10-32 | \$0.30 |
| AN525-10R22 | 1-3/8 | 31/32 | 10-32 | \$0.28 |
| AN525-10R24 | 1-1/2 | 1-3/32 | 10-32 | \$0.29 |
| AN525-416R6 | 3/8 | 1/32 | 1/4-28 | \$0.58 |
| AN525-416R7 | 7/16 | 1/16 | 1/4-28 | \$0.52 |
| AN525-416R8 | 1/2 | 1/8 | 1/4-28 | \$0.54 |
| AN525-416R9 | 9/16 | 5/32 | 1/4-28 | \$0.54 |
| AN525-416R10 | 5/8 | 7/32 | 1/4-28 | \$0.49 |
| AN525-416R12 | 3/4 | 11/32 | 1/4-28 | \$0.56 |
| AN525-416R14 | 7/8 | 15/32 | 1/4-28 | \$0.76 |
| AN525-416R16 | 1 | 19/32 | 1/4-28 | \$0.63 |
| AN525-416R18 | 1-1/8 | 23/32 | 1/4-28 | \$1.39 |
| AN525-416R20 | 1-1/4 | 27/32 | 1/4-28 | \$1.43 |


AN526 MACHINE SCREWS

Truss-head non-structural machine screws made of carbon steel, cadmium plated. Minimum tensile strength 55,000 PSI. Available in slot head or Phillips recessed head.

| Thread | Length | Phillips Part No. | Price Ea. | Slotted Part No. | Price Ea. |
|--------|---------------|-------------------|-------------|------------------|-----------|
| 4-40 | 1/4 | AN526-440R4 | \$0.20 | ---- | --- |
| | 3/8 | AN526-440R6 | \$0.07 | ---- | --- |
| | 1/2 | AN526-440R8 | \$0.06 | ---- | --- |
| | 5/8 | AN526-440R16 | ---- | ---- | --- |
| | 1 | AN526-632R4 | \$0.05 | ---- | --- |
| 6-32 | 1/2 | AN526-632R5 | \$0.06 | ---- | --- |
| | 3/8 | AN526-632R6 | \$0.06 | AN526-632-6 | \$0.14 |
| | 7/16 | AN526-632R7 | \$0.06 | ---- | --- |
| | 1/2 | AN526-632R8 | \$0.06 | AN526-632-8 | \$0.11 |
| | 9/16 | AN526-632R9 | \$0.08 | ---- | --- |
| | 5/8 | AN526-632R10 | \$0.07 | AN526-632-10 | \$0.54 |
| | 3/4 | AN526-632R12 | \$0.08 | AN526-632-12 | \$0.16 |
| | 7/8 | AN526-632R14 | \$0.07 | ---- | --- |
| | 1 | AN526-632R16 | \$0.08 | ---- | --- |
| | 1-1/2 | AN526-632-R24 | \$0.17 | ---- | --- |
| | 2 | AN526-632R32 | \$0.20 | ---- | --- |
| | 8-32 | 1/4 | AN526-832R4 | \$0.08 | ---- |
| 5/16 | | AN526-832R5 | \$0.07 | ---- | --- |
| 3/8 | | AN526-832R6 | \$0.07 | ---- | --- |
| 7/16 | | AN526-832R7 | \$0.08 | ---- | --- |
| 1/2 | | AN526-832R8 | \$0.07 | AN526-832-8 | \$0.46 |
| 9/16 | | AN526-832R9 | \$0.08 | ---- | --- |
| 5/8 | | AN526-832R10 | \$0.08 | ---- | --- |
| 3/4 | | AN526-832R12 | \$0.08 | AN526-832-12 | \$0.24 |
| 7/8 | | AN526-832R14 | \$0.09 | ---- | --- |
| 1 | | AN526-832R16 | \$0.11 | AN526-832-16 | \$0.19 |
| 1-1/4 | | AN526-832-R20 | \$0.19 | ---- | --- |
| 1-1/2 | | AN526-832-R24 | \$0.29 | ---- | --- |
| 10-32 | 1/4 | AN526-1032R4 | \$0.11 | ---- | --- |
| | 5/16 | AN526-1032R5 | \$0.08 | ---- | --- |
| | 3/8 | AN526-1032R6 | \$0.10 | ---- | --- |
| | 7/16 | AN526-1032R7 | \$0.07 | ---- | --- |
| | 1/2 | AN526-1032R8 | \$0.09 | ---- | --- |
| | 9/16 | AN526-1032R9 | \$0.09 | ---- | --- |
| | 5/8 | AN526-1032R10 | \$0.09 | AN526-1032-10 | \$0.16 |
| | 3/4 | AN526-1032R12 | \$0.12 | AN526-1032-12 | \$0.13 |
| | 7/8 | AN526-1032R14 | \$0.12 | AN526-1032-14 | --- |
| | 1 | AN526-1032R16 | \$0.13 | ---- | --- |
| | 1-1/8 | AN526-1032R18 | \$0.13 | ---- | --- |
| | 1-1/4 | AN526-1032R20 | \$0.16 | ---- | --- |
| | 1-1/2 | AN526-1032R24 | \$0.29 | ---- | --- |
| | 1-3/4 | AN526-1032R28 | \$0.28 | ---- | --- |
| 2 | AN526-1032R32 | \$0.52 | ---- | --- | |

AN526C STAINLESS STEEL MACHINE SCREWS

Stainless steel Phillips and slotted, Use slotted screws for antiques.



| Thread | Length | Phillips Part No. | Price Ea. | Slotted Part No. | Price Ea. |
|--------|--------|-------------------|-----------|------------------|-----------|
| 4-40 | 1/2 | AN526C-440R8 | \$0.08 | ---- | --- |
| | 1/4 | AN526C-632R4 | \$0.07 | AN526C-632-4 | \$0.26 |
| | 3/8 | AN526C-632R6 | \$0.09 | ---- | --- |
| 6-32 | 1/2 | AN526C-632R8 | \$0.08 | AN526C-632-8 | \$0.20 |
| | 5/8 | AN526C-632R10 | \$0.09 | AN526C-632-10 | \$0.30 |
| | 3/4 | AN526C-632R12 | \$0.10 | ---- | --- |
| | 1 | AN526C-632R16 | \$0.13 | AN526C-632-16 | \$0.29 |
| 8-32 | 1/4 | AN526C-832R4 | \$0.14 | ---- | --- |
| | 3/8 | AN526C-832R6 | \$0.10 | ---- | --- |
| | 1/2 | AN526C-832R8 | \$0.10 | AN526C-832-8 | \$0.16 |
| | 5/8 | AN526C-832R10 | \$0.11 | AN526C-832-10 | \$0.23 |
| | 3/4 | AN526C-832R12 | \$0.13 | AN526C-832-12 | \$0.34 |
| 10-32 | 1 | AN526C-832R16 | \$0.16 | AN526C-832-16 | \$1.50 |
| | 1/4 | AN526C-1032R4 | \$0.38 | ---- | --- |
| | 3/8 | AN526C-1032R6 | \$0.13 | AN526C-1032-6 | \$0.21 |
| | 1/2 | AN526C-1032R8 | \$0.13 | AN526C-1032-8 | \$0.24 |
| | 5/8 | AN526C-1032R10 | \$0.15 | AN526C-1032-10 | \$0.20 |
| | 3/4 | AN526C-1032R12 | \$0.16 | AN526C-1032-12 | --- |
| | 1 | AN526C-1032R16 | \$0.18 | ---- | --- |
| | 1-1/4 | AN526C-1032R20 | ---- | ---- | --- |
| | 1-1/2 | AN526C-1032R24 | \$0.24 | ---- | --- |
| 1/4-20 | 1/2 | AN526C-420R8 | \$1.57 | ---- | --- |
| 1/4-28 | 1/2 | AN526C-428R8 | \$0.28 | ---- | --- |
| | 3/4 | AN526C-428R12 | \$0.42 | ---- | --- |
| 1-1/8 | ---- | ---- | --- | AN526C-428-18 | \$0.69 |

Note: Some sizes of AN526C screws are furnished as commercial equipment as AN screws are no longer available.

HA