

# TEMPO FINISHES – SUPERFLITE



## ULTRA-HIGH TEMPERATURE PAINTS

Exceptional durability up to 1200°F. Will not burn off, chip or peel when properly applied. No primer required. Ideal for exhaust stacks. Ultra-High Temperature paints air-dry in minutes but require curing at temperatures over 650°F.

Black .....	P/N 13-2 .....	<b>\$8.95</b>
Aluminum .....	P/N 13-8 .....	<b>\$9.65</b>

## PREMIUM SELF-ETCHING PRIMER

Etches and primes in one easy step. Can be used under all today's automotive finishes. Perfect for spot repairs. Creates superior adhesion on most plastics, fiberglass, bare steel, aluminum and stainless steel. Color: Green. 12oz.

Spray Can..... P/N 09-02099..... **\$11.55**



## CAN-GUN



Can-Gun is an aerosol spray can trigger handle which makes painting, cleaning, and lubricating jobs safer and easier. The user-friendly form-fit handle and trigger eliminates finger fatigue and provides the user with accurate control over the amount, speed, and direction of spray. The built-in safety shield insures no more messy hands or fingers. Sprays virtually all spray paints, lacquers, polishes, cleaners, lubricants, sealers, and adhesives and Can-Gun fits most spray cans.....P/N 09-14760..... **\$1.85 ea.**

## EPOXY PROPELLER COATING

Extends blade life. Tempo's Epoxy Propeller Coating is formulated with the extra adhesion and abrasion resistance needed to protect propellers from corrosion and wear. Compared to standard enamel and lacquer paints, our epoxy formula stays on the blade more flying hours; hence, with regular use, this formula can extend blade life.

Flat Black .....	P/N 09-00982 .....	<b>\$8.95</b>
Med. Gray .....	P/N 09-00983 .....	<b>\$8.95</b>
(Matches Hartzell OE Gray)		
White.....	P/N 09-00992 .....	<b>\$8.95</b>



## KRYLON AEROSOL HIGH HEAT PAINT

Krylon High Heat & Radiator Paint is ideal for mufflers, radiators, and engine blocks. Withstands temperatures to 1200F. Guards against rust. Available in three colors. 12 oz. aerosol cans. 12 oz. Aerosol.

Aluminum.....	P/N 15-05467 .....	<b>\$14.50</b>
White .....	P/N 15-08254 .....	<b>\$16.95</b>
Black.....	P/N 15-08255 .....	<b>\$17.50</b>



## AIRCRAFT LACQUERS

**Dries in under 15 minutes**

Tempo's Aircraft Lacquer is ideal when a very fast dry is required. This blended nitrocellulose lacquer formula can be applied to all interior and exterior aluminum and steel surfaces, including wheels, landing gear and inside door hatches. When additional corrosion protection is required, we recommend Tempo Aircraft Enamel.

Black Acrylic .....	P/N 09-01032 .....	<b>\$7.50</b>
A880 Flat Black .....	P/N 09-04363 .....	<b>\$8.85</b>



## AIRCRAFT ENAMEL

**Excellent adhesion to aluminum and steel**

Tempo's Aircraft Enamel has been especially formulated to adhere to aluminum and steel; providing excellent corrosion resistance. Recommended applications are all interior and exterior aluminum and steel surfaces, including wheels, landing gear and inside door hatches. For propeller blades, we recommend Epoxy Propeller Coating.

Black .....	P/N 09-00985 .....	<b>\$8.50</b>
Gloss White .....	P/N 09-00989 .....	<b>\$8.50</b>
Flat Black .....	P/N 09-02070 .....	<b>\$8.50</b>



## TEMPO ENGINE ENAMEL

Resists heat to 500°F. Tempo's Aircraft Engine enamel withstands the high heat demands of aircraft engines. This modified chain-stop alkyd enamel formula has excellent corrosion and fuel resistance.

All Tempo spray products feature the exclusive adjustable Fanspray valve which offers a professional spray pattern so anyone can "paint like a pro". The extra-width pattern evenly coats about 3 times the area with each pass compared with an ordinary spray valve. Packaged in 11 oz. to 16 oz. cans, depending on product.

**WARNING: POSSIBLE LINK BETWEEN CHROMATE PIGMENTS AND LUNG CANCER**

Several independent technical studies have suggested that excessive inhalation of zinc chromate dust may cause lung cancer. If conditions are such that this limit may be exceeded, additional protective equipment is required. A respirator that has a NIOSH/MESA approval TC-23C. See catalog for respirators that meet this requirement.

Lyc. Gray .....	P/N 219 .....	<b>\$8.50</b>
Olds Cont. Gold.....	P/N 239 .....	<b>\$8.50</b>
Gloss Black .....	P/N 09-00995 .....	<b>\$8.50</b>
Purple .....	P/N 09-01998 .....	<b>\$6.95</b>



## VHT WRINKLE PLUS COAT

VHT Wrinkle Plus™ combines strong colors with a deep rich texture for a custom look. It is temperature resistant to 350°F (177°C) and is ideal for adding a touch of personal styling to almost any metal surface. VHT Wrinkle Plus™ resists color fading, grease, degreasers, and severe weather conditions. This tough, durable finish is extremely resistant to rust, corrosion, chipping and cracking.

**Applications:** Valve Covers, Metal Dashboards, Glove Boxes, Starters, Door Panels, Shifters, Alternators, Firewalls  
Black SP201 .....
 P/N 09-05684 ..... | **\$8.95** |

## ZINC PHOSPHATE PRIMERS

Maximum adhesion to bare aluminum and steel

Tempo's Zinc Phosphate Primers are recommended for priming bare metal. These primers provide maximum bonding to bare aluminum and steel. Tempo's Primers have been the workhorse in the aviation industry for many years.

The A-701 Yellow and A-702 Green Zinc Phosphate Primers meet the performance standards outlined in Federal Specification T-P-1757A. They also exceed the 800 hours of salt spray fog test (ASTM #B117). A-701 will replace A-901 Yellow and A-702 will replace A-902 Green.

Yellow (12oz.) A-701 .....	P/N 09-02128 .....	<b>\$9.95</b>
Green (12oz.) A-702 .....	P/N 09-02127 .....	<b>\$9.95</b>



## SUPERFLITE AIRCRAFT ENGINE ENAMELS



Superflite engine enamels are fast-drying enamels developed specifically for air-cooled aircraft engines used in light duty aviation industries. The Superflite enamels feature superior adhesion, heat resistance, and a gloss finish. Cure Schedule: Dry to touch: 15 minutes, Dry to handle: 60 minutes Dry through: 24 hours To recoat: Before 60 minutes, or after 72 hours Benefits: Topcoat - Air dry or low temperature cure, For use on bare metal or painted surfaces Specifications: Shelf Life: 12 months at recommended storage temperatures, Heat Resistance: Up to 400 degree F.

Lycoming Grey Paint Quart.....	P/N 09-02558 .....	<b>\$39.85</b>
Lycoming Grey Paint Spray .....	P/N 09-02556 .....	<b>\$11.95</b>
TCM Gold Paint Quart.....	P/N 09-02557 .....	<b>\$39.85</b>
TCM Gold Paint Spray .....	P/N 09-02550 .....	<b>\$11.95</b>
Gloss Paint Black Quart.....	P/N 09-02559 .....	<b>\$39.95</b>

