

# MACHINE SCREWS

## MS27039 & MS27039C MACHINE SCREWS



Pan head low alloy steel machine screws have 125,000 to 145,000 psi tensile strength with cadmium plate finish to QQ-P-416, Type 2, Class 3.

MS27039C screws are stainless steel Manufactured to MIL-S-6050 or MIL-8695. Equivalent to NAS 220.

Part Number	Diam.-Thrd. Size	Length (In.)	Grip Length (in)	MS27039 Price	MS27039C Price
MS27039-0804	8-32	9/32	---	\$0.16	\$0.38
MS27039-0805	8-32	11/32	---	\$0.10	\$0.48
MS27039-0806	8-32	13/32	---	\$0.13	---
MS27039-0807	8-32	15/32	---	\$0.13	---
MS27039-0808	8-32	17/32	.094	\$0.14	---
MS27039-0809	8-32	19/32	.156	\$0.15	---
MS27039-0810	8-32	21/32	.219	\$0.13	---
MS27039-0811	8-32	23/32	.281	\$0.15	\$0.84
MS27039-0812	8-32	25/32	.344	\$0.18	---
MS27039-0813	8-32	27/32	.406	\$0.14	\$0.87
MS27039-0814	8-32	29/32	.469	\$0.19	\$0.73
MS27039-0815	8-32	31/32	.531	\$0.18	\$0.99
MS27039-0816	8-32	1-1/32	.594	\$0.18	---
MS27039-0817	8-32	1-3/32	.656	\$0.21	\$0.97
MS27039-0818	8-32	1-5/32	.719	\$0.26	---
MS27039-0819	8-32	1-7/32	.781	\$0.22	---
MS27039-0820	8-32	1-9/32	.844	\$0.26	---
MS27039-0821	8-32	1-11/32	.906	\$0.26	---
MS27039-0822	8-32	1-13/32	.969	\$0.22	---
MS27039-0823	8-32	1-15/32	1.031	\$0.23	---
MS27039-0824	8-32	1-17/32	1.094	\$0.23	---
MS27039-1-04	10-32	9/32	---	\$0.15	\$0.84
MS27039-1-05	10-32	11/32	---	\$0.15	\$0.57
MS27039-1-06	10-32	13/32	---	\$0.14	\$0.59
MS27039-1-07	10-32	15/32	---	\$0.12	---
MS27039-1-08	10-32	17/32	.062	\$0.13	---
MS27039-1-09	10-32	19/32	.125	\$0.15	\$0.57
MS27039-1-10	10-32	21/32	.188	\$0.16	\$0.90
MS27039-1-11	10-32	23/32	.250	\$0.17	\$0.79
MS27039-1-12	10-32	25/32	.312	\$0.17	---
MS27039-1-13	10-32	27/32	.375	\$0.20	\$1.17
MS27039-1-14	10-32	29/32	.438	\$0.16	---
MS27039-1-15	10-32	31/32	.500	\$0.19	\$0.98
MS27039-1-16	10-32	1-1/32	.563	\$0.21	---
MS27039-1-17	10-32	1-3/32	.625	\$0.19	\$1.10
MS27039-1-18	10-32	1-5/32	.688	\$0.19	\$1.31
MS27039-1-19	10-32	1-7/32	.750	\$0.32	\$1.34
MS27039-1-20	10-32	1-9/32	.813	\$0.22	\$1.36
MS27039-1-21	10-32	1-11/32	.875	\$0.28	\$1.43
MS27039-1-22	10-32	1-13/32	.938	\$0.27	\$1.50
MS27039-1-23	10-32	1-15/32	1.000	\$0.39	\$2.50
MS27039-1-24	10-32	1-17/32	1.062	\$0.52	\$1.90
MS27039-1-25	10-32	1-19/32	1.125	\$0.53	---
MS27039-1-26	10-32	1-21/32	1.188	\$0.42	---
MS27039-1-27	10-32	1-23/32	1.250	\$0.43	---
MS27039-1-28	10-32	1-25/32	1.312	\$0.43	---
MS27039-1-29	10-32	1-27/32	1.375	\$0.78	---
MS27039-1-30	10-32	1-29/32	1.438	\$0.66	---
MS27039-1-31	10-32	1-31/32	1.500	\$0.48	---
MS27039-1-32	10-32	2-1/32	1.563	\$0.53	---
MS27039-4-06	1/4-28	13/32	---	\$0.29	\$1.73
MS27039-4-07	1/4-28	15/32	---	\$0.24	\$1.20
MS27039-4-08	1/4-28	17/32	---	\$0.21	\$1.22
MS27039-4-09	1/4-28	19/32	.062	\$0.26	\$2.14
MS27039-4-10	1/4-28	21/32	.125	\$0.24	\$1.62
MS27039-4-11	1/4-28	23/32	.188	\$0.30	\$1.14
MS27039-4-12	1/4-28	25/32	.250	\$0.27	\$1.65
MS27039-4-13	1/4-28	27/32	.312	\$0.39	\$2.52
MS27039-4-14	1/4-28	29/32	.375	\$0.32	\$2.15
MS27039-4-15	1/4-28	31/32	.438	\$0.30	\$1.50
MS27039-4-16	1/4-28	1-1/32	.500	\$0.33	\$2.39
MS27039-4-17	1/4-28	1-3/32	.563	\$0.29	---
MS27039-4-18	1/4-28	1-5/32	.625	\$2.20	---
MS27039-4-19	1/4-28	1-7/32	.688	\$0.34	---
MS27039-4-20	1/4-28	1-9/32	.750	\$0.35	---
MS27039-4-21	1/4-28	1-11/32	.813	\$0.37	---
MS27039-4-22	1/4-28	1-13/32	.875	\$0.36	---
MS27039-4-23	1/4-28	1-15/32	.938	\$0.37	---
MS27039-4-24	1/4-28	1-17/32	1.000	\$0.46	---

## MS35190 MACHINE SCREWS (CROSS RECESSED)



82° flat head machine screws have 55,000psi minimum tensile strength and feature cadmium plate finish per QQ P-416, Type 2, Class 3. Manufactured from carbon steel to Federal Standard #66.

Part Number	Old AN505R	Diam.-Thrd. Size	Length (In.)	Price
MS35190-221	-4R4	4-40	1/4	\$0.11
MS35190-222	-4R5	4-40	5/16	\$0.39
MS35190-225	-4R8	4-40	1/2	\$0.09
MS35190-226	-4R10	4-40	5/8	\$0.17
MS35190-234	-6R4	6-32	1/4	\$1.43
MS35190-236	-6R6	6-32	3/8	\$0.07
MS35190-238	-6R8	6-32	1/2	\$0.08
MS35190-239	-6R10	6-32	5/8	\$0.08
MS35190-240	-6R12	6-32	3/4	\$0.07
MS35190-250	-8R5	8-32	5/16	\$0.08
MS35190-253	-8R8	8-32	1/2	\$0.08
MS35190-254	-8R10	8-32	5/8	\$0.09

## MS35207 MACHINE SCREWS (CROSS RECESSED)



These pan head machine screws have 55,000 psi minimum tensile strength and are cadmium plated to Specification QQ-P-416, Type 2, Class 3. Manufactured from carbon steel per Federal Standard #66.

Part Number	Old AN520R	Dia.-Thread Size	Length (In.)	Price ea.
MS35207-260	-10R5	10-32	5/16	\$0.08
MS35207-261	-10R6	10-32	3/8	\$0.08
MS35207-262	-10R7	10-32	7/16	\$0.08
MS35207-263	-10R8	10-32	1/2	\$0.07
MS35207-264	-10R10	10-32	5/8	\$0.08
MS35207-265	-10R12	10-32	3/4	\$0.11
MS35207-266	-10R14	10-32	7/8	\$0.14
MS35207-267	-10R16	10-32	1	\$0.12
MS35207-268	-10R20	10-32	1-1/4	\$0.13
MS35207-269	-10R24	10-32	1-1/2	\$0.20
MS35207-270	-10R28	10-32	1-3/4	\$0.18
MS35207-271	-10R32	10-32	2	\$0.19

## MS35206 MACHINE SCREWS (CROSS RECESSED)



These pan head machine screws feature 60,000 psi minimum tensile strength and are cadmium plated to specification QQ-P-416, Type 2, Class 3. Manufactured from carbon steel to Federal Standard #66, these screws can be used as replacements for AN526 machine screws. Phillips head.

Part Number	Old AN515R	Diam.-Thrd. Size	Length (In.)	Price ea.
MS35206-203	-2R2	2-56	1/4	\$0.07
MS35206-204	-2R5	2-56	5/16	\$0.06
MS35206-205	-2R6	2-56	3/8	\$0.07
MS35206-206	-2R7	2-56	7/16	\$0.05
MS35206-207	-2R8	2-56	1/2	\$0.05
MS35206-208	-2R10	2-56	5/8	\$0.05
MS35206-209	-2R12	2-56	3/4	\$0.09
MS35206-212	-4R3	4-40	3/16	\$0.04
MS35206-213	-4R4	4-40	1/4	---
MS35206-214	-4R5	4-40	5/16	\$0.04
MS35206-215	-4R6	4-40	3/8	\$0.04
MS35206-216	-4R7	4-40	7/16	\$0.07
MS35206-217	-4R8	4-40	1/2	\$0.05
MS35206-218	-4R10	4-40	5/8	\$0.08
MS35206-219	-4R12	4-40	3/4	\$0.06
MS35206-220	-4R14	4-40	7/8	\$0.08
MS35206-221	-4R16	4-40	1	\$0.08
MS35206-222	-4R20	4-40	1-1/4	\$0.17
MS35206-223	-4R24	4-40	1-1/2	\$0.09
MS35206-226	-6R4	6-32	1/4	\$0.05
MS35206-227	-6R5	6-32	5/16	\$0.05
MS35206-228	-6R6	6-32	3/8	\$0.05
MS35206-229	-6R7	6-32	7/16	\$0.05
MS35206-230	-6R8	6-32	1/2	\$0.05
MS35206-231	-6R10	6-32	5/8	\$0.06
MS35206-232	-6R12	6-32	3/4	\$0.06
MS35206-233	-6R14	6-32	7/8	\$0.08
MS35206-234	-6R16	6-32	1	\$0.06
MS35206-235	-6R20	6-32	1-1/4	\$0.09
MS35206-236	-6R24	6-32	1-1/2	\$0.12
MS35206-238	-6R32	6-32	2	\$0.19
MS35206-241	-8R4	8-32	1/4	\$0.05
MS35206-242	-8R5	8-32	5/16	\$0.06
MS35206-243	-8R6	8-32	3/8	\$0.05
MS35206-244	-8R7	8-32	7/16	\$0.06
MS35206-245	-8R8	8-32	1/2	\$0.06
MS35206-246	-8R10	8-32	5/8	\$0.08
MS35206-247	-8R12	8-32	3/4	\$0.07
MS35206-248	-8R14	8-32	7/8	\$0.10
MS35206-249	-8R16	8-32	1	\$0.10
MS35206-250	-8R20	8-32	1-1/4	\$0.13
MS35206-251	-8R24	8-32	1-1/2	\$0.14
MS35206-252	-8R28	8-32	1-3/4	\$0.13
MS35206-253	-8R32	8-32	2	\$0.29
MS35206-261	-10R6	10-24	3/8	\$0.07
MS35206-262	-10R7	10-24	7/16	\$0.10
MS35206-263	-10R8	10-24	1/2	\$0.09
MS35206-264	-10R10	10-24	5/8	\$0.12
MS35206-265	-10R12	10-24	3/4	\$0.09
MS35206-267	-10R16	10-24	1	\$0.13

HA