

CHERRY RIVET TOOLS

HYDRO-SHIFT CHERRYLOCK® RIVETER



Specifically for the installation of all CherryLOCK® Rivets. Recommended primarily for 1/4" diameter CherryLOCK® rivets. It can be used to install all diameters and lengths as indicated on the tool capacity charts. Low recoil, low noise and a comfortable fit in the operator's hand. It can be operated in any position with one hand. The H681 Series pulling heads fit directly on this tool to install both bulbed and standard NAS type 2000 Series CherryLOCK® Rivets. With the proper adapters and pulling heads, this tool can install other types of rivets.....P/N 12-02983\$11,549.00



LOCKBOLT POWER RIVETER G84

For high speed, reliable installation of the most popular sizes of aircraft Lockbolts. Incorporates a bayonet attachment for quick change of pulling heads. This tool can also be used to install blind bolts and blind rivets. A comfortable grip for one handed operation in any position. Compatible with Huck 352 & 230 riveter pulling heads.....P/N 12-03011\$1,756.00

LOCKBOLT POWER RIVETER TOOL KIT G84LBK

Installs: 5/32", 3/16" & 1/4" NAS Style. LockBolt **Includes:** G84 LockBolt Power Riveter - Stroke: 9/16", Pulling Force: 5, 750 lbs (2,608 kgs), Weight: 7.7 lbs (3.5 kgs). H513-08-35 Pulling Head. H513S-05-20 Pulling Head Cherry 5/32" D LockBolt. H513S-06-20 Pulling Head MaxiBolt 3/16" LockBolt. P1395 Molded Carrying Case. 269C5 Grip Gauge LockBolt. 670A20 Stem Catcher Bag. 700A77 Bleeder Bottle. All Necessary Manuals. P/N 12-03013\$4,279.00



CHERRY RIVETER SERVICE KIT G84KS

All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G84. P/N 12-03012\$164.75



LIGHTWEIGHT LOCKBOLT RIVETER TOOL KIT G83AKT

Installs: 5/32" & 3/16" MS Blind Bolt & LockBOLT, 1/8", 5/32" & 3/16" Cherry MAX **Includes:** G83 Lightweight LockBolt Hand Riveter - Stroke: 7/16", Pulling Force: 3, 750 lbs (1, 701 kgs), Weight: 4.95 lbs (2.3 kgs). H513S-05-20 Pulling Head Cherry 5/32" D LockBolt. H513S-06-20 Pulling Head 3/16" LockBolt. H701B-456 Pulling Head Straight 3/4" x 1 3/4". H753A-4562 CherryMAX Pulling Heads RT Angle 2 1/4" x 5 7/16" x 3/8". H781-456 Cherry Pulling Head Offet 1/8"-5/32"-3/16". H83B-5MB Pulling Head MaxiBolt 5/32"D. H83B-6MB Pulling Head MaxiBolt 3/16" D G83/G84. P1393 Plastic Box. 269B12 MaxiBolt Gauge. 269C3 CherryMAX Grip Gauge. 269C5 Grip Gauge LockBolt. 670A20 Stem Catcher Bag. 700A77 Bleeder Bottle. 744-300 Adapter. All Necessary Manuals P/N 12-03008\$5,278.00

LIGHTWEIGHT LOCKBOLT RIVETER TOOL KIT G83BKT

Installs: 5/32" & 3/16" MS Blind Bolt & NAS Style LockBolt **Includes:** G83 Lightweight LockBolt Hand Riveter - Stroke: 7/16", Pulling Force: 3, 750 lbs (1, 701 kgs), Weight: 4.95 lbs (2.3 kgs). H513S-05-20 Pulling Head Cherry 5/32" D LockBolt. H513S-06-20 Pulling Head 3/16" LockBolt. H83B-5MB Pulling Head MaxiBolt 5/32"D. H83B-6MB Pulling Head MaxiBolt 3/16" D G83/G84. P1393 Plastic Box. 269B12 MaxiBolt Gauge. 269C5 Grip Gauge LockBolt. 670A20 Stem Catcher Bag. 700A77 Bleeder Bottle. All Necessary Manuals.....P/N 12-03009\$5,396.00



CHERRY RIVETER SERVICE KIT G83KS

All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G83. P/N 12-03010\$211.95

LIGHTWEIGHT LOCKBOLT RIVETER G83



Designed for high speed, reliable installation of the most popular sizes of aircraft Lockbolts. By bending the rubber pin deflector sideways, 1-1/2" additional clearance can be obtained. This tool can also be used to install blind bolts and blind rivets. A comfortable grip for one handed operation in any position. Compatible with Huck 352 & 230 riveter pulling heads. Stroke: 7/16". Pulling Force: 3, 750 lbs (1, 701 kgs). Weight: 4.95 lbs (2.3 kgs).....P/N 12-03007\$1,384.00

CHERRY RIVETER SERVICE KIT G800KS



All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G800. P/N 12-03006\$149.75



CHERRYMAX HYDRAULIC HAND RIVETER G800

The G800 is an ergonomic, lightweight hand powered riveter capable of installing a wide variety of blind fasteners. The all metal design makes this compact and robust tool ideal for use in rugged shop environments or field repair. Exceptional power with low hand effort for increased productivity. Mounting system (same as G704B) compatible with popular pulling heads including H782, H781-456& H753A-456. Leak-proof design with advanced seals & built-in redundancies. Ergo design with internal shock absorber & cushioned handle. Adjustable lever easily accommodates different hand sizes. Stroke: 3/4". Pulling Force: Up to 6000 lbs. Weight: 1.7 lbs (0.8 kgs)P/N 12-03004\$919.00



CHERRYMAX HYDRAULIC HAND RIVETER KIT G800CRM

G800CRM CherryMAX Hydraulic Hand Riveter Kit **Includes:** G800 CherryMAX Hydraulic Hand Riveter - Stroke 3/4", Pulling Force up to 6000 lbs, Weight 1.7 lbs. H781-456 Pulling Heads. H753A-456 Pulling Heads. 269C5 Grip Selector Gauge. 269B12 Grip Selector Gauge. Molded Plastic Case. All Necessary Manuals (except -6 all aluminum) P/N 12-03005\$2,430.00



CHERRY RIVETER SERVICE KIT G784KS

All the seals, 'O'-rings, gaskets and hardware required for routine maintenance of your Cherry blind riveters. A must for any in-house repair facility. For Tool G784. P/N 12-03002\$346.00



NUT-PLATE RIVETER G702A

The G702A is a pneumatic-hydraulic tool designed specifically for installation of nut plate rivets. Its durable, all metal housing makes this tool ideal for use in rugged shop environments. The H702-3NPR pulling head fits directly on the tool to install -3, -4, 2.5 mm & 3mm nut plate rivets. 10° angled head allows user to work using a natural hand position. A comfortable grip for one handed operation in any position. Air Pressure: 90 PSI (6.2 bar) min./110 PSI (7.6 bar) max. Cycle Time: approximately one second. Noise Level: 71 dB (A). Vibration: less than 2.5 m/s². Air Consumption: .09 SCF / cycle (2.55 L / cycle). Stroke: 3/4". Pulling Force: 1,100 lbs (499 kgs). Weight: 3.5 lbs.P/N 12-02985\$1,349.00



CHERRYLOCK POWER RIVETER KIT G784CLRB

Includes: G784 Cherry Universal Power Riveter 12" High, 8 lbs., 15/16" Stroke. P1395 Molded Carrying Case. TLC852 CherryLock Selector Card. TLC864 CherryLock Process Manual. 269C3 CherryMAX Grip Gauge. 700A77 Bleeder Bottle. **Note:** No Pulling Heads Included. P/N 12-03001\$3,669.00

CHERRYLOCK POWER RIVETER G784



Installation of CherryLOCK rivets. Will install nearly all diameters of CherryLOCK rivets up to a half-inch grip, 'A' group only. With proper adapters & pulling heads this tool can be used to install other types of rivets. A comfortable grip for one handed operation in any position. Pulling heads not included with riveter. Air Pressure: 90 PSI (6.2 bar) min./110 PSI (7.6 bar) max. Noise Level: 69.7 dB (A). Vibration: less than 2.5 m/s². Air Consumption: .27 SCF / cycle (7.65 L / cycle). Stroke: 7/8". Pulling Force: 2,600 lbs (1, 179 kgs). Weight: 8 lbs (3.6 kgs)P/N 12-02998\$2,995.00



POWER RIVETER G747

Installation of CherryMAX and nut plate rivets. This tool utilizes straight, offset and right angle pulling heads, all of which can install -4, -5 and -6 diameter CherryMAX bulb type rivets in all head styles, materials and grip lengths. Extensions are available for extending the pulling heads to reach limited access areas. 10° angled head allows user to work using a natural hand position. A comfortable grip for one handed operation in any position. Same weight as the G702A, with the power of much larger toolsP/N 12-02995\$895.00

TO