

MACHINE SCREWS



MS24694 MACHINE SCREWS (FORMERLY AN509)

These structural screws have a 100° countersunk head. Cadmium plated per QQ-P-416, Type II, Class 3. Minimum tensile strength for steel is 125,000 PSI.

MS24694 Dash No.	AN509 Dash No.	Length In.	Grip In.	Thread Size	Price Each	MS24694 Dash No.	AN509 Dash No.	Length In.	Grip In.	Thread Size	Price Each
-S1	-8R4	9/32	3/32	8-32	\$0.10	-S65	-10R23	1-15/32	1	10-32	\$0.33
-S2	-8R5	11/32		8-32	\$0.13	-S66	-10R24	1-17/32	1-1/16	10-32	\$0.26
-S3	-8R6	13/32		8-32	\$0.12	-S67	-10R25	1-19/32	1-1/8	10-32	---
-S4	-8R7	15/32		8-32	\$0.12	-S68	-10R26	1-21/32	1-3/16	10-32	---
-S5	-8R8	17/32		8-32	\$0.12	-S69	-10R27	1-23/32	1-1/4	10-32	---
-S7	-8R10	21/32	7/32	8-32	\$0.13	-S70	-10R28	1-25/32	1-5/16	10-32	\$0.41
-S8	-8R11	23/32	9/32	8-23	---	-S71	-10R29	1-27/32	1-3/8	10-32	---
-S9	-8R12	25/32	11/32	8-32	\$0.14	-S72	-10R30	1-29/32	1-7/16	10-32	\$0.58
-S10	-8R13	27/32	13/32	8-32	---	-S74	-10R32	2-1/32	1-9/16	10-32	\$0.48
-S11	-8R14	29/32	15/32	8-32	\$0.18	-S75	-10R33	2-3/32	1-5/8	10-32	\$1.12
-S12	-8R15	31/32	17/32	8-32	---	-S76	-10R34	2-5/32	1-11/16	10-32	\$0.74
-S13	-8R16	1-1/32	19/32	8-32	\$0.18	-S77	-10R35	2-7/32	1-3/4	10-32	\$0.94
-S14	-8R17	1-1/32	21/32	8-32	---	-S79	-10R37	2-11/32	1-7/8	10-32	\$0.72
-S15	-8R18	1-5/32	23/32	8-32	\$0.21	-S82	-10R40	2-17/32	2-1/16	10-32	\$0.84
-S16	-8R19	1-7/32	25/32	8-32	---	-S84	-10R42	2-21/32	2-3/16	10-32	\$0.75
-S17	-8R20	1-9/32	27/32	8-32	\$0.21	-S88	-10R46	2-29/32	2-7/16	10-32	\$1.77
-S18	-8R21	1-11/32	29/32	8-32	\$0.28	-S90	-10R48	3-1/32	2-9/16	10-32	\$0.59
-S19	-8R22	1-13/32	31/32	8-32	\$0.20	-S93	-416R6	13/32	9/64	1/4-28	---
-S20	-8R23	1-15/32	1-1/32	8-32	---	-S94	-416R7	15/32		1/4-28	---
-S21	-8R24	1-17/32	1-3/32	8-32	\$0.28	-S95	-416R8	17/32		1/4-28	---
-S28	-8R31	1-31/32	1-17/32	8-32	\$0.63	-S96	-416R9	19/32		1/4-28	---
-S29	-8R32	2-1/32	1-19/32	8-32	\$0.82	-S97	-416R10	21/32		1/4-28	\$0.29
-S31	-8R34	2-5/32	1-23/32	8-32	\$1.36	-S98	-416R11	23/32		3-16	1/4-28
-S46	-10R4	9/32	7/64	10-32	---	-S99	-416R12	25/32	1/4	1/4-28	\$0.22
-S47	-10R5	11/32		10-32	---	-S100	-416R13	27/32	5/16	1/4-28	\$0.26
-S48	-10R6	13/32		10-32	\$0.13	-S101	-416R14	29/32	3/8	1/4-28	\$0.29
-S49	-10R7	15/32		10-32	\$0.14	-S102	-416R15	31/32	7/16	1/4-28	\$0.35
-S50	-10R8	17/32		10-32	\$0.14	-S103	-416R16	1-1/32	1/2	1/4-28	\$0.32
-S51	-10R9	19/32		10-32	\$0.18	-S104	-416R17	1-3/32	9/16	1/4-28	\$0.32
-S52	-10R10	21/32		3/16	10-32	\$0.14	-S105	-416R18	1-5/32	5/8	1/4-28
-S53	-10R11	23/32	1/4	10-32	\$0.16	-S106	-416R19	1-7/32	11/16	1/4-28	\$0.26
-S54	-10R12	25/32	5/16	10-32	\$0.15	-S107	-416R20	1-9/32	3/4	1/4-28	---
-S55	-10R13	27/32	3/8	10-32	\$0.16	-S108	-416R21	1-11/32	13/16	1/4-28	---
-S56	-10R14	29/32	7/16	10-32	\$0.16	-S109	-416R22	1-13/32	7/8	1/4-28	\$0.41
-S57	-10R15	31/32	1/2	10-32	---	-S110	-416R23	1-15/32	15/16	1/4-28	\$0.36
-S58	-10R16	1-1/32	9/16	10-32	\$0.23	-S111	-416R24	1-17/32	1	1/4-28	\$0.38
-S59	-10R17	1-3/32	5/8	10-32	\$0.19	-S113	-416R26	1-21/32	1-1/8	1/4-28	\$0.70
-S60	-10R18	1-5/32	11/16	10-32	\$0.18	-S115	-416R28	1-25/32	1-1/4	1/4-28	\$0.49
-S61	-10R19	1-7/32	3/4	10-32	---	-S119	-416R32	2-1/32	1-1/2	1/4-28	\$0.72
-S62	-10R20	1-9/32	13/16	10-32	\$0.26	-S121	-416R34	2-5/32	1-5/8	1/4-28	\$2.28
-S63	-10R21	1-11/32	7/8	10-32	---	-S123	-416R36	2-9/32	1-3/4	1/4-28	\$1.83
-S64	-10R22	1-13/32	15/16	10-32	\$0.21	-S148	-516R16	1-1/32	15/32	5/16-24	---
						-S178	-516R46	2-29/32	2-11/32	5/16-24	---

HA



MS24694C STAINLESS STEEL MACHINE SCREWS

Same style screws as MS24694, except stainless steel. Phillips head. (Formerly AN509C) Minimum tensile strength for stainless steel is 85,000 PSI.

MS Part No.	AN509C No.	Thread Size	Length Inches	Price ea.	MS Part No.	AN509C No.	Thread Size	Length Inches	Price ea.
MS24694C1	-8R4	8-32	9/32	\$0.17	MS24694C48	-10R6	10-32	13/32	\$0.17
MS24694C2	-8R5	8-32	11/32	\$0.12	MS24694C49	-10R7	10-32	15/32	\$0.16
MS24694C3	-8R6	8-32	13/32	\$0.17	MS24694C50	-10R8	10-32	17/32	\$0.18
MS24694C4	-8R7	8-32	15/32	\$0.14	MS24694C51	-10R9	10-32	19/32	\$0.17
MS24694C5	-8R8	8-32	17/32	\$0.11	MS24694C52	-10R10	10-32	21/32	\$0.18
MS24694C6	-8R9	8-32	19/32	\$0.12	MS24694C53	-10R11	10-32	23/32	\$0.22
MS24694C7	-8R10	8-32	21/32	\$0.17	MS24694C54	-10R12	10-32	25/32	\$0.23
MS24694C8	-8R11	8-32	23/32	\$0.19	MS24694C55	-10R13	10-32	27/32	\$0.23
MS24694C9	-8R12	8-32	25/32	\$0.17	MS24694C56	-10R14	10-32	29/32	\$0.24
MS24694C10	-8R13	8-32	27/32	\$0.17	MS24694C57	-10R15	10-32	31/32	\$0.32
MS24694C11	-8R14	8-32	29/32	\$0.29	MS24694C58	-10R16	10-32	1-1/32	\$0.32
MS24694C13	-8R16	8-32	1-1/32	\$0.32	MS24694C59	-10R17	10-32	1-3/32	\$0.36
MS24694C14	-8R17	8-32	1-3/32	\$0.59	MS24694C60	-10R18	10-32	1-5/32	\$0.39
MS24694C15	-8R18	8-32	1-5/32	\$1.78	MS24694C61	-10R19	10-32	1-7/32	\$0.39
MS24694C46	-10R4	10-32	9/32	\$0.17	MS24694C62	-10R20	10-32	1-9/32	\$0.34
MS24694C47	-10R5	10-32	11/32	\$0.14	MS24694C92		1/4-28	3/8	\$0.59



NAS387 SERIES MACHINE SCREWS

Type: NAS387. Material: Carbon Steel Type 1016 - 1024. Finish: Nickel Plate

Thread	Length	Part No.	Price	Thread	Length	Part No.	Price	
6-32	3/8	NAS387-632-6P	\$0.16	10-32	1/2	NAS387-1032-8P	\$0.30	
	7/16	NAS387-632-7P	---		5/8	NAS387-1032-10P	\$0.20	
	1/2	NAS387-632-8P	\$0.10		3/4	NAS387-1032-12P	\$0.26	
	5/8	NAS387-632-10P	\$0.16		7/8	NAS387-1032-14P	\$0.30	
	3/4	NAS387-632-12P	\$0.16		1	NAS387-1032-16P	\$0.30	
8-32	1/2	NAS387-832-8P	\$0.20		1-1/8	NAS387-1032-18P	---	
	5/8	NAS387-832-10P	\$0.20		1-1/4	NAS387-1032-20P	\$0.29	
	3/4	NAS387-832-12P	\$0.24		1/2	NAS387-1032-24P	\$0.46	
	7/8	NAS387-832-14P	\$0.30					