


# FILLISTER HEAD SCREWS - DRIVE SCREWS



## AN500, AN501 FILLISTER HEADSCREWS

AN500 (coarse thread) & AN501 (fine thread) slotted fillister head screws are fabricated from carbon steel. Tensile strength 60,000 PSI. Cadmium plated, Type II Class 3. If there is an "A" after the dash, the part is cadmium plated, Type II, Class 3, with a drilled head. If there isn't an "A" after the dash, the part is Cadmium plated, Type I.

HA

AN500					
AN500 Dash No.*	MS35265 Dash No.	Length (In.)	Thread Size	Price ea. Drilled	Price ea. Undrilled
-A4-3	MS35265-12	3/16	4-40	\$0.20	---
-A4-4	MS35265-13	1/4	4-40	\$0.25	---
-A4-5	MS35265-14	5/16	4-40	\$0.27	---
-A4-6	MS35265-15	3/8	4-40	\$0.46	---
-A4-7	MS35265-16	7/16	4-40	\$0.23	---
-A4-8	MS35265-17	1/2	4-40	\$0.26	---
-A4-10	MS35265-18	5/8	4-40	\$0.24	---
-A4-12	MS35265-19	3/4	4-40	\$0.24	---
-A6-4	MS35265-26	1/4	6-32	\$0.43	\$0.34
-A6-5	MS35265-27	5/16	6-32	\$0.22	---
-A6-6	MS35265-28	3/8	6-32	\$0.19	\$0.38
-A6-7	MS35265-29	7/16	6-32	\$0.25	---
-A6-8	MS35265-30	1/2	6-32	\$0.20	---
-A6-10	MS35265-31	5/8	6-32	---	---
-A6-12	MS35265-32	3/4	6-32	\$0.27	---
-A6-14	MS35265-33	7/8	6-32	\$0.28	---
-A8-4	MS35265-41	1/4	8-32	\$0.31	---
-A8-5	MS35265-42	5/16	8-32	\$0.66	---
-A8-6	MS35265-43	3/8	8-32	\$0.19	---
-A8-7	MS35265-44	7/16	8-32	\$0.27	---
-A8-8	MS35265-45	1/2	8-32	\$0.24	\$0.78
-A8-10	MS35265-46	5/8	8-32	\$0.26	---
-A8-12	MS35265-47	3/4	8-32	\$0.25	---
-A8-14	MS35265-48	7/8	8-32	\$0.23	---
-A8-16	MS35265-49	1	8-32	\$0.60	---
-A10-4	MS35265-59	1/4	10-24	\$0.53	---
-A10-5	MS35265-60	5/16	10-24	\$0.83	---
-A10-6	MS35265-61	3/8	10-24	\$0.31	---
-A10-7	MS35265-62	7/16	10-24	\$0.27	---
-A10-8	MS35265-63	1/2	10-24	\$0.29	---
-A10-10	MS35265-64	5/8	10-24	\$0.27	---
-A10-12	MS35265-65	3/4	10-24	\$0.25	---
-A10-16	MS35265-66	1	10-24	\$0.64	---
-A416-8	MS35265-79	1/2	1/4-20	\$0.96	---
-A416-10	MS35265-80	5/8	1/4-20	\$0.69	---
-416-12	MS35265-81	3/4	1/4-20	\$0.42	---
AN501					
AN501 Dash No.*	MS35266 Dash No.	Length (In.)	Thread Size	Price ea. Drilled	Price ea. Undrilled
-8-12	-47	3/4	8-36	---	---
-A10-4	-59	1/4	10-32	\$0.40	---
-A10-6	-61	3/8	10-32	\$0.65	---
-A10-8	-63	1/2	10-32	\$0.28	---
-A10-10	-64	5/8	10-32	\$0.25	---
-A10-12	-65	3/4	10-32	\$0.25	---
-A10-14	-66	7/8	10-32	\$0.27	---
-A10-16	-67	1	10-32	\$0.29	---
-A10-20	-68	1-1/4	10-32	\$0.33	---

AN500AD Stainless Steel					
AN500 Dash No.*	MS35275 Dash No.	Length (In.)	Thread Size	Price ea. Drilled	Price ea. Undrilled
-AD2-2	-201	1/8	2/56	\$0.60	---
-AD2-3	-202	3/16	2/56	\$0.29	---
-AD2-4	-203	1/4	2/56	\$0.29	---
-AD2-5	-204	5/16	2/56	\$0.45	---
-AD2-6	-205	3/8	2/56	\$0.46	---
-AD2-7	-206	7/16	2/56	\$0.54	---
-AD2-8	-207	1/2	2/56	\$0.35	---
-AD2-10	-208	5/8	2/56	\$0.29	---
-AD2-12	-209	3/4	2/56	\$0.38	---
-AD4-2	-211	1/8	4-40	\$0.73	---
-AD4-3	-212	3/16	4-40	\$0.24	---
-AD4-4	-213	1/4	4-40	\$0.31	---
-AD4-6	-215	3/8	4-40	\$0.33	---
-AD4-7	-216	7/16	4-40	\$0.32	---
-AD4-8	-217	1/2	4-40	\$0.26	---
-AD4-10	-218	5/8	4-40	\$0.43	---
-AD4-12	-219	3/4	4-40	\$0.33	---
-AD4-14	-220	7/8	4-40	\$0.33	---
-AD4-16	-221	1	4-40	\$0.35	---
-AD6-4	-226	1/4	6-32	\$0.29	---
-AD6-5	-227	5/16	6-32	\$0.25	---
-AD6-6	-228	3/8	6-32	\$0.34	---
-AD6-7	-229	7/16	6-32	\$0.37	---
-AD6-8	-230	1/2	6-32	\$0.25	---
-AD6-10	-231	5/8	6-32	\$0.32	---
-AD6-12	-232	3/4	6-32	\$0.33	---
-AD6-14	-233	7/8	6-32	\$0.39	---
-AD6-16	-234	1	6-32	\$0.36	---
-AD8-5	-242	5/16	8-32	\$0.33	---
-AD8-6	-243	3/8	8-32	\$0.27	---
-AD8-7	-244	7/16	8-32	\$0.34	---
-AD8-8	-245	1/2	8-32	\$0.34	---
-AD8-10	-246	5/8	8-32	\$0.34	---
-AD8-12	-247	3/4	8-32	\$0.35	---
-AD8-14	-248	7/8	8-32	\$0.35	---
-AD8-16	-249	1	8-32	\$0.45	---
AN501AD Stainless Steel					
AN501 Dash No.*	MS35276 Dash No.	Length (In.)	Thread Size	Price ea. Drilled	Price ea. Undrilled
-AD10-5	-260	5/16	10-32	\$0.43	---
-AD10-6	-261	3/8	10-32	\$0.48	---
-AD10-7	-262	7/16	10-32	\$0.33	---
-AD10-8	-263	1/2	10-32	\$0.38	---
-AD10-10	-264	5/8	10-32	\$0.42	---
-AD10-12	-265	3/4	10-32	\$0.44	---
-AD10-14	-266	7/8	10-32	\$0.55	---
-AD10-16	-267	1	10-32	\$0.57	---



## AN502, AN503 FILLISTER HEAD SCREWS

AN502 (fine thread) and AN503 (coarse thread) drilled head, slotted fillister head screws are fabricated from steel meeting specification MIL-S-6050. Tensile strength 125,000 PSI. Cadmium plated, Type I, Class 3.

### AN502

AN502 Dash No.*	Length (In.)	Thread Size	Price Each	AN502 Dash No.*	Length (In.)	Thread Size	Price Each
-10-5	19/64	10-32	\$0.74	-10-12	3/4	10-32	\$0.37
-10-6	3/8	10-32	\$0.27	-10-16	1	10-32	\$0.46
-10-8	1/2	10-32	\$0.41	-416-12	3/4	1/4-28	\$1.24
-10-10	5/8	10-32	\$0.37	-416-16	1	1/4-28	\$1.61

### AN503

AN503 Dash No.*	Length (In.)	Thread Size	Price Each	AN503 Dash No.*	Length (In.)	Thread Size	Price Each
-6-4	1/4	6-32	\$0.44	-10-6	3/8	10-24	\$0.44
-6-6	3/8	6-32	\$0.26	-10-8	1/2	10-24	\$0.43
-8-4	1/4	8-32	\$0.26	-10-10	5/8	10-24	\$0.47
-8-6	3/8	8-32	\$0.26	-10-12	3/4	10-24	\$0.39
-8-8	1/2	8-32	\$0.39	-10-16	1	10-24	\$0.85
-8-10	5/8	8-32	\$0.35	-10-24	1-1/2	10-24	\$0.57
-8-16	1	8-32	\$0.42	-416-8	1/2	1/4-20	\$0.63
				-416-10	5/8	1/4-20	\$0.77
				-416-12	3/4	1/4-20	\$0.92