

# FUEL TRANSFER PUMPS – FUNNELS

## FUEL FILTER FUNNELS



Mr. Funnel® Fuel Filters are simply amazing. Dirty fuel in.... pure fuel out. It's that easy. The specially designed filter removes water and dirt from gas, even 2-stroke mixtures. Ethanol attracts water more than regular gasoline. Never before has a fuel filter been more important. Dirt and water are practically unavoidable in stored fuel, causing microbial growth, corrosive acids, electrolysis and rust. These contaminants can plug filters, corrode components, decrease efficient combustion and cause engine shutdown or system failure. When fuel is poured through the Fuel Filter Funnel, water and debris will not pass through the filter's fluoropolymer-coated stainless steel filter. Only filtered fuel flows through to your engine, improving its efficiency, durability, and proper operation. The sump area collects the deflected water and debris for proper disposal. The Fuel Filter Funnel will filter gasoline, diesel, heating oil, kerosene and 2-cycle mixed gas. The Fuel Filter Funnel is a heavy-duty, anti-static, and fast flow funnel with built-in filter technology. Lawn mowers, tractors weed trimmer/blowers, dirt bikes/ATVs, boats, even airplanes... will have longer useful lives if owners filter their fuel!

Part No.	Height	Diameter	Flow Rate	Price
05-00026	6.00"	3.5"	2.7 gpm	\$21.50
05-01054	8.75"	5.5"	3.9 gpm	\$29.75
05-01055	10.00"	8.5"	5.0 gpm	\$39.65
05-01371	10.00"	8.5"	12-15 gpm	\$68.90

## GOATTHROAT FUEL TRANSFER PUMP



GoatThroat Pumps have been in the industrial market for 15 years. Recently introduced to aviators, these pumps deliver fuel efficiently and directly to the filler downspout with a finger controlled discharge nozzle. Made of chemical grade polypropylene, GoatThroat Pumps can pressurize any container in seconds. Internal pressure relief valve opens at 7 psi, but 2 psi is all you need to deliver fuel safely to your plane. A drip-proof faucet dispenses small amount or gives steady flow. Containers remain upright, so there is no extra handling and little chance for accidental spills. Includes the fitting for a 55 gal. drum. 5 gal. can fitting sold separately.

Fuel Transfer Pump.....P/N 05-02196.....\$209.00  
 Adapter for Blitz 5 gal. can.....P/N 05-02197.....\$58.95  
 Adapter for Scepter 5 gal. can.....P/N 05-03031.....\$72.75

**ORDER ONLINE!**

[www.aircraftspruce.com](http://www.aircraftspruce.com)

- 100,000 Parts!
- 24 Hour Access!
- Fast, Easy Navigation!

## OIL / WATER RESERVOIR TANK



Constructed of high density polyethylene, this blow molded multi-purpose tank offers excellent durability and resistance to most chemical and fluids. All sizes nominal. Height includes neck & fittings. Width includes mounting tabs. Max working temperature is 180-deg F and max working pressure is 5 PSI.

**Features:** • Blow molded seamless wall construction • Height with neck: 6.67" • Some tanks have rugged mounting tabs with slots • Tanks are UV resistant, accessories are not • 100% leak tested prior to shipment • Do not meet CARB/EPA requirements; not for fuel • Maximum pressure: 5 psi • Maximum temperature: 180°F

• (2.25" Neck) .....P/N 15-08320 .....\$15.80

## VP SPORTSMANS CONTAINERS



These 5 gallon polyurethane ventilated containers are ideal for most motorsport fuels. The Sportsman's Container is a rugged, multipurpose tool that has a multitude of applications in the hangar and on the runway. This 5-gallon workhorse is FDA-approved for the storage of water and is also great for aircraft fluids, oils and industrial liquids. The Sportsman's Container is made using 30% more plastic than the standard 5-gallon containers and therefore designed to handle the rough treatment inherent in the maintenance and upkeep of your aviation equipment.

AP

Description	Part Number	Price
White Square	05-06953	\$33.50
White Round	05-06955	\$35.99
Blue Square	05-06954	\$37.50
Blue Round	05-06956	\$38.50
Accessories		
Replacement Cap	05-06957	\$7.85
Replacement Vent Cap	05-06958	\$1.70
Deluxe Hose	05-06959	\$10.50
Syphon Pump	05-06960	\$28.50
Large Funnel with Filter	05-06961	\$46.85



## OIL INJECTION / WATER OVERFLOW RESERVOIRS

High density polyethylene tanks; ideal for Oil Injection Reservoir or Coolant/Water Overflow. Translucent white color easily shows fluid level. Tank is blown molded with a 1/4" thick seamless construction and includes rugged mounting tabs that mount to any flat surface. Includes a threaded 2-1/4" vented cap with tether to prevent loss. Sealed tank without drain, bottom access is easy for either push in fittings or threaded bulkheads with plenty of access thru large cap opening.

1 Quart: 7.74" high x 6.2" wide x 1/4" thick. Weight 10 oz. \*\*Includes 1/4" barb spigot molded on bottom\*\* .....P/N 15-06828 .....\$36.60  
 1.5 Quart: 7.74" high x 5.9" wide x 1/4" thick. Weight 12 oz.  
 P/N 15-06830 .....\$22.00  
 2 Quart: 5" high x 6" wide x 1/4" thick. Weight 8 oz.  
 P/N 15-06936 .....\$25.75  
 4 Quart: 8-1/2" high x 6" wide x 1/4" thick. Weight 20 oz.  
 P/N 15-04841 .....\$26.25  
 Replacement 2-1/4" Vented, Black, Nylon Cap.  
 P/N 15-06936-1 .....\$4.80