

# TURN COORDINATORS – TURN & BANKS

## RC ALLEN TURN COORDINATOR 3 INCH INDICATORS



Used in many production aircraft. Incorporates an electrical Gyro Turn Indicator with an inclinometer. The inclinometer, by movement of a ball in relation to the lubber lines, indicates the slip angle of aircraft while in a turn. The airplane on the dial rotates with reference to the indices. A power failure flag drops into view whenever the supply voltage is lost or when voltage has dropped below a level acceptable for proper operation of the gyro. Operates on 14 to 28V DC. New manufacture. First installation requires electrical connector and clamp.

**Dimensions:** Length: 6 1/5 in. Max, Width: 3 3/8 in Max, Height: 3 3/8 in Max, Weight: 1.9 lbs. Meets or exceeds requirements of FAA TSO C3b

Description	Model	Part No.	Price
Unlighted - Mating Connector: MS3106A-10SL-3S	RCA82A-11	10-01372	<b>\$949.00</b>
Lighted (14V) - Mating Connector: MS3106A-10SL-3S	RCA83A-11-14	10-00485	<b>\$1,075.00</b>
Lighted (28V) - Mating Connector: MS3106A-10SL-3S	RCA83A-11-28	10-01685	<b>\$1,065.00</b>
Mating Connector	MS3106A-10SL-3S	10-00789	<b>\$26.50</b>



## WINTER SLIP INDICATORS

The basic flight instrument for co-ordinated turns. Available in two styles: Rectangular model fits easily in cramped panel space. Square model matches a 2-1/4" instrument hole, fits on either side of the panel. Both feature finely crafted metal cases and precision ball and tube assemblies.

Square.....P/N 10-03812 .....**\$93.75**  
Rectangle.....P/N 10-03857 .....**\$114.75**

## BANK INDICATORS (BALL TYPE)



In turning, instantly register slightest departure from the correct banking angle. Bank scale has white markings on black background. New manufacture. Available in 2 models:

10°-10° Scale, 2.25" between mounting holes.  
P/N 10-00600 .....**\$127.75**  
20° - 20° Scale, 5" between mounting holes.  
P/N 10-00700 .....**\$75.75**

## SWIFT BANK INCLINOMETER



The bank indicator has the function of slip indication. A very practical and simple instrument. It can be installed on an LSA, it is particularly useful in flight training.

Center distance of two Installation Holes is 48.6mm.  
P/N 10-06984 .....**\$153.80**

## MID-CONTINENT INSTRUMENTS TURN & SLIP INDICATOR



2 Inch - Widely used in the turbo-prop market as standard equipment, this dependable instrument fits into the tightest panel space. The AC brushless rotor offers great reliability. Internal lighting options of 5, 14 and 28 volt offer greater flexibility. These were factory installed on the DeHavilland Dash 8 and Boeing Chinook CH47

14V Turn & Slip...P/N 10-00305 .....**\$2,550.00**  
28V Turn & Slip...P/N 10-00310 .....**\$2,550.00**



## CABLE CLAMP MS3057-4A

This MS3057-4A can be used with Turn Coordinator TC02E-3-2 or Turn & Bank Indicator TB02E-2-1 .....P/N 11-04969 .....**\$4.80**

## MID-CONTINENT INSTRUMENTS TURN & SLIP (ELECTRIC)



Built-in voltage regulator allows it to be used in either 14V or 28V systems. Small, compact unit and weighs only 1.2 lbs. Incorporates a small "power out" warning window which is black when normal current is being supplied but turns red in the case of electrical power failure. This turn and bank is now being used in many production aircraft. New installation requires electrical connector and cable clamp. New manufacture by Electrical Gyro Corp.  
Size: 3-3/8" x 3-3/8" x 3-3/4" long.

Unlighted ..... P/N 1234T100. **\$1,317.00**  
14V Bezel-Lit ..... P/N 10-22614. **\$1,725.00**  
28V Bezel-Lit ..... P/N 10-22628. **\$1,725.00**  
MS3106A-10SL-3S Electrical Plug Connector.. P/N 10-00789.....**\$26.50**

## MID-CONTINENT INSTRUMENTS TURN COORDINATORS (ELECTRIC)



Certified to FAA TSO C3b. OEM standard - proven reliability. Includes power warning indicator. **Features:** - 4500 hours MTBF, more than double the original "Z" design - Brushless AC rotor operates on 14 or 28 VDC - Proven reliability through HALT (Highly Accelerated Life Testing) requirements and OEM usage since 1999 - Improved "Off" warning flag pulls out of view when rotor is up to speed - Is a direct replacement for the popular 1394T100-7Z and most standard 3-pin turn coordinators.

1394T100-7B Unlighted 12-32V..... P/N 10-02108.....**\$976.00**  
28V unit- 11-32V Bezel Lighting..... P/N 10-01024. **\$1,295.00**  
14V unit- 11-32V Bezel Lighting..... P/N 10-01025. **\$1,228.00**  
Unlighted G300A Autopilot, ARC..... P/N 10-02653. **\$1,922.00**  
1394T100-10RB (Cessna, KAP 140, Autopilot).. P/N 10-02311. **\$1,996.00**  
1394T100-14RB Low Wing Turn Coordinator Autopilot -  
For use on low wing aircraft. .... P/N 10-04022. **\$1,997.00**  
MS3106A-10SL-3S Electrical Plug Connector... P/N 10-00789.....**\$26.50**

## RC ALLEN TURN & BANK (ELECTRIC)



Instrument is powered by an electrically driven DC precision gyro with an inclinometer. It gives the pilot turn and bank information. The RCA56 series is an all volt instrument, with a power warning flag, a black or white ball inclinometer and either lighted or non-lighted. DIMENSIONS: Length: 6 1/4 in. Max Width: 3 3/8 in. Max Height: 3 3/8 in. Max Weight: 1.9 lbs.

Meets or exceeds requirements of FAA TSO C3b. New manufacture by A.I.D. RC Allen. New installation requires plug connector & cable clamp.  
RCA56-3B, UNLIT ..... P/N 10-01684 .....**\$949.00**  
RCA56-3BL, LIT ..... P/N 10-02138 .....**\$1,065.00**

## AN5820-1 TURN & BANK (VACUUM)



AN5820-1 Turn & Bank indicator completely overhauled and certified to FAA requirements. Fresh matte-white dial markings with "dog-houses". Power: 1.8" to 2.2" Hg vacuum produced by a 2" venturi or vacuum pump. Size: 3.25"x 3.25"x 4.75" long. Weight: 1.5 lbs. 1 year warranty .....P/N AN5820-1 .....**\$526.00**



## TURN & BANK KIT

Consists of an overhauled and certified Turn & Bank indicator, 2" venturi, hoses, fittings and instrument screws. P/N 10-00300 .....**\$625.00**