

UL FLIGHT LINE INSTRUMENTS



UL FLIGHT LINE 2 INCH CHT GAUGE

Gauge electrical, bezel black dial, black, white, pointer red Indicating instrument electrical, black bezel, black dial, white character, pointers red.

- Front: Flat; Black
- Glass: Flat
- Pointer: Red, Hub Black, Night Design

- Dial Face: Background Dull Black, White, Red, Green
 - Installation: Fixation Ring
 - Operating Temperature: 50°C - 150°C / 120°F - 300°F
 - Voltage: 12
 - Dimension: 52 mm
 - Engines: 912A, 912F, 912UL, 912S, 912ULS, 914F, 914UL
 - Illumination: LED White, Dimmable
- 2" CHT 50-150C 150-300F P/N 13-16017 **\$94.80**
 2" CHT 50-150C 125-300F P/N 13-16026 **\$88.85**



UL FLIGHT LINE 2 INCH FUEL LEVEL 0-4/4 UL LSA 12V DLT

Gauge electrical, bezel black dial, black, white, pointer red indicating instrument electrical, black bezel, black dial, white character, pointers red.

- 2" Fuel Level 0-4/4 UI DLT3-180 P/N 13-16019 **\$86.75**
 2" Fuel Level 0-4/4 UI DLT5-60/90 P/N 13-16020 **\$73.95**



UL FLIGHT LINE 2 INCH GAUGE

Gauge electrical, bezel black dial, black, white, pointer red indicating instrument electrical, black bezel, black dial, white character, pointers red.

- Front: Flat; Black
- Glass: Flat
- Pointer: Red, Hub Black, Night Design
- Dial Face: Background Dull Black, White, Red, Green

- Installation: Fixation Ring
 - Operating Temperature: 25°C - 65°C / 120°F - 300°F
 - Voltage: 12
 - Dimension: 52 mm
 - Engines: 912A, 912F, 912UL, 912S, 912ULS, 914F, 914UL
 - Illumination: LED White, Dimmable
- 2" Oil Pressure Gauge 0 - 10 Bar P/N 13-16021 **\$115.75**
 2" Oil Temperature Gauge 0-10 Bar 0-150 PSI . P/N 13-16025..... **\$84.75**



UL FLIGHT LINE 2 INCH TACHOMETER

Gauge electrical, bezel black dial, black, white, pointer red indicating instrument electrical, black bezel, black dial, white character, pointers red.

- 2" Engine Tach 0-7000 12v P/N 13-16023 **\$239.95**
 2" Rotor Tach 0-7000 12v P/N 13-16024 **\$220.95**

UL FLIGHTLINE WING FLAP INDICATOR

Indicating Instrument Electrical. LED Backlight Technology. Stepper Motor. Low Weight. Character White. Wing Flap Sensor.

- Specifications:**
- Operating voltage: 12
 - Installation diameter: 52mm
 - Resistance range: 3.180
 - Special: MF, Option Warn-LED.
- Indicator P/N 10-06466 **\$79.95**
 Angle Transmitter P/N 10-06467 **\$67.75**



UL FLIGHT TEMP GAUGE

Gauge electrical, bezel black dial, black, white, pointer red Indicating instrument electrical, black bezel, black dial, white character, pointers red.

P/N 13-19001 **\$90.75**



UL FLIGHT LINE TEMP SENDER

UL Flight Line Temp Sender 150C M10x1 M10x5 T-6 T-3.
 P/N 13-16029 **\$22.90**



UL FLIGHT LINE 2 INCH FUEL PRESSURE GAUGE

Fuel Pressure Gauge Rotax Flight Line. Gauge electrical, bezel black dial, black, white, pointer red indicating instrument electrical, black bezel, black dial, white character, pointers red.

- Front: Flat; Black
 - Glass: Flat
 - Pointer: Red, Hub Black, Night Design
 - Dial Face: Background Dull Black, White, Red, Green
 - Installation: Fixation Ring
 - Bar: 0 - 1
 - Voltage: 12
 - Dimension: 52 mm
 - Engines: 912A, 912F, 912UL, 912S, 912ULS, 914F, 914UL
 - Illumination: LED White, Dimmable.
- P/N 13-16022 **\$116.75**



UL FLIGHT LINE 2 INCH VOLTMETER

Gauge electric, incident-light, black bezel, black dial, white, pointer red Indicating instrument electrical, floodlight illumination, black bezel, black dial, white character, pointers red. 8-16V UL / LSA.

- Front: Flat; Black
 - Glass: Flat
 - Pointer: Red, Hub Black, Night Design
 - Dial Face: Background Dull Black, White, Red, Green
 - Installation: Fixation Ring
 - Operating Temperature: 8°C - 16°C
 - Voltage: 12
 - Dimension: 52 mm
 - Engines: 912A, 912F, 912UL, 912S, 912ULS, 914F, 914UL
 - Illumination: LED White, Dimmable
- P/N 13-16027 **\$96.99**

UL FLIGHT LINE FUEL PRESSURE CONNECTOR CABLE



UL Flight Line Fuel Pressure Connector Cable.

- Connection: 3-wire DLPHI Packard
- Engines: 912A, 912F, 912UL, 912S, 912ULS, 914F, 914UL

P/N 13-16018 **\$29.60**

UL FLIGHTLINE 2 INCH FUEL LEVEL GAUGE



Fuel level gauge for float-operated sensor UL/LSA. Indicating instrument electrical, LED backlight technology, stepper motor, low weight, character white.

- Specifications:**
- Operating voltage: 12
 - Installation diameter: 52mm
 - Volume range: 0.1/2.1
 - Resistance range: 3.18
 - Special: MF, Option Warn-LED
- P/N 10-06471 **\$87.75**

UL FLIGHTLINE FLOAT OPERATED SENSOR RIGHT WING



Float-operated sensor. Robust passivated metal housing.

- Specifications:**
- Dimensions float-operat. sensor install. lateral: 156 / 148 / 107
 - Full resistance: 180
 - Empty resistance: 3
 - Diameter of pitch circle and angle: 54 / 72°; 68°; 80°; 68°; 72°
 - Operating voltage: 6.24
 - Electrical connection: DIN 6.3x0.8
- Right Wing Sensor P/N 10-06468 **\$63.75**
 Left Wing Sensor P/N 10-06469 **\$62.75**

FUEL LEVEL SENDERS



- ISS Fuel Sender LH 6-12 Tank P/N 10-01099 **\$49.95**
 ISS Fuel Sender RH 6-12 Tank P/N 10-01101 **\$52.75**
 ISS Fuel Sender LH 10-15 Tank P/N 10-01102 **\$42.95**
 ISS Fuel Sender RH 10-15 Tank P/N 10-01103 **\$41.85**
 ISS Fuel Sender LH 15-5-24 P/N 10-01104 **\$44.50**
 ISS Fuel Sender RH 27-36" Tank P/N 10-01107 **\$57.25**
 ISS Fuel Sender Gasket P/N 10-01097 **\$2.64**

IN