
CAMLOC FASTENERS

The 2600 and 2700 series Camloc fasteners exceed requirements for MIL-F-5591, Style 3, Size 2. Shear and tensile strength: 300 lbs. (ultimate), 200 lbs. (rated). Studs and washers listed are made of steel. The receptacles are made of copper base alloy. All components listed are rated to 450° F. The 4002 series fasteners are considerably stronger than the 2600 and 2700 series. Shear and tensile strength: 1050 lbs. (ultimate), 700 lbs. (rated). All studs and grommets listed are made of steel. Rated to 450° F.



Dash No.	CAD Plated		Stainless		CAD Plated	
	2600 Slot Price Ea	26S8 Phillips Price Ea	Dash No.	2600 Slot Price Ea	Wing CAD Plated	Price Each
-1	\$6.60	\$9.50	-1S	\$11.50		
-2	\$6.90	\$2.90	-2S	\$8.50	2600-2W	\$36.85
-3	\$5.40	\$2.45	-3S	\$7.70	2600-3W	\$19.90
-4	\$3.55		-4S	\$4.35	2600-4W	\$19.65
-5	\$5.85		-5S	\$5.35	2600-5W	\$19.80
-6	\$4.50		-6S	\$11.95	2600-6W	\$17.50
-7	\$13.80		-7S		2600-7W	
-8	\$4.45		-8S	\$3.35	2600-8W	\$59.75
-9	\$11.65		-9S		2600-9W	\$23.50
-10	\$7.95		-10S		2600-10W	\$22.60
-11	\$11.95				2600-11W	
-12	\$7.90				2600-12W	\$21.70
-13	\$8.95					
-14					2600-14W	

2700 SERIES STUDS

	2700 0211120 01020						
	CAD	Plated	Stainless				
Dash No.	2700 Slot Price Ea	27S3 Phillips Price Ea	Dash No.	2700 Slot Price Ea			
-1	\$13.50	\$12.75	-1S	\$6.55			
-2	\$10.70	\$6.65	-2S	\$5.35			
-3	\$11.50	\$7.50	-3S	\$13.75			
-4	\$7.60	\$8.50	-4S	\$6.90			
-5	\$11.80	\$7.55	-5S	\$7.95			
-6	\$8.50	\$12.50	-6S	\$8.55			
-7	\$9.65	\$17.65	-7S	\$6.50			
-8	\$7.75	\$13.65	-8S	\$7.50			
-9	\$10.95	\$9.85	-9S				
-10		\$11.45	-10S				
-11	\$7.35		-11S				
-12		\$11.50	-12S	\$13.90			
-13		\$17.95	-13S				
-14							

4002 SERIES STUDS

		CAD Plated / Stainless						
Dash No.	4002 CAD Plated Slot	40S5 CAD Plated Phillips	SS Phillips 40S5	Price Each	Dash No.	4002 SS Slot Price Ea	Wing CAD Plated	Price Each
-2	Price Ea \$11.50	Price Ea \$5.55	40S5-2S	¢17 E0	-2S	\$15.70	4002-2W	
-3	\$5.35	\$4.35	40S5-3S	\$4.65	-3S	\$38.50	4002-3W	
-4	\$7.90	\$14.95	40S5-4S	\$6.50	-4S	\$8.75	4002-4W	
-5	\$3.25	\$6.90	40S5-5S	\$2.95	-5S	\$11.85	4002-5W	\$20.75
-6	\$9.50	\$13.70	40S5-6S	\$6.50	-6S	\$11.95	4002-6W	\$19.85
-7	\$2.75	\$9.50	40S5-7S	\$5.35	-7S	\$22.85		
-8	\$9.50	\$6.50	40S5-8S	\$6.35	-8S	\$7.50	4002-8W	\$21.75
-9	\$4.35	\$13.45	40S5-9S	\$11.60	-9S	\$20.65	4002-9W	\$37.50
-10	\$8.95		40S5-10S	\$13.50			4002-10W	
-11	\$8.60	-					4002-11W	
-12	\$7.90						4002-12W	
-13		-						
-14	\$12.70	\$9.50						
-15	\$7.50	\$9.50						
-16	\$31.75							
-17	\$22.50							

RECEPTACLES

2600 Series - Small enough to fit in limited mounting space and light weight. All of these fasteners have a 600# ultimate tensile load capacity. 4200 Series - The Modern Standard in Quick Release Fastening Systems. They have an 800# working strength and 1050# Ultimate Tensile load capacity.



Rivet	2600, 2700	Price	4002 Series	Price
Holes	Series Part No.	Each	Part No.	Each
Plain	212-12N	\$3.65	214-16N	\$5.40
Countersunk	212-12ND*	\$5.35	214-16ND*	\$8.90
Plain	Floating Bronze		244-16	\$8.90

2600 / 2700 SERIES STUD LENGTH SELECTION

P (panei tnickness)	
F (frame thickness	+ .062
GRIP (total thickness)	= .124
P+F = G	_ _

P+F = G	↓ ⊢F
	P+
	1

STUD SELECTION TABLE Using 212-12 Receptacle						
Total Grip Thickness	Use 2600	Use 2700				
.020059	2600-1	2700-1				
.060089	2600-2	2700-2				
.090119	2600-3	2700-3				
.120149	2600-4	2700-4				
.150179	2600-5	2700-5				
.180209	2600-6	2700-6				
.210239	2600-7	2700-7				
.240269	2600-8	2700-8				
.270299	2600-9	2700-9				
.300329	2600-10	2700-10				
.330359	2600-11	2700-11				
.360389	2600-12	2700-12				
.390419	2600-13	2700-13				
.420449	2600-14	2700-14				

4002 SERIES (LARGE HEAD) STUD SELECTION

To select the proper length stud, first select the grommet, for example 4002-G. Next, select the receptacle, such as 214-16. After determining the total grip thickness, use the grommet column under which the selected grommet and receptacle appear. Use the dash number which appears opposite the determined total grip thickness.

Example: If the total determined grip thickness "G" was. 144, the stud dash number for the above 4002-G grommet and 214-16 receptacle would be -4. The stud part number would be 4002-4.

Total Grip Thickness	Stud Dash Number			
Range "G"	4002-G Grommet & 214-16 Receptacle	4002-N, 4002-0 Grommet & 214-16 Receptacle		
.021050	*	-1		
.055080	*	-2		
.081110	-2*	-3		
.111140	-3	-4		
.141170	-4	-5		
.171200	-5	-6		
.201230	-6	-7		
.231260	-7	-8		
.261290	-8	-9		
.291320	-9	-10		
.321350	-10	-11		
.351380	-11	-12		
.381410	-12	-13		
.411440	-13	-14		
.441470	-14	-15		
.471500	-15	-16		
.501530	-16	-17		
.531560	-17	-		

*4002-G grommet requires .090" minimum grip.

2600, 2700 SERIES RETAINING WASHERS

Retaining washers are required for studs of -5 length or greater. Use split washer 2600-SW2 where it is desirable to have the stud fall away for minimum internal projection. Use internal tooth washer 2600-LW where it is desirable to retain the stud assembly rigidly.

P/N 2600-SW-2\$2.45 P/N 2600-LW\$0.99
4002 SERIES GROMMETS & SNAP RINGS



Description	Part No.	Price				
CAD Plated						
Flush Grommet	4002-G	\$1.40				
Flush Grommet	4002-H	\$4.45				
Plus-Flush Grommet	4002-N	\$2.30				
Stud Retaining Grommet	4002-O	\$3.50				
High Shear Flush Grommet	40G1-5	\$4.95				
Wide Area Grommet	4002-N3	\$5.35				
Grommet Retaining Ring	R4G	\$1.25				
Camloc Retaining Ring	4002-SW	\$2.75				
High Shear Grommet Retaining Ring	R4T	\$5.70				
Stainless						
High Shear Grommet Retaining Ring	40G26-1	\$2.60				
Flush Grommet	4002-GS	\$3.65				
Flush Grommet	4002-HS	\$6.50				
Plus Flush Grommet	4002-NS	\$6.50				
Flush Grommet	4002-OS	\$4.60				

SKYBOLT CAMLOC RETAINING RING SK-R4T