RODUC

LPS LOW SURFACE TENSION (LST)



A deep penetrating formulation attacks rust and corrosion to free "frozen" parts. LST has an extremely low surface tension that com-bines with a powerful foaming action to provide complete surface coverage, better penetration and improved moisture displacement.

LPS COPPER ANTI-SEIZE

Prevents seizure up to 1800°F (982°C). Lead free. Protects against seizure, heat-freeze, galling, rust and corrosion. Brushes easily. Highly adhesive on both wet and dry surfaces. Will not run, drip or settle out. Conforms to Mil-PRF-907E. Ideal for use on stainless steel and for joining dissimilar metals. Copper color 1/2 lb. can ... P/N 09-02908 \$26.95

LPS MAGNUM TEFLON LUBRICANT

LPS® Magnum Teflon® Lubricant provides ultra-high lubricity, plus the additive strength of Teflon® for high-temperature, highpressure environments. In even the most demanding situations, . extend equipment life and reduce maintenance.

11 oz.Spray Can......P/N 09-26430\$18.85

LPS® HEAVY-DUTY SILICONE LUBRICANT

Meets FDA regulation for incidental food contact. Silicone-rich formula. Water-based formula. Colorless, odorless & non staining. Ideal for rubber and plastic surfaces. Eliminates sticking, binding and squeaking. Does not contain chlorinated solvents. Safe on most surfaces NSF® H1 registered. 13oz. (368g) - aerosol P/N 09-26410.....\$15.95



CS

LPS FOOD GRADE SILICONE LUBRICANT

Food Grade Silicone Lubricant is a non-staining, high quality, lubricant designed especially for the food industry for use as an anti-stick agent for chutes and slides.

10 oz..

LPS® COLDGALVANIZE CORROSION INHIBITOR

· Zinc purity greater than 99% · Works like a hot-dip on ferrous metals indoors and outdoors · Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C) Commonly used as a flash rust preventive on welded areas . Long term protection • Flexible coating will not yellow, chalk, crack or peel • Electrochemically protects bare metal • Dries to touch in 3 to 5 minutes • 14oz. (397g) – aerosol......P/N 09-26425......\$17.95

LPS KB-88 ULTIMATE PENETRANT

KB 88 has extremely high solvency and special additives to enhance penetration and attack corrosion. It makes the toughest maintenance job easier, faster, safer, and simpler. Formulated to KBS attack and quickly release rusted and corroded nuts, bolts, hinges, and other frozen components. High KB solvency value of 151 and low surface tension and penetrates faster and deeper than most other similar products in the market place. Displaces moisture with an aggressive formula that is NSF® Certified: H2 Registration # 138554

(Aerosol). This product is VOC compliant in all 50 states.	
13 oz	.50
20 ozP/N 09-04028\$24	
LPS NICKEL ANTI-SEIZE Contains no lead, copper or graphite • Prevents seizure u 2600°F (1427°C) • Protects against rust and corrosion • For us	ie in
hostile environments and • extreme temperatures • Acid resis • Strong resistance to water washoff • Brushable to -18°F (-27	
Will not run, drip or settle out Conforms to MIL-PRF-907E Silver color	. '
1/2 LbP/N 09-04833\$28	
1 LbP/N 09-04834\$44	
PART LPS T-91 NON-SOLVENT DEGREASER	
T-91 Non-Solvent Degreaser is biogradable, non-flamma and has a neutral pH. T-91 is an excellent replacement many solvent degreasers that have potential worker safet flammability concerns. T-91 is ideal for solvent cleaning, washers, and dip tanks and is more economical than m solvent degreasers in the marketplace. T-91 has an NSF [®] registration (#141975) for use in food plants.	for y or part nost A1
Gallon\$56 Case of 4 GallonsP/N 09-02309\$257	
	.95
LPS TRIFREE BRAKE CLEANER	
The heavy-duty solvent for removal of brake fluid, grease, oil, other contaminants.	and
Single	

LPS INSTANT SUPER DEGREASER 2.0

An industrial strength degreaser with no brominated solvents, trichlo-rethylene or perchloroethylene for an improved health and safety profile.

LPS® TKX® ALL-PURPOSE LUBRICANT



LPS®

• Nonflammable • Removes oil, grease, wax, dirt, moisture, tar, • Automation of the contaminants • Fast evaporating • Low odor • Quick penetration • No residue • Non-conductive • NSF K1 registration # 059809: (aerosol); # 059810: (bulk) 19oz. (539g) - aerosol P/N 09-26407 \$13.75



LPS 1[®] PREMIUM LUBRICANT

Provides a dry, thin lubricating film. Resists oil, dust and dirt buildup. Fast acting penetration. Displaces moisture Loosens rusted or frozen parts. Provides a short term, light corrosion resistant barrier. Nonconductive Ideal for delicate mechanisms. Used worldwide in aviation. Safe on paint and most plastics. 11oz. (312g) - aerosolP/N 09-25900\$17.85

1 gal. (3.78 I)\$72.75

2® HEAVY-DUTY LUBRICANT

Strong, multi-purpose lubricant and penetrant with added corrosion protection. Provides a nondrying, light, oily film for use on indoor/outdoor equipment. Reduces wear caused by friction and corrosion. Displaces moisture Loosens rusted or frozen parts. Provides up to one year of protection. Nonconductive Safe on paint and most plastics. Inverta Spray Valve allows user to spray

in an upright or inverted position. NSF	-® HZ registered.	
11oz. (312g) – aerosol	P/N 09-26100	\$17.50
20 oz. Spray		
1 gal. (3.78 l)		

LPS 3® PREMIER RUST INHIBITOR

· Forms a transparent, soft, waxy film for protection & lubrication · Inhibits rust & corrosion, protects steel parts indoors for up to two years · Penetrates to displace moisture · Does not contain chlorinated solvents or silicone · Safe on most surfaces · Stops rust and corrosion • Provides non-sling lubrication • Provides anti-seize coating • Inverta Spray Valve allows user to spray in an upright or inverted

position - Nor 112 registered #123021	. (aerosor), #003043 (bu	11K)
11oz. (312g) – aerosol	P/N 09-26300	\$21.85
20fl. oz. (591ml) – trigger		
1 gal (3 78 l)		

LPS® QB PRECISION DUSTER *



Patented formula - Patented US #6,342,471. Electrical contact cleaner. Cleans electrical parts without harming plastics. • Nonflammable · Plastic safe · Non-conductive · No residue · Replaces HCFC 141b contact cleaners · Fast evaporating · Conforms to CARB VOC requirements.

10 oz. spray can.....

LPS 2[®] BELT DRESSING

LPS Belt Dressing is formulated to extend belt life, prevent belt slippage and resist water wash out. Features: • May be used in wet, outdoor conditions • Does not deteriorate drive belts • Eliminates squeaks from slipping belts • NSF® Certified: H1 Registration # 134508 8 Metal detectable plastic components-



ChainMate® Chain & Wire Rope Lubricant is moly-fortified and will perform under severe loads and extreme temperatures. Fortified with molybdenum disulfide, increases chain and wire rope life, effective under extreme pressure and temperature ranges.

LPS A-151 SOLVENT DEGREASER



Easy-to-use, hand-kneadable stick for immediate repairs to steel equipment and surfaces. Ideal for stopping leaks, even works on underwater applications. Permanently fills gaps and holes in metal, concrete, wood, fiberglass, and ceramics. Has a working time of 4 minutes, and will fully cure in 30 minutes to form a durable mass which can be machined, drilled, and painted. Can be used for many types of repairs, such as plumbing, electrical, ceramic, vehicle, equipment, and machinery. It is ideal for patching holes and cracks in pipes, drums, and tanks. 4 oz. stick P/N 09-26444 \$17.50

ATTENTION: Volatile Organic Compounds (VOCs) Government Regulations: Product cannot be purchased, sold or used in the states listed below. CA, CT, DC, DE, IL, IN, ME, MD, MA, MI, NH, NJ, NY, OH, PA, RI, VA

NOTE: FOR CASE OF 12 CANS OF LPS PRODUCTS ADD -12 TO THE PART NUMBER.