H3R AVIATION FIRE EXTINGUISHERS



The FAA recommends and/or requires Halon fire extinguishers on aircraft. H3Rs Halon fire extinguishers are the extinguishers of choice in the aviation industry. They cause no mess or damage, and do not require taking a plane out of service for clean-up; a costly process for both the aircraft owner and insurance carrier. The heat-seeking quality of the Halon gas makes it a superior fire fighting agent.

DISPOSABLE, LOW-MAINTENANCE HALON 1211-1301 BLEND

Contain a proprietary blend of the "liquid streaming agent," Halon 1211, and the gaseous "total flooding agent," Halon 1301. The blend's power lies in the Halon 1301, which is both a firefighting agent and a propellant. Low maintenance and non-rechargeable. Lightweight aluminum canister Disposable. Tested to ANSI/UL 711 and UL 1093. Meets DOT requirements Meets the requirements in Advisory Circular 20-42C, "Hand Held Extinguishers for Aircraft" and/or NFPA 408, "Standard for Aircraft Hand Deathble Fire Evitaguishers included." Portable Fire Extinguishers" 12-year shelf life. Fire extinguishers include a mounting bracket.

RECHARGEABLE, STURDY INDUSTRY-STANDARD HALON 1211

Required on commercial transport aircraft. Although classified a "liquid streaming agent," Halon 1211 also performs remarkably well as a "total flooding agent," seeking out and extinguishing fires in inaccessible places. A 6-year maintenance and 12-year hydrostatic test are required. Rugged steel cylinder. Pressure gauge enables easy confirmation of charge. Tested to ANSI/UL 711 and UL 1093. Meets DOT requirements. Meets the requirements in Advisory Circular 20-42C, "Hand Held Extinguishers for Aircraft" and/or NFPA 408, "Standard for Aircraft Hand Portable Fire Extinguishers". Fire extinguishers include a mounting bracket or a wall hook.

H3R Extinguishers					
HALON 1211 UNITS	Part No.	Range	Price		
A344T - 1.3 lb. (UL Rating 2B:C)	13-01993	9-12 ft	\$294.00		
A344TC - 1.3 lb. (UL Rating 2B:C)	13-02546	9-12 ft	\$359.00		
C352TS - 2.5 lb. (UL Rating 5B:C)	13-01966	9-15 ft	\$452.00		
C352TSL - 2.5 lb. (UL Rating 5B:C)	13-02547	9-15 ft	\$452.00		
C354TS - 3.0 lb. (UL Rating 5B:C)	13-02548	9-15 ft	\$524.00		
B355T - 5.0 lb. (UL Rating 10B:C)	13-02545	9-15 ft	\$684.00		
B369 - 15.7 lb.(UL rating 1A:10B:C)	13-02557	12-18 ft.	\$1,174.00		
B371 - 19.9 lb. (UL rating 2A:40B:C)	13-02558	12-18 ft.	\$1,606.00		
674 - 460.0 lb. (UL rating 10A:80B:C)	13-02562	30-45 ft.	\$12,394.00		
B394TS - 9.3 lb. (UL rating: 5B:C)	13-02549	9-15 ft.	\$704.00		
337TS - 3.18 lb. (UL rating: 2B:C)	13-24405	7-8 ft.	\$1,378.00		
351- 19.88 lb.(UL rating: 2A:10B:C)	13-24406	15-17 ft.	\$8,176.00		
347 - 6.0 lb. (UL rating: 5B:C)	13-23573	~10 ft.	\$2,496.00		
349 - 6.0 lb. (UL rating: 5B:C)	13-23574	~10 ft.	\$2,496.00		

H3R QUICK RELEASE FIRE EXTIGUISHER BRACKET

Fire extinguisher quickly releases from bracket. Fiberglass reinforced nylon construction and corrosion resistant hardware. Designed to meet MIL SPEC 810G (test in progress). Tested to withstand inertial loads in excess of 27G in all directions. Fire extinguisher cannot be accidently disengaged from bracket. Fits H3R Performance fire extinguishers with 4.25" diameter cylinders (B355T). "Pull to Release" flag enhances Does not obscure fire extinguisher nameplate. Designed for use with H3R Performance vehicle seat mount. Weighs a scant 15 oz!

3" BracketP/I	N 13-18452 \$78.75
4-1/4" BracketP/I	N 13-18453 \$78.75
5" BracketP/I	N 13-18454 \$78.75

FIRE EXTINGUISHER BRACKETS

Designed for use with H3R Aviation fire extinguisher models 347 and 349. BKT325 has been tested to ensure that it can meet the most demanding aviation requirements.P/N 13-23575 ... 325 Red

H3R FIRE EXTINGUISHER MODEL 674

While it is less powerful pound for pound than Halon 1211. Halotron 1 offers all of Halon 1211's clean agent benefits, and Halotron 1 is less damaging to the ozone layer. H3R Aviation offers two Halotron 1 fire extinguishers: one FAA-approved unit for aircraft use and one wheeled unit for the flight line/

ramp. These rechargeable extinguishers have pressure gauges and require a 6-year maintenance and a 12-year hydrostatic test.



H3R BILLET MOUNTS

P/N 13-02562 \$12,394.00

H3R Performance hand held 1 lb. and 2.5 lb. fire extinguishers come standard with aviation style mounting brackets. Stylish and versatile billet mounting accessories are also available. Band

clamps fit 2.6" or 3.0" diameter fire extinguishers, and can be combined with the flat surface mount or either of the two roll bar mounts. Available in polished and brushed finishes. One year limited warranty. Brushed -Band clamp for 2.5 lb. fire extinguishersP/N 13-06067\$63.85



PRT FIRE EXTINGUISHERS MODELS RT-A400, RT-A600 AND RT-A1200

These extinguishers contain a unique blend of liquefied gas 1211/1301, two highly effective fire fighting agents. These units are self expelling which means that the pressure remains constant even when the extinguishers are almost empty.

1600, contain a unique blend of liquefied gas 1211/1301 which results in a more effective fire fighting agent. (Incendex is a registered trade mark of Protection R.T. Inc.). These 1211/1301 commercial extinguishers can continue to operate adequately even with loss of inert gas propellant, due to the unique blend used.

Protection RT Extinguishers				
Protection R.T. Extinguishers	Part No.	Range	Price	
RT A400 - 14 oz. (UL Rating 2B:C)	13-07650	4-6 ft	\$166.95	
RT A600 - 1.2 lb. (UL Rating 2B:C)	13-07655	6-8 ft	\$223.95	
RT A1200 - 2.5 lb. (UL Rating 5B:C)	13-07660	7-9 ft	\$395.00	
A1600 - 3.5 lb. (UL Rating 1A:5B:C)	13-07665	8-10 ft	\$536.00	

FIRE EXTINGUISHER BRACKETS



BKT400	
Brackett for the RT-A400P/N 13-06166	\$17.50
BKT600	
Brackett for the RT-A600P/N 13-06167	\$17.50
BKT1200	
Brackett for the RT-A1200P/N 13-06168	\$17.50
845	
Brackett for the A344TP/N 13-06170	\$15.75
Brackett for the A344TCP/N 13-06171	\$15.75

8175 - Brackett for the C352TS, C352TSC, C354TS P/N 13-06172**\$23.65**

ACTIVE EXTINGUISHING LINE



Active Extinguishing Line is totally independent, 1kg, fire extinguishing system from any power source. Its main secret lies in the heat detector in a form of a line made out of special laser predriller polymer, shich will react instantly to any source of heat or fire. This line (heat detector) is connected to reservoir containing

fire-extinguishing agent: hexafluoropropane FE-36. Inside of the protected device (equipment) a loop made out of the heat detector breaks, creating a mini sprinkler, directly over source of fire or heat, extinguishing it instantly. In a moment of activation the system closed circuit switch collapsses sending a signal informing of fire. For experimental aircraft only. Ask for status of pending STCs.

P/N 13-03266\$698.00



OCEAN SIGNAL SAFESEA GMDSS HANDHELD VHF RADIO

The Ocean Signal range of survival craft VHF hand portable radiotelephones exceed the requirements of IMO, SOLAS and GMDSS. Lithium Polymer rechargeable battery option available with rapid charger, for everyday normal use. Fully waterproof, even 40C thermal shock. High efficiency transmitter for maximum battery life. Rugged design exceeds GMDSS environmental requirements. Lithium primary battery for emer-

gency use. Novel battery protection tab protects from inadvertent use. Battery classified as non-hazardous for shipment. Battery provides in excess of 16 hours typical operation, even at -20°C. (10% Tx, 10% Rx, 80% Squelched). Laser etched key legends for durability. High contrast, backlit LCD and keypad. Rugged accessory socket option; waterproof to IP68 for use with headsets, helmets, fist mikes, etc. 4 scanning modes, DW, TW, scan and memory scan. 21 simplex channels according to IMO SOLAs requirements. Unit Only......P/N 13-20261\$623.00

RESCUE LASER FLARE MAGNUM



EMERGENCY STROBE

Waterproof • USCG approved • Operates up to 60 hours

· Uses D battery · Red lens available

