

STANLEY TAPE MEASURE

This 12 foot steel tape measure, with 1/2" blade, is graduated in tenths and hundredths of inches and also in fractions of inches (32nds). Very handy for all aircraft construction. A "must" for composite con-

No. 33-272P/N 33-272 ---



STANLEY UTILITY KNIFE

Aluminum, die-cast in two sections - provides blade storage. Has handy hang hole. Furnished with No. 11-921 blade and blade quard.

No. 10-099P/N 10-099-----



KNIFE BLADE

Heavy-duty pointed razor-type utility knife blade for No. 10-099 knife and most other makes of utility knives.

No. 11-921 (Pkg. of 5 Blades)
P/N 11-921-------



HOOK BLADE

For use with No. 10-099 knife and most other makes of utility knives to cut linoleum, roofing material, cartons, etc., without damage. The razor-sharp hooked ends cut to full thickness in one stroke.



SINGLE-EDGE RAZOR **BLADES**

Used for trimming rough edges of laminatesP/N 01-24904 ---/ea.



SPRING CLAMPS

Heavy-gauge steel clamps with vinyl grips and tips to prevent marring work. Jaws specially formed to hold flat or round objects. Two sizes available:

No. 3202-HT - Jaw Opening 2", Length 6" P/N 12-03778.....---



X-ACTO TOOLS X-ACTO BLADE NO. 11

Classic fine point blade. A general purpose blade. Package of 5

P/N 01-16500-



STRAIGHT EDGE

A 6-ft. long kiln-dried spruce board, 7/8" to 1" thick and 3" to 4" wide, used for checking the straightness of flying surfaces during composite construction....P/N 01-25900



6" STEEL RULER

Flexible stainless steel rule graduated in 10ths and 100ths on one side and in quick-reading 32nds and 64ths on the other side.



FELT TIP MARKERS

Used for marking locations on fiberglass throughout construction.

P/N 01-26000-



12-05600

12" LONG DRILL BITS

For use with standard electric drill	for hard-to-reach jobs.	
3/32" (.094" Dia.)	P/N 12-05200	
1/8" (.125" Dia)	P/N 12-05300	
3/16" (.188" Dia)	P/N 12-05400	
#10 (.1935" Dia.)	P/N 12-05500	
1/4" Dia	P/N 12-05600	

RUBBER SEALANT



No. 732 RTV general-purpose, clear, one-part silicone rubber. Cures to a firm silicone rubber in 24 hours at room temperature. 4.7 Oz. TubeP/N 09-27800----

JIFFY MIXER

This is a very effective 2-1/2" diameter stainless steel mixer on a 15" shaft. Attach to an air drill for fast, efficient mixing of larger batches. It will not dig into or gouge the sides or bottom of your mixing container.

P/N 01-00395.....----



CALRAD VARIABLE VOLTAGE CONTROL

A fine quality control to supply the electrical current for hot-wire cutting of styrofoam and PVC foam. One unit can serve to build many aircraft. Input 115 volts AC Output variable from 0 to 130 volts AC at 5 amps Caution - fuse should be inserted in the secondary to protect the control in the event of a short circuit.

Input: 117V AC 60Hz 3-Prong AC cord. Output: 0-130V AC Adj. 60Hz; volt meter, power jack. Fuse Protection