
- · Centerless ground & threaded
- Minimum tensile strength 125,000 PSI
- Cadmium plated per spec QQ-P-416A, Type II, Class 3
- 431 Stainless steel (CRES)








				ne, A" O				
EXAMPLE:								
AN6H-10A								
	1 /							
				=::				
Ц								

END DDILLED HEAD

HEAD ONLY DRILLED

FOR DRILLED HEAD AND SHANK ADD "H" ONLY EXAMPLE: **AN6H-10**



BOTH HEAD AND SHANK DRILLED

									(-) INDICATES CORROSION RESISTANT				
Bolts are sold			AN3					AN4					
"EACH" ALL BOLTS			Cadmium Plated AN3 (10-32)		Stainless AN3C (10-32)			Cadmium Plated AN4 (1/4-28)		Stainless AN4C (1/4-28)			
	Dash No.	Nominal Length	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A' Price	Grip Length	Drilled Price	Undrilled "A" Price	Drilled Price	Undrilled "A" Price	
ı	-3	15/32	1/16					1/16					
1	-4	17/32	1/8					1/16					
4	-5	21/32	1/4					3/16					
Ì	-6	25/32	3/8					5/16					
ı	-7	29/32	1/2					7/16					
Ì	-10	1-1/32	5/8					9/16					
Ì	-11	1-5/32	3/4					11/16					
İ	-12	1-9/32	7/8					13/16					
ı	-13	1-13/32	1					15/16					
Ì	-14	1-17/32	1-1/8					1-1/16					
Ì	-15	1-21/32	1-1/4					1-3/16					
ħ	-16	1-25/32	1-3/8			-		1-5/16			-		
,	-17	1-29/32	1-1/2					1-7/16					
Ì	-20	2-1/32	1-5/8					1-9/16					
Ì	-21	2-5/32	1-3/4			-		1-11/16			-		
Ì	-22	2-9/32	1-7/8			-		1-13/16			-		
Ì	-23	2-13/32	2			-		1-15/16			-		
Ì	-24	2-17/32	2-1/8			-		2-1/16			-		
Ì	-25	2-21/32	2-1/4			-		2-3/16			-		
Ì	-26	2-25/32	2-3/8			_		2-5/16					
ı	-27	2-29/32	2-1/2					2-7/16			-		
Ì	-30	3-1/32	2-5/8			-		2-9/16			-		
Ì	-31	3-5/32	2-3/4			-	-	2-11/16			-	_	
	-32	3-9/32	2-7/8			_	_	2-13/16				_	
1	-33	3-13/32	3				_	2-15/16				_	
•	-34	3-17/32	3-1/8			-	_	3-1/16			-	_	
Ì	-35	3-21/32	3-1/4			-		3-3/16			-	-	
Ì	-36	3-25/32	3-3/8			-	-	3-5/16			-	-	
ı	-37	3-29/32	3-1/2				_	3-7/16				_	
Ì	-40	4-1/32	3-5/8			-	_	3-9/16			-	-	
Ì	-41	4-5/32	3-3/4			-	-	3-11/16			-	_	
ı	-42	4-9/32	3-7/8			_	-	3-13/16				_	
ID	-43	4-13/32	4	-			-	3-15/16			-	-	
Ì	-44	4-17/32	4-1/8			-	-	4-1/16			-	_	
Ì	-45	4-21/32	4-1/4			-	-	4-3/16			-	-	
	-46	4-25/32	4-3/8			-	-	4-5/16			-	-	
ı	-47	4-29/32	4-1/2			-	-	4-7/16			-	-	
	-50	5-1/32	4-5/8			-	-	4-9/16			-	-	
∄∣	-51	5-5/32	4-3/4			_	-	4-11/16			-	_	
	-52	5-9/32	4-7/8	-		-	-	4-13/16			-	-	
Ì	-53	5-13/32	5	-	-	-	-	4-15/16	-		-	-	
Ì	-54	5-17/32	5-1/8			-	-	5-1/16	-		-	-	
ł	-55	5-17/32	5-1/4	-		-	-	5-3/16			-	-	
	-56	5-25/32	5-3/8			-	-	5-5/16			-	-	
ŀ	-57	5-29/32	5-1/2	-		-	-	5-7/16				-	
ł	-60	6-1/32						5-9/16					
Į	-00	0-1/32	5-5/8			-	-	J-3/10			-	-	