

CLEVIS BOLTS



AN173, AN174, & AN175 CLOSE TOLERANCE BOLTS

Note: All AN173-AN175 bolts are drilled shank.

Non-corrosion-resistant cadmium-plated steel machine bolts. Manufactured to Revision 20 (April, 1990) of the military specification.

Cat. #	Dia. (inches)	Threads/inch	Length (inches)	Grip (inches)	Price
AN173-5	.1900	32 NF-3A	.656	.250	---
AN173-6			.781	.375	---
AN173-7A			.906	.500	---
AN173-7			.906	.500	---
AN173-10			1.031	.625	---
AN173-11			1.156	.750	---
AN173-12			1.281	.875	---
AN173-13			1.406	1.000	---
AN173-14			1.531	1.125	---
AN173-15			1.656	1.250	---
AN173-16			1.781	1.375	---
AN174-3	.2500	28 UNF-3A	.469	.062	-----
AN174-4			.531	.062	-----
AN174-5			.656	.188	---
AN174-6			.781	.312	---
AN174-7			.906	.438	---
AN174-10			1.031	.562	---
AN174-11			1.156	.688	---
AN174-12			1.281	.812	---
AN174-13			1.406	.938	---
AN174-14			1.531	1.062	---
AN174-15			1.656	1.188	---
AN174-16	0.25	28 UNF-3A	1.781	1.312	-----
AN174-17	1.906	1.438	1.875	1.4375	---
AN174-20	2.031	1.562	2	1.5625	---
AN174-21	2.156	1.688	-----	-----	-----
AN174-23	2.406	1.938	-----	-----	---
AN174-24	2.531	2.062	-----	-----	-----
AN175-14	0.3125	24 UNF-3A	1.594	1.062	---
AN175-15	1.719	1.188	1.625	1.25	---
AN175-16	1.844	1.312	1.75	1.375	---
AN175-17	1.969	1.438	-----	-----	-----
AN175-20	2.094	1.562	2	1.5625	---
AN175-21	2.219	1.688	1.125	1.6875	---
AN175-22	2.344	1.812	2.25	1.8125	---
AN175-23	2.469	1.938	-----	-----	-----
AN175-24	2.594	2.062	-----	-----	-----
AN175-25	2.719	2.188	-----	-----	-----
AN175-26	2.844	2.312	-----	-----	-----
AN175-27	2.969	2.438	-----	-----	-----
AN175-30	3.094	2.562	-----	-----	-----
AN175-31	3.219	2.688	-----	-----	-----
AN175-32	3.344	2.812	3.25	2.8125	---
AN175-33	3.469	2.938	3.375	2.9375	---

Cat. #	Nominal Length	Grip Length	Price
AN176-10A	1-3/32	7/16	---
AN176-13A	1-15/32	13/16	---
AN176-14A	1-19/32	15/16	---
AN176-15	1-1/16	1-45/64	-----