

# STOP NUTS – ANCHOR NUTS

## AN363 & MS21042 ALL METAL STOP NUTS



AN363



MS21042

MS21045 • NAS1021A

The AN363 and MS21042 all-metal stop nuts are designed for use in high temperature installations (up to 450°F). The MS21042 nuts are shorter than the AN363 nut but develop the same tensile strength. Fabricated from carbon steel and cadmium plated per specification QQ-P-416C.

| AN363 CAD<br>Plated Dash # | Price<br>Each | AN363C<br>SS Dash # | Price<br>Each | Thread<br>Size | MS21042<br>Dash # | Price<br>Each |
|----------------------------|---------------|---------------------|---------------|----------------|-------------------|---------------|
| -632                       | ---           | -632                | ---           | 6-32           | -06               | ---           |
| -832                       | ---           | -832                | ---           | 8-32           | -08               | ---           |
| -1032                      | ---           | -1032               | ---           | 10-32          | -3                | ---           |
| -428                       | ---           | -428                | ---           | 1/4-28         | -4                | ---           |
| -524                       | ---           | -524                | ---           | 5/16-24        | -5                | ---           |
| -624                       | ---           | -624                | ---           | 3/8-24         | -6                | ---           |
| -720                       | ---           | ---                 | ---           | 7/16-20        | -7                | ---           |
| -820                       | ---           | ---                 | ---           | 1/2-20         | -8                | ---           |
| -918                       | ---           | ---                 | ---           | 9/16-18        | -9                | ---           |

## AN364, AN365 ELASTIC STOP NUTS



AN364



AN365

MS21083 • NAS1022N MS21044 • NAS1021N

These precision-made nuts are reliable and economical fastening devices. The nylon insert gives a friction grip on the threads of the bolt and holds securely. The AN364 (thin) stop nut is for use in structural applications where the bolt is loaded primarily in shear or in any application where the tensile strength of the regular height AN365 is not required. Cad stop nuts are furnished to military specifications. Insert color designates manufacturer only.

| Dash<br>No. | Thread<br>Size | Price Ea. | Dash<br>No. | Thread<br>Size | Price Ea. |
|-------------|----------------|-----------|-------------|----------------|-----------|
| AN364       | AN365          | AN364     | AN365       | AN364          | AN365     |
| -440A       | 4-40           | ---       | -524A       | 5/16-24        | ---       |
| -440        | 4-40           | ---       | -624A       | 3/8-24         | ---       |
| -632A       | 6-32           | ---       | -720A       | 7/16-20        | ---       |
| -832A       | 8-32           | ---       | -820A       | 1/2-20         | ---       |
| -1024A      | 10-24          | ---       | -918A       | 9/16-18        | ---       |
| -1032A      | 10-32          | ---       | -1018A      | 5/8-18         | ---       |
| -428A       | 1/4-28         | ---       | -1216A      | 3/4-16         | ---       |

### NSWC ELASTIC STOP NUT KIT

Contains: • AN364-428A (20 qty) • AN364-918A (4 qty) • AN364-624A (22 qty) • AN364-720A (4 qty) • AN364-820A (32 qty) ... P/N 04-01729

## AN364, AN365 STAINLESS STOP NUTS

| Thread  | Part No.    | Price | Thread  | Part No.    | Price |
|---------|-------------|-------|---------|-------------|-------|
| 1/4-28  | AN364C-428  | ---   | 1/4-28  | AN365C-428  | ---   |
| 3/8-24  | AN364C-624  | ---   | 5/16-24 | AN365C-524  | ---   |
| 632     | AN364C-632  | ---   | 3/8-24  | AN365C-624  | ---   |
| 7/16-20 | AN364C-720  | ---   | 6-32    | AN365C-632  | ---   |
| 1/2-20  | AN364C-820  | ---   | 7/16-20 | AN365C-720  | ---   |
| 8-32    | AN364C-832  | ---   | 1/2-20  | AN365C-820  | ---   |
| 9/16-18 | AN364C-918  | ---   | 8-32    | AN365C-832  | ---   |
| 5/8-18  | AN364C-1018 | ---   | 5/8-18  | AN365C-1018 | ---   |
| 10-32   | AN364C-1032 | ---   | 10-32   | AN365C-1032 | ---   |



## MS21044 / MS21083 STAINLESS STOP NUTS

| Part<br>Number | Bolt<br>Size | Price<br>Ea. | Part<br>Number | Bolt<br>Size | Price<br>Ea. |
|----------------|--------------|--------------|----------------|--------------|--------------|
| MS21044C04     | #4           | ---          | MS21083C7      | 7/16         | ---          |
| MS21044C10     | 5/8          | ---          | MS21083C8      | 1/2          | ---          |
| MS21083C9      | 9/16         | ---          | MS21083C10     | 5/8          | ---          |
| MS21083C4      | 1/4          | ---          |                |              |              |

## STAINLESS STOP NUTS

| Dash<br>No. | Thread<br>Size | Price Ea. | Dash<br>No. | Thread<br>Size | Price Ea. |
|-------------|----------------|-----------|-------------|----------------|-----------|
| Com364      | Com365         | Com364    | Com365      | Com364         | Com365    |
| -440        | 4-40           | ---       | -624        | 3/8-24         | ---       |
| -632        | 6-32           | ---       | -720        | 7/16-20        | ---       |
| -832        | 8-32           | ---       | -820        | 1/2-20         | ---       |
| -1024       | 10-24          | ---       | -918        | 9/16-18        | ---       |
| -1032       | 10-32          | ---       | -1018       | 5/8-18         | ---       |
| -428        | 1/4-28         | ---       | -1216       | 3/4-16         | ---       |
| -524        | 5/16-24        | ---       |             |                |           |

## ANCHOR NUTS

Anchor nuts are designed for blind mounted applications where it is impractical to use hex nuts or where it is desirable to have an attached nut for ease of maintenance. Use 3/32" dia. rivets with nut sizes 632, 832, 1032 and 428. Use 1/8" dia. rivets with 524 and 624.

## TWO LUG ANCHOR NUTS



AN366F  
NA1, MS21078,  
NAS1023N



K1000  
MS21047, NAS680S,  
NAS1023A



MK1000  
MS21069, NAS697N

## ELASTIC-INSERT ANCHOR NUT

| Part No.     | Thread<br>Size | Price<br>Each | Part No.    | Thread<br>Size | Price<br>Each |
|--------------|----------------|---------------|-------------|----------------|---------------|
| MS21078-06   | 6-32           | ---           | AN366F-428A | 1/4-28         | ---           |
| AN366F-832A  | 8-32           | -             | AN366F-524  | 5/16-24        | -             |
| AN366F-1032A | 10-32          | ---           |             |                |               |

## ALL METAL ANCHOR NUT

| Dash<br>No. | Thread<br>Size | K1000<br>(Full Size)<br>Price Ea. | MK1000<br>(Miniature)<br>Price Ea. | (Dimpled Rivet<br>Holes) MS21047<br>Price Ea. |
|-------------|----------------|-----------------------------------|------------------------------------|-----------------------------------------------|
| 04          | 4-40           | ---                               | ---                                | ---                                           |
| 06          | 6-32           | ---                               | ---                                | ---                                           |
| 08          | 8-32           | ---                               | ---                                | ---                                           |
| 3           | 10-32          | ---                               | ---                                | ---                                           |
| -4          | 1/4-28         | ---                               | ---                                | ---                                           |
| -5          | 5/16-24        | ---                               | ---                                | ---                                           |
| -6          | 3/8-24         | ---                               | ---                                | ---                                           |

## ONE LUG ANCHOR NUTS



NA17  
MS21080, NAS1025N



MK2000  
MS21071, NAS696A

| Elastic-Insert<br>Anchor Nut |            | Thread Size | All-Metal Anchor Nut |                        |
|------------------------------|------------|-------------|----------------------|------------------------|
| Part No.                     | Price Each |             | Dash No.             | Price Each             |
|                              |            |             |                      | MS21051<br>(Full Size) |
|                              |            |             |                      | MS21071<br>(Miniature) |
|                              |            | 6-32        | L06                  | ---                    |
|                              |            | 8-32        | L08                  | ---                    |
| MS21080-3                    | ---        | 10-32       | L3                   | ---                    |
|                              |            | 1/4-28      | L4                   | ---                    |



## ANCHOR NUT, DIMPLED, STANDARD SIZE

Anchor Nut, Dimpled Standard Size

K1100-06 ..... 6-32 Thread ..... P/N 04-01724 .....  
K1100-08 ..... 8-32 Thread ..... P/N 04-01725 .....  
Anchor Nut, One Leg, Dimpled, Standard size

MS21053-L08 ..... 8-32 Thread ..... P/N 04-01726 .....  
MS21053-L08 ..... 8-32 Thread ..... P/N 04-01726 .....  
MS21053-L08 ..... 8-32 Thread ..... P/N 04-01726 .....



NA5  
MS21081  
NAS1027N



K3000  
MS21055  
NAS684A  
NAS1027A

## CORNER NUTS

| All-Metal Anchor Nut | Price Ea. | Size   | Anchor Nut | Price Ea. |
|----------------------|-----------|--------|------------|-----------|
| MS21081-3            | ---       | 8-32   | MS21055L08 | ---       |
|                      |           | 10-32  | MS21055L3  | ---       |
|                      |           | 1/4-28 | MS21055L4  | ---       |



NA27 (AN256F)

## RIGHT ANGLE FLOATING NUTS

| Part No.     | Thread Size | Price Ea. |
|--------------|-------------|-----------|
| 22NA27-22-62 | 6-32        | ---       |
| 22NA27-22-82 | 8-32        | ---       |

## TWO LUG MINI ANCHOR NUTS

| Part Number | Thread Size | Price Each |
|-------------|-------------|------------|
| MS21075L06  | 6-32        | ---        |
| MS21075L08  | 8-32        | ---        |
| MS21075L3   | 10-32       | ---        |



F5000  
MS21059

## ALL-METAL FLOATING ANCHOR NUTS



F2000  
MS21061

| Two-Lug Nut | Price Ea. | Thread Size | One-Lug Nut | Price Ea. |
|-------------|-----------|-------------|-------------|-----------|
| ---         | ---       | 4-40        | MS21061-04  | ---       |
| MS21059L06  | ---       | 6-32        | MS21061L06  | ---       |
| MS21059L08  | ---       | 8-32        | MS21061L08  | ---       |
| MS21059L3   | ---       | 10-32       | MS21061L3   | ---       |
| MS21059L4   | ---       | 1/4-28      | MS21061-L4  | ---       |