

MACHINE SCREWS



MS27039 & MS27039C MACHINE SCREWS

Pan head low alloy steel machine screws have 125,000 to 145,000 psi tensile strength with cadmium plate finish to QQ-P-416, Type 2, Class 3. MS27039C screws are stainless steel Manufactured to MIL-S-6050 or MIL-8695. Equivalent to NAS 220.

Part Number	Thread	Length (In.)	Grip Length (in)	MS27039 Price	MS27039C Price
MS27039-0804	8-32	9/32	---	---	---
MS27039-0805	8-32	11/32	---	---	---
MS27039-0806	8-32	13/32	---	---	---
MS27039-0807	8-32	15/32	---	---	---
MS27039-0808	8-32	17/32	.094	---	---
MS27039-0809	8-32	19/32	.156	---	---
MS27039-0810	8-32	21/32	.219	---	---
MS27039-0811	8-32	23/32	.281	---	---
MS27039-0812	8-32	25/32	.344	---	---
MS27039-0813	8-32	27/32	.406	---	---
MS27039-0814	8-32	29/32	.469	---	---
MS27039-0815	8-32	31/32	.531	---	---
MS27039-0816	8-32	1-1/32	.594	---	---
MS27039-0817	8-32	1-3/32	.656	---	---
MS27039-0818	8-32	1-5/32	.719	---	---
MS27039-0819	8-32	1-7/32	.781	---	---
MS27039-0820	8-32	1-9/32	.844	---	---
MS27039-0821	8-32	1-11/32	.906	---	---
MS27039-0822	8-32	1-13/32	.969	---	---
MS27039-0823	8-32	1-15/32	1.031	---	---
MS27039-0824	8-32	1-17/32	1.094	---	---
MS27039-1-04	10-32	9/32	---	---	---
MS27039-1-05	10-32	11/32	---	---	---
MS27039-1-06	10-32	13/32	---	---	---
MS27039-1-07	10-32	15/32	---	---	---
MS27039-1-08	10-32	17/32	.062	---	---
MS27039-1-09	10-32	19/32	.125	---	---
MS27039-1-10	10-32	21/32	.188	---	---
MS27039-1-11	10-32	23/32	.250	---	---
MS27039-1-12	10-32	25/32	.312	---	---
MS27039-1-13	10-32	27/32	.375	---	---
MS27039-1-14	10-32	29/32	.438	---	---
MS27039-1-15	10-32	31/32	.500	---	---
MS27039-1-16	10-32	1-1/32	.563	---	---
MS27039-1-17	10-32	1-3/32	.625	---	---
MS27039-1-18	10-32	1-5/32	.688	---	---
MS27039-1-19	10-32	1-7/32	.750	---	---
MS27039-1-20	10-32	1-9/32	.813	---	---
MS27039-1-21	10-32	1-11/32	.875	---	---
MS27039-1-22	10-32	1-13/32	.938	---	---
MS27039-1-23	10-32	1-15/32	1.000	---	---

Part Number	Thread	Length (In.)	Grip Length (in)	MS27039 Price	MS27039C Price
MS27039-1-24	10-32	1-17/32	1.062	---	---
MS27039-1-25	10-32	1-19/32	1.125	---	---
MS27039-1-26	10-32	1-21/32	1.188	---	---
MS27039-1-27	10-32	1-23/32	1.250	---	---
MS27039-1-28	10-32	1-25/32	1.312	---	---
MS27039-1-29	10-32	1-27/32	1.375	---	---
MS27039-1-30	10-32	1-29/32	1.438	---	---
MS27039-1-31	10-32	1-31/32	1.500	---	---
MS27039-1-32	10-32	2-1/32	1.563	---	---
MS27039-4-06	1/4-28	13/32	---	---	---
MS27039-4-07	1/4-28	15/32	---	---	---
MS27039-4-08	1/4-28	17/32	---	---	---
MS27039-4-09	1/4-28	19/32	.062	---	---
MS27039-4-10	1/4-28	21/32	.125	---	---
MS27039-4-11	1/4-28	23/32	.188	---	---
MS27039-4-12	1/4-28	25/32	.250	---	---
MS27039-4-13	1/4-28	27/32	.312	---	---
MS27039-4-14	1/4-28	29/32	.375	---	---
MS27039-4-15	1/4-28	31/32	.438	---	---
MS27039-4-16	1/4-28	1-1/32	.500	---	---
MS27039-4-17	1/4-28	1-3/32	.563	---	---
MS27039-4-18	1/4-28	1-5/32	.625	---	---
MS27039-4-19	1/4-28	1-7/32	.688	---	---
MS27039-4-20	1/4-28	1-9/32	.750	---	---
MS27039-4-21	1/4-28	1-11/32	.813	---	---
MS27039-4-22	1/4-28	1-13/32	.875	---	---
MS27039-4-23	1/4-28	1-15/32	.938	---	---
MS27039-4-24	1/4-28	1-17/32	1.000	---	---

MS35190 MACHINE SCREWS (CROSS RECESSED)



82° flat head machine screws have 55,000psi minimum tensile strength and feature cadmium plate finish per QQ P-416, Type 2, Class 3. Manufactured from carbon steel to Federal Standard #66.

Part Number	Old AN505R	Dia. - Thread Size	Length (In.)	Price
MS35190-221	-4R4	4-40	1/4	---
MS35190-222	-4R5	4-40	5/16	---
MS35190-225	-4R8	4-40	1/2	---
MS35190-226	-4R10	4-40	5/8	---
MS35190-234	-6R4	6-32	1/4	---
MS35190-236	-6R6	6-32	3/8	---
MS35190-238	-6R8	6-32	1/2	---
MS35190-239	-6R10	6-32	5/8	---
MS35190-240	-6R12	6-32	3/4	---
MS35190-250	-8R5	8-32	5/16	---
MS35190-253	-8R8	8-32	1/2	---
MS35190-254	-8R10	8-32	5/8	---