CLAM



200 HOSE CLAMPS

Aero-Seal stainless steel clamps are for industrial & aircraft applications. This tangential wormscrew type clamp is for use on fuel, oil, air & coolant lines. The worm drive provides uniform clamping pressure without distorting hose. Tighten slotted head with screwdriver.

QS200	Dia. Range (In.)		Price	QS200	Dia. Range (In)		Price
Dash No.	Min.	Max.	Each	ch Dash No.	Min.	Max.	Each
-06H	7/16	25/32		-44H	2-5/16	3-1/4	
-08H	1/2	29/32		-48H	2-9/16	3-1/2	
-10H	9/16	1-1/16		-52H	2-13/16	3-3/4	
-12H	11/16	1-1/4		-56H	3-1/16	4	-
-16H	13/16	1-1/2		-60H	3-5/16	4-1/4	1
-20H	13/16	1-3/4		-64H	3-9/16	4-1/2	-
-24H	1-1/16	2		-72H	4-1/8	5	-
-28H	1-5/16	2-1/4		-80H	4-5/8	5-1/2	-
-32H	1-9/16	2-1/2		-88H	5-1/8	6	
-36H	1-13/16	2-3/4		-96H	5-5/8	6-1/2	
-40H	2-1/16	3					



200 WING HOSE CLAMPS

Perforated Stainless Steel worm-drive clamp. Heavy-duty four-piece Quadra-Lock construction enables far more tightening torque to be delivered to the band perforations. Use for aircraft and heavy-duty industrial applications. Conical Arched Perforated Slots: More steel between perforations for added strength and smoother worm-drive engagement. Made in the USA

QS200	Dia. Range (In.)		Price	QS200	Dia. Range (In)		Price
Dash No.	Min.	Max.	Each	Dash No.	Min.	Max.	Each
-06W	7/16	25/32		-24W	1-1/16	2	-
-08W	1/2	29/32		-28W	1-9/16	2-1/4	
-10W	9/16	1-1/16		-32W	1-9/16	2-1/2	
-12W	11/16	1-1/4		-36W	1-13/16	2-3/4	
-16W	13/16	1-1/2		-40W	2-1/16	3	



BREEZE AEROSPACE CLAMPS AN737TW SERIES

Breeze offers a several products to meet various Aerospace and Military specifications includ-ing the NAS1922, NAS 1924, MS35842, and AN737TW clamps that meet Federal Supply Class 4730. Made in the USA

Specifications: • 410 Stainless Steel Thumb Wing Screw • 9/16" Band in 300-Series SS • Meets Federal Supply Class 4730 Features: • Stainless Steel • Meets Federal Supply

Class 4730 • Diameter Range 7/16" - 10 5/16"

Part No.	Min	Max	Price
AN737TW30	11/16"	15/16"	
AN737TW44	61/64"	1 3/8"	



BREEZE AERO-SEAL STAINLESS CLAMP KITS

Perforated stainless steel worm-drive clamp. Heavy-duty four-piece Quadra-Lock construction enables far more tightening torque to be delivered

to the band perforations. Use for aircraft and heavy-duty industrial applications. Conical Arched Perforated Slots: More steel between perforations for added strength and smoother wormdrive engagement. Made in the USA

Aero-Seal Specs: • 9/16" (14.2mm) band • 5/16" (7.9mm) slotted hex screw • Per SAE standard J1508 Type "F

Pack A : Contains 2 each QS200 -52H, -64H, -72H and -80H

P/N 05-00942 Pack B : Contains 2 each QS200 -8H, -12H, -24H, -32H, -40H, & -64H. P/N 05-01340



BREEZE LINER CLAMPS

An integral extension of the band as an inner liner protects soft-surface hose (silicone and others) from damage caused by extrusion or shearing through the band slots. Liner clamps afford maximum protection to soft hoses while providing a true concentric seal.

Standard 1/2" (12.7mm) band 5/16" (7.9mm) slotted hex head screw Per SAE standard J1508 Type "F"

SAE Size	Description	Min	Max	Part Number	Price
6	Breeze Clamp 9406H	7/16"	25/32"	05-14930	
8	Breeze Clamp 9408H	1/2"	29/32"	05-04708	
10	Breeze Clamp 9410H	9/16"	1-1/16"	05-14931	
12	Breeze Clamp 9412H	11/16	1-1/4	05-04709	
16	Breeze Clamp 9416H	13/16	1-1/2	05-04711	
20	Breeze Clamp 9420H	13/16"	1-3/4"	05-14932	
24	Breeze Clamp 9424H	1-1/16"	2"	05-14933	
28	Breeze Clamp 9428H	1-5/16"	2-1/4"	05-14934	
32	Breeze Clamp 9432H	1-9/16"	2-1/2"	05-14935	
36	Breeze Clamp 9436H	1-13/16"	2-3/4"	05-14936	
40	Breeze Clamp 9440H	2-1/16"	3"	05-14937	
44	Breeze Clamp 9444H	2-5/16"	3-1/4"	05-14938	
48	Breeze Clamp 9448H	2-9/16"	3-1/2"	05-14939	
52	Breeze Clamp 9452H	2-13/16"	3-3/4"	05-14940	
52	Breeze Clamp 9452	2-13/16"	3-3/4"	05-15419	
56	Breeze Clamp 9456H	3-1/16"	4"	05-14941	
60	Breeze Clamp 9460H	3-5/16"	4-1/4"	05-14942	
64	Breeze Clamp 9464H	3-9/16"	4-1/2"	05-14943	
72	Breeze Clamp 9472H	1-7/8"	5"	05-14944	
80	Breeze Clamp 9480H	2-1/2"	5-1/2"	05-14945	



BREEZE AERO-SEAL® 300 SERIES CLAMPS

The original perforated stainless steel wormgear clamp. Heavy duty four-piece Quadra-Lock construction enables far more tightening torque to be delivered to the band perforations. Use for aircraft and heavy-duty industrial applications. • 9/16" (14.2 mm) band • 5/16" (7.9 mm) slotted hex screw • Per SAE standard J1508 Type "F"

SAE Size	Description	Min	Max	Part Number	Price
6	Breeze Clamp 300-06H	7/16"	25/32"	05-14905	
8	Breeze Clamp 300-08H	1/2"	29/32"	05-14906	
10	Breeze Clamp 300-10H	9/16"	1-1/16"	05-14907	
12	Breeze Clamp 300-12H	11/16"	1-1/4"	05-14908	
16	Breeze Clamp 300-16H	13/16"	1-1/2"	05-14909	
20	Breeze Clamp 300-20H	13/16"	1-3/4"	05-14910	
24	Breeze Clamp 300-24H	1-1/16"	2"	05-14911	
28	Breeze Clamp 300-28H	1-5/16"	2-1/4"	05-14912	
32	Breeze Clamp 300-32H	1-9/16"	2-1/2"	05-14913	
36	Breeze Clamp 300-36H	1-13/16"	2-3/4"	05-14914	
40	Breeze Clamp 300-40H	2-1/16"	3"	05-14915	
44	Breeze Clamp 300-44H	2-5/16"	3-1/4"	05-14916	
48	Breeze Clamp 300-48H	2-9/16"	3-1/2"	05-14917	
52	Breeze Clamp 300-52H	2-13/16"	3-3/4"	05-14918	
56	Breeze Clamp 300-56H	3-1/16"	4"	05-14919	
60	Breeze Clamp 300-60H	3-5/16"	4-1/4"	05-14920	
64	Breeze Clamp 300-64H	3-9/16"	4-1/2"	05-14921	
72	Breeze Clamp 300-72H	1-7/8"	5"	05-14922	
80	Breeze Clamp 300-80H	2-1/2"	5-1/2"	05-14923	
88	Breeze Clamp 300-88H	3-1/8"	6"	05-14924	
96	Breeze Clamp 300-96H	3-5/8"	6-1/2"	05-14925	
104	Breeze Clamp 300-104H	4-1/8"	7"	05-14926	
128	Breeze Clamp 300-128H	5-5/8"	8-1/2"	05-14927	
152	Breeze Clamp 300-152H	7-1/8"	10"	05-14928	
188	Breeze Clamp 300-188H	9-3/8"	12-1/4"	05-14929	

rices Subject to Change without Notice - Valid as of June 1, 2025. WWW.AIRCRAFTSPRUCE.COM