STRATOFLEX HOSE & FITTINGS



STRATOFLEX 111 HOSE

Price Per Ft.	Wt Per Ib./In.	Max Press	Hose ID.	Tube O.D.	Part No
	.0120	3000	.188	.250	111-4
	.0130	3000	.250	.312	111-5
	.0190	2000	.312	.375	111-6
	.0220	2000	.406	.500	111-8
	.0310	1750	.500	.625	111-10
	.0380	1500	.625	.750	111-12
	.0368	800	.875	1.00	111-16

STRATOFLEX 300 STRAIGHT FLARED **FITTINGS FOR 111 HOSE**



Part No.	Tube O.D.	Thread	Price Ea.
 300-3S	.188	3/8-24	
300-4S	.200	7/16-20	
300-5S	.312	1/2-20	
300-6S	.375	9/16-18	
300-8D	.500	3/4-16	
300-10D	.625	7/8-14	
300-12D	.750	1-1/16-12	
300-16D	1.00	1-5/16-12	

AP

5

STRATOFLEX 124 HOSE

and	Descriptio
(AAAAAAAAA)	124-3 Hos
	124-4 Hos
	124-6 Hos
	124-8 Hos

Part No. Price on 124-3 se se 124-4 124-6 se 124-8 24-8 Hose 124-10 Hose 124-10

STRATOFLEX 156 MEDIUM PRESSURE HOSE

Part No	Tube O.D.	Hose ID.	Max Press	Mini Blend	Price/Ft.
156-3	.188	.156	1500	1.75	
156-4	.250	.219	1500	2.00	
156-5	.312	.281	1500	2.25	
156-6	.375	.344	1500	2.50	
156-8	.500	.438	1250	3.50	
156-10	.625	.562	1250	4.00	
156-12	.750	.688	1250	4.50	
156-16	1.000	.875	1000	5.50	

STRATOFLEX 678 45° ELBOW **FLARED FITTINGS FOR 156 HOSE**

678-3S



678-4S .250 7/16-20 678-6D <u>.37</u>5 9/16-18 3/4-16 678-8D .500 ----678-10D .625 7/8-14 ----678-12D .750 1-1/16-12

Part No. Tube O.D. Thread Price Ea.

3/8-24

.188



STRATOFLEX 193 HOSE

Specifications: Hose meets or exceeds the requirements of MIL-H-5593. Construction: Tube - Seamless Buna - N. Reinforcement - One braid of high tensile fiber cord. Cover - Synthetic rubber. Identification: LP-MIL-H-5593-size, date of manufacture, manufac-

turer's code (CAGE) marked on one side of the hose. Stratoflex 193-size marked on other side of hose. Yellow markings are repeated every 12 inches. Application: Low pressure air and vacuum instrument systems. Vacuum service 20"Hg sizes -2 thru -6; 10"Hg sizes -8and -10. Temperature range: -65 to +165°F / (-54 to +74°C).

Part No	Tube O.D.	Hose ID.	Max Press	Weight per In. (I.b.)	Price Per Ft.
193-2	.35	.125	300	.0038	
193-3	.41	.188	250	.0050	
193-4	.48	.250	200	.0058	
193-6	.60	.375	150	.0079	
193-8	.75	.500	150	.0015	
193-10	.87	.625	150	.0138	

STRATOFLEX 646/640 45° ELBOW FLARED **FITTINGS FOR 111 HOSE**



Part No.	Tube O.D.	Thread	Price Ea.
646-4S	.250	7/16-20	
646-6S	.375	9/16-18	
646-8D	.500	3/4-16	
646-10D	.625	7/8-14	
640-12D	.750	1-1/16-12	
640-16D	1.00	1-5/16-12	

STRATOFLEX 649/643 90° ELBOW FLARED FITTINGS FOR 111 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
649-4S	.250	7/16-20	
649-6S	.375	9/16-18	
649-8D	.500	3/4-16	
649-10D	.625	7/8-14	
649-12D	.750	1-1/16-12	

STRATOFLEX 676 STRAIGHT FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
676-3S	.188	3/8-24	
676-4S	.250	7/16-20	
676-5S	.312	1/2-20	
676-6D	.375	9/16-18	
676-8D	.500	3/4-16	
676-10D	.625	7/8-14	
676-12D	.750	1-1/16-12	
676-16D	1.000	1-5/16-12	

STRATOFLEX 680 90° ELBOW FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
680-3S	.188	3/8-24	
680-4S	.250	7/16-20	
680-5S	.312	1/2-20	
680-6D	.375	9/16-18	
680-8D	.500	3/4-16	
680-10D	.625	7/8-14	
680-12D	.750	1 1/16-12	
680-16D	1.000	1 5/16-12	

STRATOFLEX 311 STRAIGHT FLARED FITTING FOR 193 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
311-2D	.125	5/16-24	
311-3D	.188	3/8-24	
311-4D	.250	7/16-20	
311-6D	.375	9/16-18	
311-8D	.500	3/4-16	
311-10D	.625	7/8-14	

STRATOFLEX 2650 FIRE SLEEVE



Part No.	Use	With	Hose	e No.	*10781-4	Price
Part NO.	124	193	111	156	Clamp	Per Ft.
2650-6	-4	-	-	-	-	-
2650-8	-6	-3	-	-4	22CR	
2650-9	-	-4	-	-5	22CR	
2650-10	-8	-	-4	-6	22CR	
2650-11	-	-6	-	-	-	-
2650-12	-10	-	-5,-6	-8	22CR	
2650-13	-	-8	-8	-	-	-
2650-14	-12	-	-	-	22CR	
2650-16	-	-10	-10	-10	32CR	
2650-18	-	-	-	-12	32CR	
2650-20	-16	-	-12	-	32CR	
2650-22	-	-	-16	-16	32CR	



STRATOFLEX FIRE SLEEVE	
END DIP	
staflay E007 Deem temperature ouring com	-

Stratoflex 5027 Room temperature curing cement for Stratoflex Firesleeve. To use, dip each end of firesleeve in accordance with P-104-29 and applicable drawing. Always use current specifications.

P/N 5027