

SILICONE BAFFLE SEALS

Excellent for replacement of baffle seals. exceeds asbestos type seals in durability and flexibility over its entire operating heat range of -80 F to +425 F..

Available in red, blue & black.

IRON OXIDE RED: Meets Mil Spec ZZR765B. ISR3 meets Mil Spec AMS3320 (P/N 05-00770, 05-00771-3, 05-00771) AMS3303 for all others. 3/32" thick x 3" wide x 9' long
LIPSTICK RED: Meets Mil Spec ZZR765B. ISR3 meets Mil Spec
AMS3303.
3/32" thick x 36" wide
3/32" thick x 3" wide
DARK BLUE: Meets Mil Spec ZZR765B. ISR3 meets Mil Spec AMS3303. 3/32" think x 3" wide x 9' long
BLUE: Meets Mil Spec ZZR765B. ISR3 meets Mil Spec AMS3303.
3/32" thick x 3" wide x 9' long
3/32" thick x 36" wide
3/32" thick x 3" wide
1/8" thick x 3"W x 9' w/ fiberglass insert P/N 05-00792
1/8" thick x 36"W w/ fiberglass insertP/N 05-00791
1/8" thick x 3" wide w/ fiberglass insertP/N 05-00791-3
BLACK: Meets Mil Spec ZZR765B. ISR3 meets Mil Spec AMS3303 (P/N 05-00810, 05-00811, 05-00811-3) AMS3320 for all others. 3/32" thick x 3" wide x 9' long
ASSORTED SILICONE 50 FEET: This is a 50 foot assortment of silicone lengths, thicknesses and colors

AIRCRAFT BAFFLE SEAL KITS

These pre-cut baffle seal kits are cut to original specifications. Please specify aircraft make, model, serial number, and color of seal. Kits are furnished with rivets, washers, drill bits, & silicone, P/N 00-00103

CALL FOR PRICE AND P/N OF KIT FOR YOUR AIRCRAFT or VISIT www.aircraftspruce.com FOR BAFFLE KIT INFORMATION.

COWL SEAL HARDWARE & TOOLS

GB4-4A: Baffle Seal Pop Rivet, Button Head. 1/8" Dia. x 3/16" Grip Requires a metal baffle strip or back-up washer to secure. Pkg. of 100
GB-A4: Back-up Washers Pkg of 150P/N 05-56130
GB-SF- 3/16: Baffle Seal Fastener (Post Type) for joining sides or overlapping of baffle material. Includes one male and one female piece. 1/8" NPT. Each
GBL4-4A: Baffle Seal Pop Rivet, Large Flange, Silver. 1/8" Dia. x .187"250" grip range Qty. 100
GBL4-4AB: Black Pop Rivet, large flange for black baffle seal 1/8" x 3/16" grip. GBL4-4AB. Qty 100
SILICONE REVOLVING PUNCH TOOL: Makes various size holes in baffle material.
Fach P/N 72



BLACK COWL SEAL

1/16" x 3" x 9' Cowl & Engine Baffle Seal First quality woven fiberglass cloth heavily impregnated with neoprene for unsurpassed durability. -40° to 300°. Black. TA-8071. MIL-R-6855. 1/16" x 3" x 9' Roll... P/N 06-02461.............---



COWLING CHAFE CLOTH

Off-white, 100% non-asbestos woven tape. Unaffected by most chemicals and temperatures.

1" x 15 ft. Roll.....P/N 09-31800----



A-56-12 COWL

CHAFE SEAL 3/4"
Phenolic-cure Nigen Cotton Webbing used on engine cowls to protect where overlapping the airframe. Not affected by cold, heat or most solvent chemicals. 1/16" thick.

P/N 05-11171----



AEROSTAR ENGINE COWL ANTI-CHAFING LINER

Marsh Brothers Aerostar Engine Cowl Anti-Chafing Liner kit (Chafe Protection) provides protection of the interior surface of the engine cowl where the engine airframe seals contact with the upper engine cowling assembly. By providing a tough abrasion resistant surface

made from Marsh Brothers proprietary material AeroLas-White, wear on the aluminum upper engine cowl is eliminated.

Unlike most other chafe protection material available our anti-chafing liners do not have an adhesive backing. Instead, they are bonded in place using 3M DP420 two-part epoxy (not included in the kit). This results in a significantly stronger bondP/N 05-27284



FIBERGLASS CLOTH **BAFFLE MATERIAL**

The same material used by several OEM aircraft manufacturers. Neoprene coated fiberglass cloth is heat & flame resistant, selfextinguishing, ozone & weather resistant, & will not support combustion. Temperature range -40F to +200F. AMS3783.

Black 3" x 9" RollP/N 05-12642----Black 36" x 36" SheetP/N 05-12643----



SILICONE CEMENT WITH **CATALYST**

This silicone cement is the same cement that is included with some of the chafe seals and is excellent for attachment of any silicone seal.

Note: GBSC-2 or GBSC-4 silicone cement to apply silicone seals requires silicone cement only for application.Storage & Shelf Life: · Best if refrigerated under 70° • 18 months shelf life when stored properly · Easier to fill

2.5 oz.P/N 05-13310----



BAFFLE FASTENER KIT Screw Fastener (Post Type) for joining

sides or overlapping of baffle material. Includes one male and one female piece. GB-SF-3/16 8-32 Threads.

P/N 05-01829-----

INDIVIDUAL FASTENERS

Male 8-32 Thread	P/N 05-01235	
Female 8-32 Thread	P/N 05-01236	