

GASKETS - O-RINGS - GROMMETS



MS35769 GASKETS

AN900 (MS35769) annular copper-asbestos gaskets are suitable for temperatures up to 500° F. and pressures up to 200 PSI. Ring width is 1/8"; thickness is 3/32.

AN900 Dash No.	MS35769 Dash No.	I.D. (In.)	Price Each	AN900 Dash No.	MS35769 Dash No.	I.D. (In.)	Price Each
-3	-1	3/16	*	-17	-24	1-1/16	---
-4	-2	1/4	---	-18	-26	1-1/8	---
-5	-5	5/16	---	-19	-29	1-3/16	---
-6	-6	3/8	---	-20	-31	1-1/4	---
-7	-8	7/16	---	-21	-33	1-5/16	---
-8	-9	1/2	---	-22	-35	1-3/8	---
-9	-10	9/16	---	-23	-38	1-7/16	---
-10	-11	5/8	---	-24	-39	1-1/2	---
-11	-13	11/16	---	-25	-41	1-9/16	---
-12	-15	3/4	---	-26	-42	1-5/8	---
-13	-17	13/16	---	-27	-46	1-11/16	---
-14	-18	7/8	---	-28	-48	1-3/4	---
-15	-20	15/16	---	-29	-51	1-13/16	---
-16	-21	1	---	-30	-52	1-7/8	---

AP



AN900 GASKET KIT

144 piece kit of copper crush washers in common sizes. Complete with durable plastic case with dividers and size chart..... P/N 05-02220

Plastic Case Only..... P/N 13-03017

AN900 Gasket Organizer..... P/N 13-19792

MS28778 TUBE FITTING BOSS GASKET (FORMERLY AN6290)

Straight-thread tube fitting boss gaskets are used to provide a seal between straight-thread fittings, such as AN815, and ports of instruments with female straight threads instead of the more common female tapered pipe threads.

Dash No.	Tube O.D.	Price Ea.	Dash No.	Tube O.D.	Price Ea.
-2	1/8	---	-10	5/8	---
-3	3/16	---	-12	3/4	---
-4	1/4	---	-14	---	---
-5	5/16	---	-16	1	---
-6	3/8	---	-20	1-1/4	---
-8	1/2	---			

AN931 ELASTIC GROMMETS (MS35489)



Flexible grommets, made of black synthetic rubber to specification MIL-G-3036. Resistant to hot oil & coolant. Used to protect tubing, wiring and control cables where they pass through bulkheads & firewalls.

Part No.	MS35489	ID	OD	Hole Size	Thickness	Price
AN931-2-9	-2	1/8	3/4	9/16	3/16	---
AN931-2-16	-3	1/8	1-1/4	1	1/4	---
AN931-3-5	-4	3/16	7/16	5/16	3/16	---
AN931-3-9	-134	3/16	3/4	9/16	3/16	---
AN931-4-7	-6	1/4	5/8	7/16	3/16	---
AN931-4-12	-7	1/4	1	3/4	1/4	---
AN931-4-16	-8	1/4	1-1/4	1	1/4	---
AN931-5-9	-9	5/16	13/16	9/16	5/16	---
AN931-5-12	-10	5/16	1	3/4	5/16	---
AN931-6-10	-11	3/8	7/8	5/8	5/16	---
AN931-6-16	-12	3/8	1-1/4	1	1/4	---
AN931-7-11	-13	7/16	15/16	11/16	5/16	---
AN931-8-13	-14	1/2	1-1/16	13/16	5/16	---
AN931-8-20	-15	1/2	1-1/2	1-1/4	1/4	---
AN931-9-13	-16	9/16	1-1/16	13/16	5/16	---
AN931-10-14	-17	5/8	1-1/8	7/8	5/16	---
AN931-10-20	-18	5/8	1-1/2	1-1/4	1/4	---
AN931-11-16	-19	11/16	1-5/16	1	3/8	---
AN931-12-17	-20	3/4	1-3/8	1-1/16	3/8	---
AN931-12-20	-135	3/4	1-5/8	1-1/4	1/4	---
AN931-12-23	-21	3/4	1-13/16	1-7/16	3/8	---
AN931-14-20	-22	7/8	1-5/8	1-1/4	7/16	---
AN931-16-22	-23	1	1-3/4	1-3/8	7/16	---

MS29513 FUEL RESISTANT O-RINGS

These MS29513 series O-rings are resistant to fuel and are ideal for applications such as fuel injection connections and primers. A small amount of fuel proof grease applied to these O-rings helps the installation and operation of primers. Not resistant to automotive fuels.

Part Number	Nominal Size			Price Each
	I.D.	O.D.	Width	
MS29513-005	3/32	7/32	1/16	---
MS29513-006	1/8	1/4	1/16	---
MS29513-007	5/32	9/32	1/16	---
MS29513-008	3/16	5/16	1/16	---
MS29513-009	7/32	11/32	1/16	---
MS29513-010	1/4	3/8	1/16	---
MS29513-011	5/16	7/16	1/16	---
MS29513-012	3/8	1/2	1/16	---
MS29513-013	7/16	9/16	1/16	---
MS29513-014	1/2	5/8	1/16	---
MS29513-015	9/16	11/16	1/16	---
MS29513-016	5/8	3/4	1/16	---
MS29513-017	11/16	13/16	1/16	---
MS29513-020	7/8	1	1/16	---
MS29513-028	1-3/8	1-1/2	1/16	---
MS29513-031	1-3/4	1-7/8	1/16	---
MS29513-033	2	2-1/8	1/16	---
MS29513-110	3/8	9/16	3/32	---
MS29513-111	7/16	5/8	3/32	---
MS29513-112	1/2	11/16	3/32	---
MS29513-113	9/16	3/4	3/32	---
MS29513-114	5/8	13/16	3/32	---
MS29513-115	11/16	7/8	3/32	---
MS29513-116	3/4	15/16	3/32	---
MS29513-130	1-5/8	1-13/16	3/32	---
MS29513-137	2-1/16	1/4	3/32	---
MS29513-138	2-1/8	2-5/16	3/32	---
MS29513-148	2-3/4	2-15/16	3/32	---
MS29513-155	4	4-3/16	3/32	---
MS29513-214	1	1-1/4	1/8	---
MS29513-220	1-3/8	1-5/8	1/8	---
MS29513-232	2-3/4	3	1/8	---
MS29513-233	2-7/8	3-1/8	1/8	---
MS29513-237	3-3/8	3-5/8	1/8	---
MS29513-264	7-1/2	7-3/4	1/8	---
MS29513-337	3-3/8	3-3/8	3/16	---
MS29513-338	3-1/8	3-1/2	3/16	---
MS29513-339	3-1/4	3-5/8	3/16	---
MS29513-241	3-7/8	4-1/8	1/8	---



M25988 O-RINGS

M25988 O-Rings, these O-Rings are intended for packing and are oil & fuel resistant.

Description	Part No	Price
M25988/1-022 Packing O-Ring	08-10778	---
M25988/1-212 Packing O-Ring	08-10779	---
M25988/1-928 Packing O-Ring	08-10782	---
M25988/1-010 Packing O-Ring	05-12763	---
M25988-1-022 Packing O-Ring	04-03839	---
M25988-1-114 Packing O-Ring	04-02534	---
M25988/1-212 Packing O-Ring	04-03831	---
M25988/1-904 Packing O-Ring	04-03884	---
M25988/1-905 Packing O-Ring	04-03885	---
M25988/1-916 Packing O-Ring	04-03832	---
M25988/1-928 Packing O-Ring	04-03841	---