– GROMMETS -



Used to secure fabric to metal ribs in wings and control surfaces. Replaces rib-stitch cord or P-K screws. Provides a more secure and streamlined installation. Drastically reduces covering time. FAA-approved for aircraft listed. Easily adapts to homebuilts with metal ribs. Spacing between clips, 3". Spacing may be reduced to 1-1/2" on high-performance aircraft by using 2 wires, with clips inserted in alternate holes that are spaced 1-1/2" apart. Fabricated from stainless steel wire. Supplied in 25-ft. continuous coils.

NOTE: FAA Approved for some aircraft.

Please see our website for complete approval list.

25-Ft. Coil......P/N 09-19400......

Aircraft Model	STC No.	Part No.	Feet Req'd.
Aeronca-Champion	SA150S0	09-19500	225
Piper — All Models	SA126S0	09-19600	175-250
Stinson	SA615S0	09-19700	175
Taylorcraft	Original Equipment	09-19800	225

INSTALLATION KITS

All install kits ---. No clips are included. Order separately. *If clips are used to secure fabric on controls, add 50 ft.

CESSNA-TYPE FABRIC CLIPS

Individual spring steel clips used to attach fabric to metal ribs. Eliminates rib stitching. P/N 09-19900

3M[™] FINE-LINE PAINT TAPE

This 3M[™] tape is particularly suitable for pin striping, multicolor and other custom painting applications. It is a thin, conformable green polypropylene film tape with a special finish that resists paint runoff. The adhesive adheres instantly and offers good holding power, resists lifting and curling. Stretchable and easy to handle. Provides an extremely fine color-line separation for decorative painting of aircraft. Scotch No. 218. 1/2" x 60 Yds......P/N 09-20400 3/4" x 60 Yds......P/N 09-20500



WOOD BRUSHES

Natural, undyed bristle with smooth, unpainted wood handles. Unaffected by paint, dopes, thinners or solvents.

Brush Width	Part Number	Price Each	Brush Width	Part Number	Price Each
1/2"	09-21100		2-1/2"	09-38825	
1"	09-21200		3"	09-38803	
2"	09-21300		4"	09-38804	

ACID OR GLUE BRUSHES

Horse hair with metal handle.

DOLLAR PATCHES

Grade B fabric patches for quick repairs on Grade B
& Dacron covering. Smooth edge, 2.5" dia. Also avail-
able in Dacron which are more durable & less notice-
able on aircraft exterior. Less 10% For 12 or More.
Dacron Dollar PatchesP/N 09-17705/ea.
Ceconite C101P/N 09-00162
Ceconite C102P/N 09-00163
PF P-103 MedP/N 09-18750
P99 Heavy DutyP/N 09-00164

RIB LACING & SEWING NEEDLES

<u> </u>	Description	Size	Part Number	Price
_	3" Curved	Needle 3C	09-18705	
	6" Curved	Needle 6C	09-18710	
	12" Curved Tip	Needle 12C	09-18720	
-	12" Straight	Needle 12	09-18725	
0	18" Curved Tip	Needle 18C	09-18730	

Needle Assortment includes 1 each of the following: 3" curved, 6" curved, 12" curved, 12" straight, 18" straight ...P/N 09-18735

RIB STITCH NEEDLES

Made from the highest quality steel. Heat treated, nickel plated.

Description	Gauge Size	Part Number	Price
2-1/4" Curved	18	09-18300	
4" Straight	15	09-18400	
10" Straight	13	09-18500	
14" Straight	13	09-18600	
18" Straight	12	09-18700	

"T" HEAD PINS

Used to hold fabric in place temporarily in covering operation. Plated steel, 1-1/2" L. 100 Pins. P/N 09-18850 ----

SCREWS Used on some aircraft models to attach fabric to metal wing ribs and empennage ribs instead of rib lacing. Truss-head, type "A" self-tapping sheet metal screws.

			4.	SIZE #4)
ea	T4X4	P/N	teel, Phillips Head	Stainless
ea	4RX1/2SS.	sP/N	teel Type A. Phillip	Stainless
ea	T4X6	sP/N	teel Type A, Phillip	Stainless

AD-41H CLOSED-END BLIND POP RIVET

1/8" diameter. Used to seal tubing vent holes.

P/N 04-01496 --

BLIND RIVETS

Use these 1/8" dia. "Pop" rivets to attach fabric to the ribs on Champion/Bellanca aircraft. 100 Rivets. P/N 09-18900

WASHERS

Aluminum washers may be use in place of original plastic washers under screws and pop rivets to attach

DRAIN GROMMETS

Manufactured from virgin cellulose acetate butyrate resin.

		(ſ			
Grommet Type	Part No.	O.D.	I.D.	Price each	Grommet Type	Part No.	O.D.	I.D.	Price each
Flat	AN231-1	1-1/4"	3/8"		Seaplane*	AN231-4	1-1/8"	-	
Flat	AN231-2	3/4"	5/16"		Aluminum	09-19110	3/4"	1/4"	

*Depressed center

INSPECTION RINGS

Clear plastic rings, 4-5/8" O.D. x 3-1/2" I.D. x .050" thick, molded from virgin cellulose acetate butyrate resin. To be cemented to fabric as inspection plate P/N 09-19200 --- ea. retainer.

INSPECTION RING PATCHES

Glued over inspection rings to prevent accidental removal. P/N 09-18750 --- ea.

INSPECTION PLATES



DOMED - Concave aluminum snap-type plate has single clip riveted across full diameter. Snaps to the ring at 2 contact points. Plate is 4.75" dia. P/N 09-19300 --- ea..... ---/100

RECESSED - Recessed center and flanged-edge design will not creep off center due to vibration in propwash areas. 4-3/4" dia. x .020 aluminum. Will not twist or vibrateP/N 09-18740P.

PIPER INSPECTION ACCESS HOLE KIT



Piper inspection access hole kit 765-106 comes with hardware, 2 plates, and 2 backup ring assemblies. P/N 09-05779

trices Subject to Change without Notice - Valid as of June 1, 2025. WWW.AIRCRAFTSPRUCE.COM