T MOUNTING & ADAPTER

INSTRUMENT MOUNTING KITS MK-01 MK-03 MK-02 REAR VIEW 3 1/8" STD. 0000 0000 000 ALIGNMENT GUIDE

Kits come with "special" self-locking black pan head screws and nylon washers Precision machined "Nut Ring" instrument mounting kit. Designed to

slide on from the back side of the instrument using the alignment guide pin inserted through a screw hole. Pulling on the alignment pin from the front side of the panel allows you to hold the instrument in correct alignment in the panel. Specially designed self-locking pan head black brass mounting screws and nylon washers are then easily installed from the front. Countersunk self-locking black brass screws are also available. Extra screws & washers are sold in packs of 12. The nylon washer keeps from chipping the instrument panel. All self-locking screws are extra long to accommodate the extra thickness of light wedges and internally lighted instruments. Nut Rings can be installed without removing hoses, tubing, or electrical connections. Designed to replace "grasshopper nuts". PMA'd.

Alignment guide pin sold separately. (P/N 10-03696)

•	• •		,	
MKNR-05	Model	Description	Part No.	Price
TTTT	MK-01	3-1/8" Std.	10-00335	
	MK-02	3-1/8" ALT/VSI	10-00336	
0000	MK-03	2-1/4" Std.	10-00337	
MKNR-06	MKNR-05	Pan Head Screws	10-00338	
人口	MKNR-06	Countersunk Screws	10-00339	
	Accessories			
100 Deg.	AP-01	Alignment Mounting Kit	10-03696	
Countersunk Head				

"EZ NUTS" INSTRUMENT MOUNTING SYSTEM BY SPT



IN

Take the frustration out of mounting instruments with the use of Superior Panel Technology's EZ Nuts. Adhesive tape securely holds nut ring in place. No realignment if instrument is later removed. Aluminum bezel is treated to pre-The pressed in vent corrosion. stainless steel inserts eliminate the

problem of striped threads. Simply cut off one corner if only three screws are needed. Save labor time when compared to "grasshopper nuts". Includes four 1-1/2" non-magnetic black oxide stainless steel, pan-head screws. Stronger than brass. Includes four black nylon washers to prevent marring of the panel.

present manual estimates	
*100 degree countersunk screws available and are sold in packs	of eight.

2-1/4" Bezel	P/N 11-01831
Black-Oxide Stainless St	eel Countersunk screw package

(set of 8)P/N 11-06546P/N 11-06546P/N 11-06546 eight black nylon washers that will enhance the appearance of the panel and will prevent the marring and scratching of the panel during instrument installation and removal.

(set of 8)P/N 11-09911



PITOT TUBE PROTECTORS

These hinged pitot tube protectors open automatically in take off at speed of about 40 mph and close automatically at end of landing roll.

Model No.	Part No.	Fits Pitot Tube Sizes	Price
1	10-02000	1/4" O.D.	
2	10-02100	1/2" O.D.	
3	10-04968	3/16" O.D.	

REMOVE BEFORE FLIGHT RIBBON

REMOVE BEFORE FLIGHT 0

This 3" x 24" orange vinyl streamer with black letters, features a grommet for a clip ring to attach anywhere on the aircraft. High visibility, fire resistant material......P/N 15200P/N 15200

INSTRUMENT ADAPTER KITS



CNC Machined from aircraft grade aluminum. The adapter face is raised .075" to give the flush panel look. Easy to install and easily painted. See www.aircraftspruce.com for specifications.

See www.anclanspluce.com for specifications.			
Model	Description	Part No.	Price
MK-620	3-1/8" Blank	10-00340	
MK-621	3-1/8" ALT/VSI Blank	10-00341	
MK-622	3-1/8" ALT/VSI Plug	10-00342	
MK-623	3-1/8" to 2-1/4"	10-00343	
MK-624	2-1/4" Blank	10-00344	
MK-630	KI525 Blank	10-00345	
MK-631	KI525 to 2-1/4"	10-00346	
MK-632	KI525 to 3-1/8"	10-00347	
MK-633	KI525 to 3 ATI	10-00348	
MK-640	3 ATI Blank	10-00349	
MK-641	3 ATI to 2-1/4"	10-00350	
MK-642	3 ATI to 3-1/8"	10-00351	

PITOT TUBE COVERS PITOT TUBE BOOTY - Durable leather-like cover provides optimum protection. Velcro strap attaches booty to 5/8" or 11/16" dia. L-shaped pitot tube. Bright red "Remove Before Flight" streamer. Made of flame-proof & weather-resistant National Aerospace material P/N 15210 SLIP-ON PITOT TUBE COVER - Not shown. Same as above except is slip fit over 1/4" or 1/2" dia. pitot tube. Red "Remove Before Flight" streamer is attached to cover. Made of flame-proof and weather-resistant National Aerospace

DEGROFF'S PITOT SHIELDS



BEFORE FLIGH

PITOT SHIELDS are a "fail-safe" pitot tube cover that will protect the pitot tube from contamination by insects, debris and ice while the airplane is on the ground. It is friction-fit to the pitot tube and has a calibrated "flat-plate-forward" design that, upon reaching a specific velocity, will release from the pitot tube and fall harmlessly away, allowing for normal airspeed indications. The cover utilizes EVA foam that is UV

resistant and stable at temperatures reached by heated pitot tubes. It is a highly visible color with the words "REMOVE BEFORE FLIGHT" printed and visible from all directions. This pitot tube cover is soft, but tough. It will not damage aircraft surfaces when it comes off during ground roll, nor will it be a potentially hazardous foreign-object on the runway.

For 5/8" pitot tube	P/N 10-00491
For 3/4" pitot tube	P/N 10-00492

ALUMINUM PITOT MAST

Custom manufactured aluminum pitot mast designed for the popular Van's Aircraft RV kit aircraft. Aluminum streamline tubing is correct size for all popular pitot tubes. Aluminum mounting plate is .070" thick aluminum, precision welded to the tubing. Mounting plate measures 3" wide X 4" long. Streamlined mast is 5" long. The mounting plate has a jog on the forward side to overlap the spar flange inside the wing. This mast can be used on other popular aircraft that require a mast for the pitot tube. Blue anodized finish. Mounting instructions and template included. Made

540