# ER AV

#### **BATTERIES AND BATTERY CHARGERS** FOR HANDHELDS

Battery Model	Description	Part No.	Price
For Icom A24/A6			
BP-210N	7.2V 2000mAh Ultra long life	11-08251	
BP-211N	Lightweight, Ultra ling life. Li-On	11-08254	
EMS-211	charger required. Rapid Desktop Cgr for BP-211/N	11-08256	
	Handheld aviation radios-	11 00200	
BP-197H	Alkaline Battery pack	11-01082	
BP-200XL	9.6v 1450 mAh long Life Ni-MH	11-06351	
BP-200L	9.6V 850mAh	11-08274	
CP-12L	12VDC Cig Lighter for A5	11-08249	
Por ICOM A-4 Har BP-196	ndheld aviation radios-	11-00227	
EMS-196	9.6v 1500 mAh pk Desktop Fast Charger		
	BP-195/196	11-08248	
For ICOM A-22 &/		11.00000	r
CM-166 EMS-166	NiMH Battery 12.0v 1200 mAh Desktop Charger for CM-166	11-00228	
EC-166	Wall charger for CM-166	11-08234	
BC-79A	Desktop Charger	11-18557	
WC-166	Battery Charger	11-08234	
	/ IC-A14S Handheld aviation radi		
BP-232N	Operating Time: 15.5 hours	11-08231	
For ICOM A-20, A		11.00000	
CM-7x	13.2v 1000 mAh pk Wall charger for CM-7 / CM-7X	11-00230	
IC-WC IC-8	8 cell AA case 3-1/4" tall	11-08237 11-08246	
IC-0	Car Power/Charge cord	11-00351	
For ICOM R-1 rad			
BP-83	7.2v 600 mAh pk	11-00233	
BP-83xh	7.2v 1500 mAh pk	11-00234	
BC-79A	Desktop Quick Charger	11-18557	
Icom Chargers	Do Dawar/Charge Coulter 10014		r
CP-11L	DC Power/Charge Cord for ICOM IC-T90A, IC-91AD, IC-A24, IC-A5	11-06348	
EMS-201	7.2V thru 13.2V Ni-cd & Ni-MH	11-08245	
EMS-210N	Smart charger for ICOM	11-06350	
EMS-232	Rapid Desktop Charger for Icom-	11-08233	
	style Lithium ION Bttys		
EMS-30i	Desktop smart-quick charger.	11-06352	
For Yaesu Avlato FNB-41xh	r Pilot & Aviator Pro nav/com rad 9.6v 1000 mAh pk	11-00237	
FNB-47xh	7.2v 1800 mAh pk	11-00238	
FNB-41xs	9.6v 1450 mAh pk	11-06354	
EMS-41/47	Rapid Cgr for FNB-40/41/47	11-08244	
FNB-80LI	7.2V 1600mAh Yaesu & Vertex	11-08268	
CBE-41	Battery Eliminator	11-06355	
CBE-80	Battery Eliminator Cig Lighter	11-08269	
E-DC-5BA EM-57-83	DC Power Cord, Cig Lighter Super Desktop Charger	<u>11-08241</u> 11-08239	
For Bendix/King		11-00239	
BP-KX99	10.0v 1500 mAh pk	11-00240	
KX-99XH	10.0V 2700 mAh	11-08257	
IC-CP	Car Power/Charge cord	11-00351	
KX-99	Battery case, 8-cell AA (BP-99A)	11-08258	
For STS handheld		11 00041	
BP-STS+ WC-STS	7.2v 1400 mAh pk Wall Charger	11-00241 11-00352	
	en 100/200/250XLT-	1 11 00002	
	en 2500XLT, 3000XLT, & 3500XLT	-	
BP-2500x	6.0v 1000 mAh pk	11-00322	
	en Trunk Tracker & Sportcat-		
BC-120	4.8v 1000 mAh pk	11-00323	
BC-120x BP-120XE	4.8v 1500 mAh pk 4.8V 2000 mAh Long Life	11-00324	
BP-120XE BP-120XX	4.8V 2500 mAh	11-08272 11-08273	
BP-120 80	4.8v 800 mAh pk	11-08270	
BP-120 110	4.8v 1100 mAh pk	11-08271	
For Santec/Narco	radios-		
BP-800	9.6v 600 mAh pk	11-00242	
BP-800sh	9.6v 1000 mAh pk	11-00325	
	C528A/C628A, etc.	11.0000	
CNB-152XS	12V 1800mAHr NiMH	11-08261	
<u>CNB-152XH</u> CSA-181	12V 1200mAh Long Life Quick Desktop Charger	<u>11-08259</u> 11-08266	
	Headset Series 1	11200200	
BP-A	14.4v 1250 mAh	11-00243	
Battery Eliminato			·
CBE-152	DC Battery Eliminator for stan-	11-08262	
	dard-ADI-JRC radios		· ·
CBE-196	Battery Eliminator for ICOM	11-08247	
CBE-83	12VDC. 5W, Voltage & Current limiting, & noise filter!	11-08238	
	I miniting, a noise linter!	l	

#### **BECKER AR 6201 TRANSCEIVER**



AR6201 series of square sized VHF transceivers from Becker are a family of affordable airborne radios optimized by their functionalities, state of the art technology, compact dimensions, and low weight for many different aircraft categories in general aviation, from smaller to larger aircraft.

The radios fit in any 2 1/4 inch cut out for easy installation and the different models are equipped with sunlight readable LC displays and high per-

formance transmitters with 6 or 10 watts power output, continous power supply from 10.25 to 33 V DC, 8.33 kHz / 25 kHz channel spacing, sensitive receiver, VOX intercom and many other features. • 8.33 or 25 kHz · Supply voltage 9-33 V DC · 6 W or 10 W transmit power · VOX / INTERCOM · Scan (SCN) mode active/preset frequency · Tandem Operation. Model No. AR6201-(022) · Channel Spacing: VHF transceiver 6W, 8.33/25kHz spacing, blue white backlight LC - display Article - No. 0636.399 - 910 AR6201 COM Harness 3.7m ......P/N 11-18178 .....

#### BECKER GK 615 PORTABLE VHF STATION



The carrying case contains the battery, speaker, antenna socket, the 5 way DIN socket for the micro- phone or microphone speaker and the voltage converter. A microphone, a headset or a helmet (ultra- light) can be connected to the 5-way DIN socket. The built-in battery is a maintenance-free recharge- able 12 V / 2 Ah dry lead

acid battery. The transmitter power is approximately 5 to 7 W. Charging voltage can be varied between 10 V and 32 V. Charging time approx. 8 hours. The nominal operating time for the portable VHF station is approximately 6 hours at a keying ratio of 1:10 normal ra- dio traffic) and transmitter output power of 5 W. Features: • Frequency Range: 118.000 MHz to 136.990 MHz · Channel Spacing: 8.33 or 25 kHz · Channel Selection: 8.33 or 25 kHz (selectable) • RF-Output Power: > 6 W (carrier power) · Receiver Sensitivity: > 12 dB sinad for 2 uV.

Model No.	Watts	Description	Part No.	Price
0940.472 923	5	GK 615-5 Portable VHF Station	11-12319	
0940.432 923	10	GK 615-10 Portable VHF Station	11-12320	



## **BECKER AR6203 VHF /** AM TRANSCEIVER The AR6203 VHF-AM transceiver is smaller

and lighter than its forerunner due to implementation of state-of-art DSP (Digital Signal Processing) technology it is designed in a 160mm format and is equipped with a highly efficient AM transmitter, a very sensitive receiver and a full graphic LC-display that allows easy reading under all light conditions, including full sun light readibility. Push button and display illumination can be dimmed.

Description	Part No.	Price
AR6201-022: 8.33/25kHz Switchable, 6W	11-14411	
AR6203-012: 8.33/25kHz Switchable, 10W	11-14415	

### BECKER GT6203 VHF / AM GROUND TRANSCEIVER



Designed for operations at airfields and airports in a very demanding environment, the GT6203 offers latest technology and comfortable operation on all frequency

channels in the aeronautical frequency range, adjustable in 25 kHz steps as well as in 8,33 kHz steps. The user friendly operator menu and the extensive setup possibilities allow a very personal setup for the user. The large, clear and dazzle-free LC display shows the active frequency and either the standby frequency or memory channel. With an output power of 6W or 10W, the transmitter is strong enough

for medium range communications, ensuring a low cost of ownership for the customer.

Derived from its airborne counterpart AR6203, the GT6203 is the robust, reliable and flexible solution for your ground operations.

6 Watt	 P	P/N 1	1-19086	
0 Watt	 P	P/N 1	1-19087	