

CHERRY PULLING HEADS

CHERRY PULLING HEAD H1900-456

The H1900-456 is designed to reliably install all sizes of the single action NAS1919/1921 product assembled with or without a drive washer. To install the product without a drive washer use the appropriate nose piece. Total weight without riveter: .27 lbs (0.1222 kg). Use with G83 or G84 Cherry Riveter or any riveter equipped with a 352 Style Mounting System.....P/N 12-03019 ----

COMPACT UNIVERSAL STRAIGHT PULLING HEAD H800

Compact Universal Straight Pulling Head for G800 riveter. Weight - 0.15 lbs.....P/N 12-03092 ----

SHORT PINTAIL BASIC PULLING HEAD H513



Cherry Short Pintail Basic Pulling Head H513 - See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price
H513-04-20	1/8"	2" (51 mm)	12-03020	---
H513-04-35	1/8"	3-1/2" (89 mm)	12-03021	---
H513-05-35	5/32"	3-1/2" (89 mm)	12-03022	---
H513-06-20	3/16"	2" (51 mm)	12-03023	---
H513-06-60	3/16"	6" (152 mm)	12-03024	---
H513-08-35	1/4"	3-1/2" (89 mm)	12-03025	---

SWIVEL NOSE PULLING HEAD H513S



Cherry Swivel Nose Pulling Head H513S - See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price
H513S-05-20	2" (51 mm)	5/32"	12-03026	---
H513S-05-35	3-1/2" (89 mm)	5/32"	12-03027	---
H513S-06-20	2" (51 mm)	3/16"	12-03028	---
H513S-06-24	2-3/8" (60 mm)	3/16"	12-03029	---
H513S-06-35	3-1/2" (89 mm)	3/16"	12-03030	---
H513S-06-48	4-13/16" (122 mm)	3/16"	12-03031	---
H513S-08-24	2-3/8" (60 mm)	1/4"	12-03032	---
H513S-08-35	3-1/2" (89 mm)	1/4"	12-03033	---
H513S-08-48	4-13/16" (122 mm)	1/4"	12-03034	---
H513S-10-27	2-11/16" (68 mm)	5/16"	12-03035	---
H513S-10-42	4-3/16" (106 mm)	5/16"	12-03036	---
H513S-12-27	2-11/16" (68 mm)	3/8"	12-03037	---
H513S-12-42	4-3/16" (106 mm)	3/8"	12-03038	---

SELF RELEASING SWIVEL NOSE PULLING HEAD H513SR



Cherry Self Releasing Swivel Nose Pulling Head H513SR - See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price
H513SR-05-20	2" (51 mm)	5/32"	12-03039	---
H513SR-05-35	3-1/2" (89 mm)	5/32"	12-03040	---
H513SR-06-20	2" (51 mm)	3/16"	12-03044	---
H513SR-06-24	2-3/8" (60 mm)	3/16"	12-03045	---
H513SR-06-35	3-1/2" (89 mm)	3/16"	12-03046	---
H513SR-06-48	4-13/16" (122 mm)	3/16"	12-03047	---
H513SR-08-24	2-3/8" (60 mm)	1/4"	12-03048	---
H513SR-08-48	4-13/16" (122 mm)	1/4"	12-03049	---
H513SR-10-27	2-11/16" (68 mm)	5/16"	12-03050	---
H513SR-10-42	4-3/16" (106 mm)	5/16"	12-03051	---
H513SR-12-27	2-11/16" (68 mm)	3/8"	12-03052	---
H513SR-12-42	4-3/16" (106 mm)	3/8"	12-03053	---

SELF RELEASING SWIVEL NOSE/ CHISEL SHAPE PULLING HEAD H513SRC



Cherry Self Releasing Swivel Nose/Chisel Shape Pulling Head H513SRC - See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	LockBolt Dia.	Installed Length	Part No.	Price
H513SRC-05-20	2" (51 mm)	5/32"	12-03054	---
H513SRC-05-35	3-1/2" (89 mm)	5/32"	12-03055	---
H513SRC-06-20	2" (51 mm)	3/16"	12-03056	---
H513SRC-06-35	3-1/2" (89 mm)	3/16"	12-03057	---
H513SRC-08-48	4-13/16" (122 mm)	1/4"	12-03058	---

CHERRYLOCK "A"

CODE PULLING HEAD H84-8CLA

Cherrylock "A" Code Pulling Head for use with G84 riveters. Tool weight (without riveter): .3 lbs (0.14 kg).P/N 12-03104 ----



OFFSET LOCKBOLT/ SHORT PINTAIL PULLING HEAD H563SP

See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	Type	LockBolt Dia.	Part No.	Price
H563SP-4B	Basic Pulling/Short Pintail	1/8"	12-03064	---
H563SP-5B	Basic Pulling/Short Pintail	5/32"	12-03065	---
H563SP-6B	Basic Pulling/Short Pintail	3/16"	12-03066	---

CHERRYLOCK® STRAIGHT PULLING HEAD H681



Fits directly on all Cherry hydroshift riveters, 2-9/16" installed. Separate pulling head is required for each style & diameter rivet.

Description	Rivet Dia.	A/B Dims.	Part No.	Price
H681-3C Universal C-Sunk Head	3/32"	.163" / .332"	12-03070	---
H681-4C Universal C-Sunk Head	1/8"	.208" / .341"	12-03071	---
H681-4F Countersunk Head 156	1/8"	.430" / .358"	12-03072	---
H681-4S Countersunk Head NAS 1097	1/8"	.174" / .341"	12-03073	---
H681-5C Universal C-Sunk Head	5/32"	.269" / .352"	12-03074	---
H681-6C Universal C-Sunk Head	3/16"	.335" / .386"	12-03075	---
H681-6F Countersunk Head 156	3/16"	.625" / .367"	12-03076	---
H681-6S Countersunk Head NAS 1097	3/16"	.281" / .386"	12-03077	---
H681-8C Universal C-Sunk Head	1/4"	.458" / .398"	12-03078	---

CHERRYLOCK® STRAIGHT PULLING HEAD H681B



Fits directly on all Cherry hydroshift riveters, 2-9/16" installed. Separate pulling head is required for each style & diameter rivet.

Description	Rivet Dia.	A/B Dims.	Part No.	Price
H681B166-4 Uni-Sink Head	1/8"	.250" / .359"	12-03079	---
H681B166-5 Uni-Sink Head	5/32"	.313" / .377"	12-03080	---
H681B166-6 Uni-Sink Head	3/16"	.375" / .419"	12-03081	---

CHERRYMAX® STRAIGHT PULLING HEAD H701B-456



CherryMAX Straight Pulling Head H701B-456 - Installs 1/8", 5/32" & 3/16" Nominal & Oversize CherryMAX Rivets.

P/N 12-03083 ----

NUT PLATE PULLING HEAD WITH NOSEPIECES H702-3NPR



Cherry® Nut Plate Pulling Head. Includes nosepieces: 728A9-3 (3/32") & 728A9-104 (1/8"). For G702A Riveter. Installs 3/32" & 1/8", 2.5 mm & 3 mm Nut Plate.

P/N 12-03084 ----

CHERRYMAX STRAIGHT PULLING HEAD H744A-8



CherryMAX Straight Pulling Head installs 1/4" Nominal & Oversize CherryMAX Rivets (G744 Only)P/N 12-03087 ----

CHERRYMAX RIGHT ANGLE PULLING HEAD H753A-456



CherryMAX Right Angle Pulling Head H753A-456 installs 1/8", 5/32" & 3/16" Nominal & Oversize CherryMAX Rivets P/N 12-03089 ----

CHERRYMAX OFFSET PULLING HEAD H781-456



CherryMAX Offset Pulling Head installs 1/8", 5/32" & 3/16" Nominal & Oversize CherryMAX RivetsP/N 12-03090 ----

OFFSET LOCKBOLT PULLING HEAD H563



See Tool Specifications below to determine which pulling head is needed.

Cherry P/N	Type	LockBolt Dia.	Part No.	Price
H563-4B	Basic Pulling	1/8"	12-03061	---
H563-5B	Basic Pulling	5/32"	12-03062	---
H563-6B	Basic Pulling	3/16"	12-03063	---

STRAIGHT PULLING HEAD -8 CHERRYMAX® H84A-8

Straight pulling head H84A-8 for use with G84 Power Riveter and G84-LS Split Power Riveter (with adaptor 744-700). Pulling Head Weight: 0.2 lbs (0.09 kg).P/N 12-03106 ----

TO