STEELMAX METAL CUTTING SAW 9 INCH



More efficient than any portable metal cutting process you are using now! . Increase Productivity - No Milling or de-burring with near surgical dry-cut technology. • Cuts a Variety of Metals, Plastic and Wood - Bring your saw to

Accessories	Teeth	Arbor	Part No.	Price
9" Stainless Steel Blade	80T	1.0"	12-01805	
9" Alluminum Blade	80T	1.0"	12-01807	

STEELMAX DRYCUT SAW S14 Utilizing a 14" carbide tipped blade, the Steelmax S14 cuts



through metal faster, safer and cleaner than abrasive chop saws in a fraction of the time and cost. Powered with a 15 amp motor and geared to turn slower than a chop saw, the S14 dry cutter cuts like a cold saw, but at a fraction of the cost. Sold standard with a 14" carbide tipped mild

steel blade attached, heavy duty, industrial strength cast iron base and two position locking vise, this saw is ready for immediate action! Cuts

Accessories	Teeth	Arbor	Part No.	Price
14" Stainless Steel (Less Than 1/4")	90T	1.0"	12-01809	
14" Thin Mild Steel (Less Than 1/4")	90T	1.0"	12-01810	



MAGNETIC BASE DRILL

SteelMax® brand drills maintain rigidity and accuracy throughout the life of the drill. The rail system eliminates the need to adjust or maintain traditional gibs. In addition to saving on maintenance, cutter life is increased by reducing movement at the cutter tips. When cutters last Ionger, you save money every day you use SteelMax! Magnetic Base Drill.......P/N 12-01718Portable Magnetic DrillP/N 12-01811

CUTTERS FOR MAGNETIC BASE BRILL

Dia.	D.O.C.	Part No.	Price		Dia.	D.C).C.	Part N	о.	Price
7/16"	1"	12-01813			1/2"	2	"	12-018	34	
1/2"	1"	12-01814			9/16"	2	"	12-018	35	
9/16"	1"	12-01815			5/8"	2	"	12-018	36	
5/8"	1"	12-01816			11/16"	2	"	12-018	37	
11/16"	1"	12-01817			3/4"	2	"	12-018	38	
3/4"	1"	12-01818			13/16"	2	"	12-018	39	
13/16"	1"	12-01819			7/8"	2	"	12-018	40	
7/9"	1"	12-01829			15/16"	2	"	12-018	41	
1"	1"	12-01831			1"	2	"	12-018	42	
1-1/16"	1"	12-01832			1-1/16"	2	"	12-018	43	
7/16"	1"	12-01833								
Assessmine for Base Drill Bast No. Drive					Duite					
Accessories for Base Drill				Pa	rt No.		Price			
1" Center Pin For SM4374				12	01845					

1" Center Pin For SM4374	12-01845	
1" Center For1" DOC Cutters	12-01844	
2" Center Pin For SM437L Only	12-01847	
2" Center For 2" DOC Cutters	12-01846	



1/2 INCH CHUCK & ADAPTER

With this optional industrial arbors and 2MT-1/2"Drill Chuck now you can! SteelMax industrial arbors let you easily adapt our premium m2AL cutters to a variety of machinery, including CNC, lathe's, stationary drill presses and similar equipment. With our integrated coolant collar, cutter

performance and cutter life is assured!P/N 12-01812

6 AND 13 PIECE CUTTER SETS

Description	Includes	Part No.	Price
6 Piece Set 1" DOC	9/16", 11/16", 13/16", 15/16", 1-1/16", Cutter Case, and 1" Pilot 9/16"-1-1/16"	12-01848	
6 Piece Set 2" DOC	9/16", 11/16", 13/16", 15/16", 1-1/16", Cutter Case, and 2" Pilot 9/16"-1-1/16"	12-01849	
13 Piece Set 1" DOC	7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8" 15/16", 1", 1-1/16", Cutter Case, and1" Pilot 7/16", 1" Pilot9/16"-1-1/16"	12-01850	
13 Piece Set 2" DOC	7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", 7/8" 15/16", 1", 1-1/16", Cutter Case, and1" Pilot 7/16"-1/2", 1" Pilot 9/16"-1-1/16"	12-01851	

TENSITRON TRANSDUCERS

Tensitron's transducers convert a material's tension into a reliable signal that can be used for remote indication, high-speed recording, computer hook-ups, or as input for automatic tension control systems. Note: A Signal Conditioner is needed to provide the necessary excitation, amplification, signal conditioning, calibration functions, display/readout and other options necessary to operate strain gaged transducers. Attention: Tensitron products may not be cancelled or returned.



TENSITRON FIBER AND WIRE TRANSDUCERS

-				
Model No.	Description	Tension Range	Part No.	Price
E-090-00	Single Roller Low Force Load Cell	1 - 100 lb.	12-05002	
E-091-00	3 Roller Low Force Load Cell		12-05003	
E-095-01	Notched Beam Trans- ducer	10 - 1,000 lb.	12-05005	
E-095-03	3 Roller Notched Beam Transducer	10 - 1000 lb.	12-05006	
E-415-002	Small Space Transducer with Single Roller	5 - 5,000 g	12-05011	
F-1806	Platform Mounted Fiber Transducer	5 - 5,000 g	12-05013	
FT-107	Small Space Fiber Transducer	5 - 5,000 g	12-05014	
FT-107- TIS	Small Space Fiber Transducer - Titanium	5 - 5,000 g	12-05015	
FT-116	Low Profile 3 Roller Sensor	5 - 5,000 g	12-05016	
FT-117	Single Roller Sensing Beam	5 - 5,000 g	12-05017	



TENSITRON WEB AND BELT TRANSDUCERS

Model No.	Description	Tension Range	Part No.	Price
4260	Single Roller Web Transducer.	2-200 lb.	12-05001	
E-091-02	Low Force Load Cell with Cyindrical Rollers	1-100 lb.	12-05004	
E-095-04	Notched Beam Transducer with Cylindrical Roller.	25-250 lb.	12-05007	
E-200-00	Cantilever Transducer	1-25 lb.	12-05008	-
E-202-00	Pillow Block Load Cell Transducer	25-1,000 lb.	12-05009	
E-210-00	S Column Transducer	5-250 lb.	12-05010	
E-415-003	Small Space Transducer with 3 Rollers	5-5000 g.	12-05012	



OMEGA-NEWPORT INFCS TRANSDUCER SIGNAL CONDITIONERS

Model No.	Description	Part No.	Price
INFCS-000	Infinity Basic Signal Conditioner, 115	12-	
B	VAC	05023	
INFCS-001	Infinity Basic Signal Conditioner,	12-	
B	115 VAC Analog Out	05024	
INFCS-010	Infinity Basic Signal Conditioner,	12-	
B	115 VAC Dual 5A Relays	05025	
INFCS-011 B	Infinity Basic Signal Conditioner, 115 VAC Analog Out & Dual 5A Relays	12- 05027	
INFCS-100	Infinity Basic Signa	12-	
B	Conditioner, 230 VAC	05028	
INFCS-101	Infinity Basic Signal Conditioner,	12-	
B	230 VAC Analog Out	05029	
INFCS-110	Infinity Basic Signal Conditioner,	12-	
B	230 VAC Dual 5A Relays	05030	
INFCS-111 B	Infinity Basic Signal Conditioner, 230 VAC Analog Out & Dual 5A Relays	12- 05031	
INFCS-411 B	Infinity Basic Signal Conditioner, 10 to 30 VDC Analog Out & Dual 5A Relays		