ALUMINUM TUBING

6061T6 SQUARE ALUMINUM TUBING

Size (In.)	Wall Thickness	Wt/Ft (Lb.)	Part No.	Price Per Ft.
1/2x1/2	.058	.156	03-00008	.
3/4x3/4	.049	.217	03-00009	.
1x1	.065	.300	03-38900	.
2x2	.125	1.120	03-00141	.
6061T6511 2x2	.190	1.420	03-00205	.
6063T52 2x2	.125	1.120	03-39000	.

5052-0 ALUMINUM TUBING

Rigid 5052-0 aluminum alloy tubing is used for low and medium pressure hydraulic systems, fuel lines and oil lines. This tubing will withstand a higher pressure than 3003-0 tubing.

O.D. (In.)	I.D. (In.)	Thickness	Wt./Ft. (Lb.)	Part No.	Price Per Ft.
1/8	.069	.035	.0101	03-39100	.
3/16	.132	.035	.0168	03-39200	.
1/4	.152	.049	.0371	03-39250	.
	.180	.035	.0281	03-39300	.
5/16	.242	.035	.0360	03-39400	.
3/8	.305	.035	.0449	03-39500	.
	.277	.049	.0602	03-39550	.
1/2	.436	.035	.0612	03-39600	.
	.402	.049	.0829	03-39650	.
5/8	.555	.035	.0760	03-39700	.
	.527	.049	.1060	03-39750	.
3/4	.680	.035	.0938	03-39800	.
	.652	.049	.1288	03-39850	.
1	.930	.035	.1256	03-39900	.
	.902	.049	.1754	03-39950	.

Sold in full 6-ft. or 12-ft. lengths only. No charge for cutting to 8 ft. or less for UPS shipment. Unlisted sizes of aluminum tubing available in full 12' lengths. No charge for cutting to 8' or less for UPS. Longer lengths shipped via truck. **Ordering tubing/bar by the foot. Add a dash number after part number to indicate length of tubing required. Ex: 3 ft required add -3, 03-00100-3.**

3003-0 VERSATUBE

Soft aluminum tubing for instrument air and vacuum lines, fuel and oil lines, and primer lines.

***Safety factor of 2 20% discount for full 50' coils of Versatube**

O.D. (In.)	Wall Thickness	Max. Working Pressure* (PSI)	Part No.	Price Per Ft.
1/8	.025	1820	03-40200	.
3/16	.028	880	03-40300	.
1/4	.032	795	03-40400	.
5/16	.035	630	03-40500	.
3/8	.035	520	03-40600	.
1/2	.035	390	03-40700	.
5/8	.035	305	03-40800	.

IF MFG TEST REPORTS ARE REQUIRED THERE IS A . CHARGE PER ORDER. PLEASE INDICATE AT TIME OF ORDER

ROUND ALUMINUM TUBING 6061T6

O.D. (In.)	I.D. (In.)	Wall Thickness	Wt./Ft. (Lb.)	Part No.	Price/Ft.
3/16	.118	.035	---	03-00012	.
1/4	.180	.035	.0281	03-35300	.
	.152	.049	.036	03-00014	.
5/16	.215	.049	.0423	03-35350	.
	.197	.058	.0561	03-35400	.
3/8	.305	.035	.0449	03-35500	.
	.259	.058	.0694	03-35600	.
	.245	.065	.0755	03-35700	.
	.209	.083	.0895	03-35750	.
7/16	.308	.065	.090	03-35775	.
1/2	.444	.028	.0496	03-35795	.
	.430	.035	.0612	03-35800	.
	.402	.049	.0816	03-35850	.
	.384	.058	.0962	03-35900	.
	.370	.065	.1040	03-35950	.
	.260	.120	.168	03-35975	.
5/8	.555	.035	.0775	03-36000	.
	.527	.049	.1060	03-36010	.
	.509	.058	.1227	03-36050	.
	.495	.065	.1367	03-36100	.
3/4	.680	.035	.093	03-36150	.
	.652	.049	.1288	03-36200	.
	.634	.058	.1506	03-36300	.
	.620	.065	.164	03-36350	.
7/8	.805	.035	.109	03-36375	.
	.777	.049	.150	03-36380	.
	.759	.058	.1777	03-36400	.
	.745	.065	.1983	03-36450	.
	.635	.120	.3350	03-36500	.
1	.930	.035	.1275	03-36600	.
	.902	.049	.1754	03-36610	.
	.884	.058	.2060	03-36700	.
	.870	.065	.2295	03-36800	.
	.830	.083	.281	03-36850	.
	.810	.095	.3244	03-36900	.
	.750	.125	.404	03-36950	.
	.500	.250	.693	03-36975	.
1-1/8	1.027	.049	.185	03-36980	.
	1.009	.058	.2321	03-37000	.
	.875	.125	.4712	03-37100	.
1-1/4	1.180	.035	.1601	03-37200	.
	1.152	.049	.2213	03-37210	.
	1.134	.058	.2601	03-37300	.
	1.120	.065	.2907	03-37400	.
	1.010	.120	.510	03-37450*	.
1-3/8	1.259	.058	.2865	03-37500	.
1-1/2	1.430	.035	.1928	03-37550	.
	1.402	.049	.2683	03-37610	.
	1.384	.058	.3137	03-37710	.
	1.370	.065	.3519	03-37800	.
	1.260	.125	.635	03-37850	.
1-5/8	1.509	.058	.3409	03-37900	.
1-3/4	1.680	.035	.2264	03-37910	.
	1.652	.049	.3142	03-37925	.
	1.634	.058	.3703	03-37950	.
	1.584	.083	.5202	03-37975	.
1-7/8	1.759	.058	.3954	03-38000	.
2	1.902	.049	.3601	03-38100	.
	1.884	.058	.4225	03-38200	.
	1.870	.065	.4743	03-38300	.
2-1/4	2.152	.049	.406	03-38307	.
	2.120	.065	.5328	03-38308	.
	1.959	.083	.824	03-38309	.
	2.000	.125	.999	03-38310	.
2-1/2	2.430	.035	.3254	03-38315	.
	2.402	.049	.444	03-38318	.
	2.370	.065	.5803	03-38320	.
3	2.930	.035	.3891	03-38330	.
	2.870	.065	.7140	03-38340	.
4	3.902	.049	.7153	03-38360	.

* This item will be supplied as either .120 or .125.