

STRATOFLEX HOSE & FITTINGS



STRATOFLEX 111 HOSE

Part No	Tube O.D.	Hose ID.	Max Press	Wt Per lb./in.	Price Per Ft.
111-4	.250	.188	3000	.0120	.
111-5	.312	.250	3000	.0130	.
111-6	.375	.312	2000	.0190	.
111-8	.500	.406	2000	.0220	.
111-10	.625	.500	1750	.0310	.
111-12	.750	.625	1500	.0380	.
111-16	1.00	.875	800	.0368	.

STRATOFLEX 300 STRAIGHT FLARED FITTINGS FOR 111 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
300-3S	.188	3/8-24	.
300-4S	.200	7/16-20	.
300-5S	.312	1/2-20	.
300-6S	.375	9/16-18	.
300-8D	.500	3/4-16	.
300-10D	.625	7/8-14	.
300-12D	.750	1-1/16-12	.
300-16D	1.00	1-5/16-12	.

STRATOFLEX 124 HOSE



Description	Part No.	Price
124-3 Hose	124-3	.
124-4 Hose	124-4	.
124-6 Hose	124-6	.
124-8 Hose	124-8	.
124-10 Hose	124-10	.

STRATOFLEX 156 MEDIUM PRESSURE HOSE



Part No	Tube O.D.	Hose ID.	Max Press	Mini Blend	Price/Ft.
156-3	.188	.156	1500	1.75	.
156-4	.250	.219	1500	2.00	.
156-5	.312	.281	1500	2.25	.
156-6	.375	.344	1500	2.50	.
156-8	.500	.438	1250	3.50	.
156-10	.625	.562	1250	4.00	.
156-12	.750	.688	1250	4.50	.
156-16	1.000	.875	1000	5.50	.

STRATOFLEX 678 45° ELBOW FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
678-3S	.188	3/8-24	.
678-4S	.250	7/16-20	.
678-6D	.375	9/16-18	.
678-8D	.500	3/4-16	.
678-10D	.625	7/8-14	.
678-12D	.750	1-1/16-12	.



STRATOFLEX 193 HOSE

Specifications: Hose meets or exceeds the requirements of MIL-H-5593. Construction: Tube - Seamless Buna - N. Reinforcement - One braid of high tensile fiber cord. Cover - Synthetic rubber. Identification: LP-MIL-H-5593-size, date of manufacture, manufacturer's code (CAGE) marked on one side of the hose. Stratoflex 193-size marked on other side of hose. Yellow markings are repeated every 12 inches. Application: Low pressure air and vacuum instrument systems. Vacuum service 20"Hg sizes -2 thru -6; 10"Hg sizes -8 and -10. Temperature range: -65 to +165°F / (-54 to +74°C).

Part No	Tube O.D.	Hose ID.	Max Press	Weight per ln. (l.b.)	Price Per Ft.
193-2	.35	.125	300	.0038	.
193-3	.41	.188	250	.0050	.
193-4	.48	.250	200	.0058	.
193-6	.60	.375	150	.0079	.
193-8	.75	.500	150	.0115	.
193-10	.87	.625	150	.0138	.

STRATOFLEX 646/640 45° ELBOW FLARED FITTINGS FOR 111 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
646-4S	.250	7/16-20	.
646-6S	.375	9/16-18	.
646-8D	.500	3/4-16	.
646-10D	.625	7/8-14	.
640-12D	.750	1-1/16-12	.
640-16D	1.00	1-5/16-12	.

STRATOFLEX 649/643 90° ELBOW FLARED FITTINGS FOR 111 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
649-4S	.250	7/16-20	.
649-6S	.375	9/16-18	.
649-8D	.500	3/4-16	.
649-10D	.625	7/8-14	.
649-12D	.750	1-1/16-12	.

STRATOFLEX 676 STRAIGHT FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
676-3S	.188	3/8-24	.
676-4S	.250	7/16-20	.
676-5S	.312	1/2-20	.
676-6D	.375	9/16-18	.
676-8D	.500	3/4-16	.
676-10D	.625	7/8-14	.
676-12D	.750	1-1/16-12	.
676-16D	1.000	1-5/16-12	.

STRATOFLEX 680 90° ELBOW FLARED FITTINGS FOR 156 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
680-3S	.188	3/8-24	.
680-4S	.250	7/16-20	.
680-5S	.312	1/2-20	.
680-6D	.375	9/16-18	.
680-8D	.500	3/4-16	.
680-10D	.625	7/8-14	.
680-12D	.750	1 1/16-12	.
680-16D	1.000	1 5/16-12	.

STRATOFLEX 311 STRAIGHT FLARED FITTING FOR 193 HOSE



Part No.	Tube O.D.	Thread	Price Ea.
311-2D	.125	5/16-24	.
311-3D	.188	3/8-24	.
311-4D	.250	7/16-20	.
311-6D	.375	9/16-18	.
311-8D	.500	3/4-16	.
311-10D	.625	7/8-14	.

STRATOFLEX 2650 FIRE SLEEVE



Part No.	Use With Hose No.	*10781-4 Clamp	Price Per Ft.
2650-6	-4	-	-
2650-8	-6	-3	-4 22CR
2650-9	-	-4	-5 22CR
2650-10	-8	-4	-6 22CR
2650-11	-	-6	-
2650-12	-10	-5,-6	-8 22CR
2650-13	-	-8	-
2650-14	-12	-	- 22CR
2650-16	-	-10	-10 32CR
2650-18	-	-	-12 32CR
2650-20	-16	-	-12 32CR
2650-22	-	-16	-16 32CR

STRATOFLEX FIRE SLEEVE END DIP



Stratoflex 5027 Room temperature curing cement for Stratoflex Firesleeve. To use, dip each end of firesleeve in accordance with P-104-29 and applicable drawing. Always use current specifications.

P/N 5027