

# O-RINGS

## AN6230B O-RINGS

| Part No.   | MS Equivalent | Width | ID    | OD    | Price |
|------------|---------------|-------|-------|-------|-------|
| AN6230B-1  | MS28775-223   | 1/8   | 1-5/8 | 1-7/8 | .     |
| AN6230B-2  | MS28775-224   | 1/8   | 1-3/4 | 2     | .     |
| AN6230B-3  | MS28775-225   | 1/8   | 1-7/8 | 2-1/8 | .     |
| AN6230B-4  | MS28775-226   | 1/8   | 2     | 2-1/4 | .     |
| AN6230B-5  | MS28775-227   | 1/8   | 2-1/8 | 2-3/8 | .     |
| AN6230B-6  | MS28775-228   | 1/8   | 2-1/4 | 2-1/2 | .     |
| AN6230B-7  | MS28775-229   | 1/8   | 2-3/8 | 2-5/8 | .     |
| AN6230B-8  | MS28775-230   | 1/8   | 2-1/2 | 2-3/4 | .     |
| AN6230B-9  | MS28775-231   | 1/8   | 2-5/8 | 2-7/8 | .     |
| AN6230B-10 | MS28775-232   | 1/8   | 2-3/4 | 3     | .     |

## VITON MS83248 O-RINGS



Fluorocarbon rubber o-rings. Fluorocarbon rubber is commonly known as Viton. It is an advanced rubber that has extremely good fuel and heat resistance and is ideally suited for aircraft fuel system applications.


| Model        | Specifications                             | Part No. | Price |
|--------------|--------------------------------------------|----------|-------|
| M83248/1-006 | 1/8 ID X 1/4 OD X 1/16 W                   | 05-22191 | .     |
| M83248/1-008 | 3/16 ID x 5/16 OD x 1/16 W                 | 05-12761 | .     |
| M83248/1-010 | 1/4 ID x 3/8 OD x 1/16 W                   | 04-03305 | .     |
| M83248/1-011 | 5/16 ID x 7/16 OD x 1/16 W                 | 08-13085 | .     |
| M83248/1-022 | --                                         | 04-04173 | .     |
| M83248/1-015 | 9/16 ID x 11/16 OD x 1/16 W                | 04-03836 | .     |
| M83248/1-119 | 13/16 ID x 15/16 OD x 1/16 W               | 05-14681 | .     |
| M83248/1-111 | 7/16 ID x 5/8 OD x 3/32 W                  | 04-02549 | .     |
| M83248/1-113 | 9/16 ID x 3/4 OD x 3/32 W                  | 04-02551 | .     |
| M83248/1-115 | 11/16 ID x 7/8 OD x 3/32 W                 | 04-03837 | .     |
| M83248/1-117 | 13/16 ID x 1 OD x 3/32 W                   | 08-10794 | .     |
| M83248/1-120 | 1 ID x 1-3/16 OD x 3/32 W                  | 04-03833 | .     |
| M83248/1-126 | 1-3/8 ID x 1-9/16 OD x 3/32 W              | 04-03835 | .     |
| M83248/1-127 | --                                         | 04-04170 | .     |
| M83248/1-130 | --                                         | 04-04171 | .     |
| M83248/1-133 | --                                         | 04-04172 | .     |
| M83248/1-216 | --                                         | 05-13046 | .     |
| M83248/1-224 | 2-7/16 ID x 2-5/8 OD x 3/32 W              | 04-03840 | .     |
| M83248/1-224 | 1-3/4 ID x 2 OD x 1/8 W                    | 04-03842 | .     |
| M83248/2-904 | --                                         | 04-04165 | .     |
| M83248/1-012 | --                                         | 04-02536 | .     |
| M83248/1-128 | 1-1/2 in ID, 1-11/16 in OD, 3/32 in Thick  | 05-32537 | .     |
| M83248/1-223 | 1-5/8 in ID x 1-7/8 in OD x 0.139 in Thick | 05-32538 | .     |
| M83248/1-230 | 2-1/2 in ID x 2-3/4 in OD, 1/8 in Thick    | 05-32539 | .     |
| M83248/1-910 | 3/4 in ID x 3/32 in Thick                  | 05-32540 | .     |
| M83248/1-916 | 1-23/64 in ID, 7/64 in Thick               | 05-32541 | .     |

## 800-0001-6 PACKING SEAL



The 800 Series Lock-O-Seal is a two piece combination seal comprised of a separately molded O-ring fitted within a surrounding metal washer. These Lock-O-Seals are intended to seal beneath the head of a fastener .....P/N 05-14698 .....

## M83461/1-222 MILITAR NITRILE O-RING



Used in MIL-H-5606 Fluid; Aircraft Hydraulic Fluid. Better dynamic performance than MS28775. Excellent resistance to petroleum-based products; hydraulic fluids; most silicone fluids; and fuels. Excellent resistance. Dimensions: (1-1/2 ID X 1-3/4 OD X 1/8 W) P/N 04-03601 .....



## AS3569-232 O-RING

O-Ring AS3569-232. (2-3/4 ID X 3 OD X 1/8 W). P/N 04-02528 .....



## AS3208-4 O-RING

O-Ring AS3208-4.....P/N 05-27151 .....



## AS3209-016 O-RING

O-Ring AS3209-016.....P/N 05-27153 .....



## AS3209-126 O-RING

O-Ring AS3209-126.....P/N 05-27152 .....



## MS28776M2-22 METAL SCRAPER RING

P/N 05-15260 .....



## NAS1611 O-RING

O-rings give effective sealing over wide ranges of pressure, temperature, and movement, with the advantage of sealing pressure in both directions and reducing friction and wear on moving parts. The use of O-rings as gaskets or static seals permits metal-to-metal contact and allows almost unlimited pressures under extreme vibration.

| Part No     | MS Equivalent | Width | ID    | OD    | Price |
|-------------|---------------|-------|-------|-------|-------|
| NAS1611-268 | MS28775-268   | 1/8   | 8-1/2 | 8-3/4 | .     |

## MS28773 O-RINGS

| Model      | Specifications                                        | PN       | Price |
|------------|-------------------------------------------------------|----------|-------|
| MS28773-08 | Dia: 0.656 in • Width: 1/8 in • Thickness: 0.061 in   | 05-32534 | .     |
| MS28773-10 | Dia: 0.769 in • Width: 0.131 in • Thickness: 0.073 in | 05-32535 | .     |
| MS28773-16 | Dia: 1.191 in • Width: 0.169 in • Thickness: 0.073 in | 05-32536 | .     |



## AN901 O-RINGS

AN901 tube connection seals are fabricated from type 1100 alum., H14 temper.

**Discount Less 20% For 100 Per Size**

| AN901 Dash No. | Tube O.D. | Price Each | AN901 Dash No. | Tube O.D. | Price Each |
|----------------|-----------|------------|----------------|-----------|------------|
| -4A            | 1/4       | .          | -8A            | 1/2       | .          |
| -5A            | 5/16      | .          | -10A           | 5/8       | .          |
| -6A            | 3/8       | .          | -12A           | 1-1/16    | .          |
| -4C            | 1/4       | .          | -10C           | 5/8       | .          |
| -5C            | 5/16      | .          | -12C           | 3/4       | .          |
| -6C            | 3/8       | .          | -16A           | 1         | .          |



## AN/MS O-RING KIT

This AN/MS O-Ring Kit includes over 382 O-rings made of Nitrile Buna N 70 duro material. These rings have a temperature range of -6 to 275°F and are for use with petroleum oils and fluids. Size range in kit is 0 through 30.(O-Ring Set An6227B-1, -30).....P/N 05-02210 .....



## AS568A O-RING KIT

- 70 Duro Nitrile
- 382 O rings
- Great kit for the homebuilder
- Sizes: -06 to -32 ....P/N 13-02804 .....