

FUEL FILTERS – FUEL EXTENSION KITS

PHENIX SELECT-FLO FUEL FILTERS



Phenix Select-Flo Fuel Filter: select the inlet size from -6 to -10 and the outlet size from -6 to -10 based on what your engine needs. No ORB fittings to buy in addition to the filter, the male AN is machined onto the filter caps, along with 100 micron. All filter elements in stainless steel mesh so they can be cleaned and used indefinitely. Proudly manufactured in the USA.

Description	Part No.	Price
Select-flo Filter Dash 10 In To Dash10 Out Blk / 100 Micron Element	04-03671	.
Select-flo Filter Dash 8 In To Dash 8 Out Blk / 100 Micron Element	04-03672	.
Select-flo Filter Dash 6 In To Dash 6 Out Blk / 100 Micron Element	04-03673	.

PHENIX SELECT-FLO FUEL FILTER BRACKETS

Phenix Select-Flo Fuel Filter Brackets: All filter elements in stainless steel mesh so they can be cleaned and used indefinitely. Proudly manufactured in the USA.



Description	Part No.	Price
Select-flo Filter Mounting Bracket Type A	04-03666	.
Select-flo Filter Mounting Bracket Type B	04-03667	.
Select-flo Filter Mounting Bracket Tube Mount 1-1/2"	04-03668	.
Select-flo Filter Mounting Bracket Tube Mount 1-5/8"	04-03669	.
Select-flo Filter Mounting Bracket Tube Mount 1-3/4"	04-03670	.

KING AIR FUEL FILTER DRAIN VALVE



Improved, repairable valve for thousands less than Beech!

- Improved seal design provides a long life reliable valve
- Teflon lined control conduit and stainless steel cable
- Reliable design - proven to over 10,000 cycles
- Latest Viton fuel-proof seals
- Anodized for better corrosion resistance
- Unheard of 10 Year Limited Warranty!

Consists of two components: a valve housing and a replaceable valve control plunger assemblyP/N 05-13139

MICRON 10 FUEL FILTER

Length: 4.25"; Diameter: 2.0"; Flow rate: 15.3 gpm; Weight: 5 oz.; Fitting Size: use (-6) Phenix Fittings - see "Accessories" tab; Filter medium: 1.375" dia. 304 pleated SST disk; Filter Efficiency: 10 Micron; Operating Pressure: 8,000 PSIG; Drop in pressure: 1.0% Fitting Size: AN6. This filter is washable and reusable..... P/N 05-01699



Replacement Screen..... P/N 05-21822

FILTERS FOR ELECTRONIC FUEL INJECTION PUMPS



If you have electronic fuel injection, you should run a coarse pre-filter (FF-2, 90 micron) before the fuel pump, and a fine post filter (FF-1, 10 micron) after the fuel pump. If you are running mechanical fuel injection, you will only need the FF-2 pre-filter.

The FF-2 pre-filter is a 90 micron stainless mesh filter that will keep large debris from entering and damaging your fuel pump. The FF-1 post-filter is a 10 micron, high surface area, high pressure filter that will keep fine particulates out of your electronic fuel injectors, if so equipped.

Mechanical Injection Systems Require Only a Pre Filter
Specifications: FF-1 - Includes one 10 micron post pump filter with AN-6 fittings and mounting clamp • FF-2 - Includes one 90 micron screen pre pump filter with AN-6 fittings and mounting clamp.

Post FilterP/N 07-19989

Pre FilterP/N 07-19990



ACS FREE FLOW ONE-WAY CHECK VALVE

Prevents return fuel flow during normal operation but provides by-pass fuel feed in an emergency if the fuel pump fails. Wt. 1 oz., 2-7/8" long. Use with tube fittings for 3/8" dia. fuel line. Anodized for corrosion resistance.

P/N 10630



PIPER DRAIN VALVE FOR PA-15/PA-17

Model	Description	Part No.	Price
22179-000	Fuel Drain Valve 3/8" NPT	05-21969	.
189-543	Fuel Drain Plastic Tubing	05-21970	.



CESSNA DRAIN VALVES

S2106-4.....P/N 06-03056

S2020-2.....P/N 06-00989



INLINE FUEL FILTER

In-line, high-capacity, translucent filter with screen. Has standard 1/4" barb inlet and outlet tubes.

P/N 05-14958



FUEL FILTER

In-tank type. Brass construction with fine-mesh screen. Has standard 1/4" barb inlet and outlet tubes

P/N 05-01031



3/8 INCH PLASTIC FILTER

Plastic in-line fuel with 3/8" inlet & outlet - metal version is 33033 with hoses and camps. Style: Fuel Filter. Height: 3.543. Outer Diameter: 1.826. Nominal Micron Rating: 30.

P/N 05-04701

FUEL FILTERS

For homebuilts. Used on VariEze and various gyrocopters. Rated to 10 PSI. Not recommended for fuel injected systems.



Description	Part No.	Price
1/4" Fuel Filter (Metal)	05-33031	.
3/8" Fuel Filter (Plastic)	05-04701	.
1/4" Fuel Filter (Plastic)	05-33001	.
Universal Fuel Filter Inline 1/4", 5/16", 3/8"	15-05826	.

ANDAIR FS20 SERIES FUEL SELECTOR EXTENSION KITS



Steps	Valve Model/Length	Part No.	Price
Extension Kits	FS20-1	05-15318	.
--	FS20-2	05-15319	.
--	FS20-3	05-15320	.
--	FS20-4	05-15321	.
--	FS20-5	05-15322	.
--	FS20-7	05-15323	.
--	FS20-8	05-15324	.
Extension Tubes	6"	05-15325	.
--	12"	05-15326	.
--	18"	05-15327	.
--	24"	05-15328	.
--	30"	05-15329	.
--	36"	05-15330	.