

AIR FILTERS – LUBRICANTS – DEGREASERS

AIR-MAZE AIR FILTERS



Filter for Continental for A-65 thru C-125*.
P/N A40599
Filter for Lycoming O-235, O-290, some O-320 (advise aircraft application).....P/N A40599
Aeronca 7AC, 11AC.....P/N 2-849

***FOR NEW INSTALLATION - P/N 24306 & P/N 24308 ARE REQUIRED**

VARI-EZE / LONG

EZ AIR INTAKE FILTER



NAPA #2904 air intake filter (equivalent to Purolator #AFP-177 & AC #44-8C) .P/N 2904

OVAL AIR FILTER FOR DUAL BING 54 CARBURETOR



Oil impregnated, pleated, washable, polyester air filter. Can be washed and re-oiled for years. Traps dirt and other foreign particles to keep engine clean.
Filter for Rotax 532 582 and 618P/N 15-08370
Filter for Rotax 503.....P/N 15-08343

NAPA AIR FILTER



Air Filter for 7GCA, 7GCB, 7GC, 7HC Models. Experimental Only. Direct replacement of FRAM made by NAPA.....P/N 05-06388

NAPA 6153 GOLD AIR FILTER



These Filters Contain 30% More Media Than OES Filters And Use A Phenolic Resin Treated Enhanced Cellulose Media Which Provides Excellent Durability Against Moisture Ingestion. When Applicable, The High-Tear Strength Polyurethane Seal Survives Extreme Hot And Cold Temperature Conditions. Air Filter Laboratory Tests Per ISO 5011 At Least 99.5% Efficiency (Based On NAPA # 2389) NAPA Gold Filters Are Recommended For OEM Air Filter Change Intervals. **Specifications:** • Height (Inches): 1.62 in • Length: 10.68 in • Width: 7.95 in P/N 08-17162

NAPA 7243 OIL FILTER



HD Oil Filters Feature a Cellulose/Poly Media w/ Contaminant Holding Capacity
Specifications: • Filter O.D. (Inches): 3.778 in. • Flow Rate: 28 To 30 gpm • Height (Inches): 5.962 in. • Micron Rating: 21 • Style: Spin-On Oil Filter • Thread Size: 1-1/2 in-16.
P/N 08-17161

GPL WASHABLE RE-USEABLE AIR FILTER FOR BING 54



Oil Impregnated, Pleated, Washable, Polyester Air Filter. Can be washed and re-oiled for years. Fits Bing 54 Carburetor. GPL Part # 3920 For Bing 54. 3.5" D x 4" L x 2 1/16" IDP/N 08-07665

MCFARLANE AIR FILTER SHROUD ASSEMBLIES



McFarlane now has FAA-PMA approval on their improved Cessna Airbox Shroud/Seal Assemblies for various 150, 152 and 172 aircraft! McFarlane patented Cowl Saver Material with Bi-Flex is used with the new shroud to prevent cowl damage.

Description	Part Number	Price
MC0450066-5 Air Filter Shroud Assembly	05-27124	.
MC0452017-15 Air Filter Shroud Assembly	05-27125	.
MC052130-11 Air Filter Shroud Assembly	05-27126	.

PERMATEX FORM-A-GASKET NO. 1



Seals and repairs a wide range of gaskets. Fills in uneven flanges surfaces. Seals pipe fittings, air ducts, boilers, plumbing connections and threaded assemblies. Dries fast, sets hard for sealing permanent or rigid assemblies. Easy to apply. Improves gasket sealing power, adds reliability to rigid or permanent assemblies. Eliminates delays.
3 oz., Tube, #1BP/N 09-28415
11 oz, Tube, #1CP/N 09-28430

PERMATEX FORM-A-GASKET NO. 2



A non-hardening, heavy-bodied, pliable sealant for semi-permanent assemblies. Use on threaded assemblies, over plates and hose connections, metal-to-metal applications. Temperature range -65° to 400° F., pressures up to 5000 PSI. Apply with putty knife or stiff bristle brush. Conforms to MIL-S-45180B Type II.
3 Oz. Tube #2BP/N 09-28420
11Oz. Tube #2CP/N 09-28400

LOCTITE® HIGH TEMPERATURE GASKET SEALANT



LOCTITE® High Temperature Gasket Sealant is a slow drying viscous paste. It remains pliable and flexible and is designed to seal flanges, threaded connections and fasteners at temperatures from -45° C to +315 °C. It can be effectively applied to cork, paper, plastic and metal surfaces. P/N 09-28425

ANDEROL ROYCO 782 HYDRAULIC FLUID



Synthetic fire resistant "Super Clean" hydraulic fluid ROYCO 782 is a red - colored synthetic hydraulic fluid developed to meet the severe duty demands of today's military and industrial equipment. Modern additive technology is employed for oxidative stability, corrosion inhibition, and anti-wear protection. ROYCO 782 is compatible with petroleum based fluids and all components used in mineral oil type hydraulic systems. Mil-Spec: MIL-PRF-83282.

Quart.....P/N 08-07539-1
Case (24 Quarts).....P/N 08-07539

ROYCO 757 HYDRAULIC FLUID

Royco® 757 hydraulic and preservative fluid is a super-clean, additized, highly refined mineral oil that is intended to be utilized across a wide operating temperature range. from -64°C to +135°C.

5 GallonP/N 08-19305

ROYCO 602 FLUID DIELECTRIC

Royco® 602 is a synthetic based dielectric coolant consisting of a stable synthetic hydrocarbon known as polyalphaolefin (PAO) and modern additives. Royco® 602 offers exceptional performance over a temperature range of -54 to 200 °C.

5 GallonP/N 08-19308

ROYCO 950 CALIBRATION FLUID

Royco® 950 is a specialized fractionation of a Stoddard solvent with stabilizing additives to prevent the formation of gums and peroxides. Royco® 950 is used for the calibration of fuel system components in both reciprocating and gas turbine aircraft engines. Royco® 950 meets all requirements of MIL-PRF-7024G.

5 GallonP/N 08-19307

55 GallonP/N 08-19304

AVIATION FORM-A-GASKET NO. 3



Slow-drying, non-hardening brush-top sealant approved for use in aviation as well as automotive applications. Temperature range -65°F to 400°F (-54°C to 204°C); resists gasoline, oil and grease. **Application:** Close-fitting machined surfaces, sealing hoses, solid gaskets. Conforms to MIL-S-45180B, Type III.

4 Oz. Can #3HP/N 09-28500
1 Pint Can #3DP/N 09-28600

MARVEL MYSTERY OIL



Standard for break-in on new or overhauled engines and for carbon removal from cylinder heads, piston rings, valves, etc. Mix with regular oil for perfect engine operation to -20°F. Lubricates tight nuts, control hinges and landing gear. Dust repellent.

Quart.....P/N 09-27500
PintP/N 09-27505
GallonP/N 09-27600

MOUSE MILK OIL



For speedy help in removal of rusted or frozen studs, nut and bolts; frees up cables, slides and linkage; unequalled wherever a lubricant and penetrant are required. Lasting lubricating qualities.

Attention: Volatile Organic Compounds (VOCs) Government Regulations. Product cannot be purchased, sold, or used in California.

8 OzP/N 09-39608
32 OzP/N 09-39632

MOUSE MILK OIL PURPLE - VOC COMPLIANT



Mouse Milk Purple is a vegetable oil based VOC-compliant alternative to the traditional Mouse Milk. The Greener Alternative. For speedy help in removal of rusted or frozen studs, nut and bolts; frees up cables, slides and linkage; unequalled wherever a lubricant and penetrant are required. Lasting lubricating qualities.

8 OzP/N 09-05784

BENDIX MAGNETO GREASE



#10-27165 - Factory recommended lubricant for bearings in Bendix magnetos. 1 Lb. Can..... P/N 10-27165
#10-391200 - For use on distributor block bushing. Provides proper shaft lubrication. 8 oz. can. P/N 10-391200
#10-86527 - High temperature breaker/cam lubricant
P/N 10-86527

AIM-A-SQUIRT



Apply lubricants, corrosion inhibitors and solvents in those hard to reach areas with out getting the products all over everything. Aim-A-Squirt has been tested with hundreds of different products which have had no affect on the special plastics the straw is made of. The straw is flexible enough that it will not kink when it is twisted in a small circle. • Two sizes to fit most cans • 32" lengthP/N 09-02325

EP