

POLY-FIBER AIRCRAFT COATINGS

AIRCRAFT SPRUCE - WORLD'S LARGEST DISTRIBUTOR OF POLY-FIBER PRODUCTS



This FAA approved process utilizing Poly-Fiber Dacron polyester and the unique "Poly" line of finishes assures a beautiful, durable, weather-resistant cover job every time. Documented time tested results by the professionals. The Poly-Fiber Covering Process was issued Supplemental Type Certificate No. SA-1008-WE in 1965 and this number will apply to all aircraft.

Note: Formerly known as Stits covering process. Only Poly-Fiber materials may be used through the topcoat paint to comply with STC requirements. Poly-Fiber finishes are required for approval. Poly-Fiber is approved for use on most certified aircraft. To be sure, check the Master Eligibility List in the latest revision of Poly-Fiber Procedure Manual No. 1.

POLY-FIBER FABRIC

UNCERTIFIED LIGHT




1.87 oz/sq. yard. Lightweight fabric recommended for covering ultralight aircraft. This fabric will be unstamped. It is not approved for certified aircraft except on plywood surface. 72" Width.
P/N 09-02001 /Linear Yd.

MEDIUM WEIGHT



2.79 oz/sq. yard. Standard fabric recommended for normal service on all types of aircraft regardless of speed, wing loading or horsepower.
P/N 09-01600 /Linear Yd.

HEAVY DUTY



3.40 oz/sq. yard. Recommended for severe operating conditions and very high wing loading aircraft where a very tough, durable, low elongation, high tension fabric is required and weight is not critical. Great for agricultural, aerobatic and bush planes. 72" Width.
P/N 09-01700 /Linear Yd.

POLYESTER PADDING

Non -woven, 45" wide, 3 oz. per yard. Used under fabric on wing leading edge and turtle deck to smooth rough surfaces.

P/N 09-01750

POLY-FIBER POLYESTER PINKED EDGE TAPES

Part No.	Style #	Roll Width	Roll Length	Price.
09-02200	Med.	1"	25 yds.	.
09-02400	Med.	1-1/2"	25 yds.	.
09-02450	Med.	2"	25 yds.	.
09-02500	Med.	2"	50 yds.	.
09-02900	Med.	3"	25 yds.	.
09-03300	Med.	4"	25 yds.	.
09-03350	Med.	6"	25 yds.	.
09-02300	Light	1"	25 yds.	.
09-02350	Light	1-1/2"	25 yds.	.
09-02705	Light	2"	25 yds.	.
09-02700	Light	2"	50 yds.	.
09-03100	Light	3"	25 yds.	.
09-03400	Light	4"	25 yds.	.
09-03545	Light	6"	25 yds.	.
09-03565	Bias	2"	25 yds.	.
09-03570	Bias	3"	25 yds.	.
09-03580	Bias	4"	25 yds.	.

POLY-FIBER TAPES, CORD & THREAD



	Item	Part No.	Yards Spool	Price
Reinforcing Tape	3/8" Wide	09-03600-1	60	.
	1/2" Wide	09-03700-1	60	.
Rib Lacing Cord	(Std. Round)	09-03800	296	.
	Rib Cord, Flat	09-03810	500	.
Sewing Thread	Machine	09-03900	500	.
	Hand	09-04000	250	.
Anti-Chafe	1" Wide	09-02110	30	.

HEAVY INTER-RIB BRACING TAPE

Non-adhesive polyester twill tape for inter-rib bracing. Twice as strong as cotton tape. 36 yd. rolls. 1/2" Wide P/N 09-40912

THE POLY-FIBER PRACTICE KIT



If you're thinking of building a fabric-covered airplane but are wondering what the covering process is like, this is the perfect answer. You get a practice frame, fabric, tapes, needles, rib lacing cord, thermometer, instructions, and all the coatings you need to work through the Poly-Spray stage. There's enough of everything to do the entire process twice. You'll see how easy and enjoyable fabric covering really is.

P/N 09-06220

POLY-FIBER COLOR CHART #50



Note: These samples are an approximate computer representation of the actual color and are to be used for reference only.

P/N 09-00234

POLY-FIBER SOLVENTS & CLEANERS



METL-SOL C-2200 METAL SURFACE CLEANER

A strong solvent blend formulated to remove oil, silicone, wax and other contaminants from all metal surfaces before priming. Not for painted surfaces.

Quart.....P/N 09-40710

Gallon.....P/N 09-40720



C-2210 PAINT SURFACE CLEANER

A mild solvent blend formulated to remove oil, silicone, wax and other contaminants from all painted or primed surfaces. Also removes tape gum from painted surfaces and acrylic windshield materials.

Quart.....P/N 09-40810

Gallon.....P/N 09-40820



310 ALKALINE DETERGENT CLEANER

Highly recommended as an alkaline metal cleaner for removing greases and oils. Also a very good cleaner for interior cabins and vinyl upholstery, as well as a wide variety of household applications to remove waxes, dirt, and stains. Furnished as a concentrate for 32:1 dilution with water. Lemon scented and not harmful to your hands.

Quart.....P/N 310-QT

Gallon.....P/N 310-1G



POLY-FIBER MEK

Solvent used to remove coatings for repairs, for clean up, and to release cemented seams. NOT used to thin or reduce any products.

Quart.....P/N 09-40835

Gallon.....P/N 09-40845

CS