

# 3M™ ABRASIVES - ADHESIVES

## 3M™ GREEN CORPS™ CUT OFF WHEEL



Wheel is designed to provide high cut rates and long life on most all materials including fiberglass, stainless steel, mild steel and aerospace alloys. Ideal for use on a wide variety of utility type cut off tools. Do not use on tools without guards. 4"X1/32"X3/8".....P/N 09-01524 .....

## 3M™ SCOTCH-BRITE™ DEBURRING WHEEL



**Two Styles Available:** Cut & Polish/Unitized Wheel-7A Medium grade (harder) Use to radius and deburr edges of aluminum parts. These wheels give a uniform brushed satin finish to parts and deburr quicker and easier than hand finishing. These wheels are discs of Scotch-Brite web compressed and bonded to form a rugged, dense wheel. Wheel size: 6" dia. x 1" wide x 1/2" thru hole.....P/N 12-00875 .....

### Light Deburring Wheel-7S Fine Grade (Softer)

Light deburring 7S Fin 6 x 1 x 1. This wheel has a 1" thru hole. To fit 1/2" order P/N 12-01585.....P/N 12-00948 .....

### 9S Deburring Wheel - Fine Grade (Softer) - 1" thru hole

P/N 09-05641 .....

3M Flange Adapter 3 45035 1/2".....P/N 12-01585 .....

## 3M™ ROLOC™ DISC PAD



3M™ Roloc™ Disc Pad TR 45092, Medium 3" 1/4-20 Internal. 3M™ Roloc™ Disc Pad optimizes the performance of Roloc™ discs and bristle discs by providing the right backup system and a secure attachment for grinding applications. Plus it saves time by eliminating the need to align edges of the disc with the disc pad—the screw aligns the disc, making disc changes quick and easy.....P/N 09-01554 .....

## 3M™ 5 INCH 80 GRIT SANDING DISC



3M SandBlaster 5" 8 Hole Sanding Disc. 80 grit disc, designed for moderate stripping and surface leveling. Premium Cubitron™ ceramic mineral. Clog-resistant. Designed for use on random orbital sanders. Stays significantly sharper longer to sand faster than 3M conventional sandpaper of comparable grit. Use on wood, oil enamel, latex primer, lacquer, sanding sealer and other coatings.....P/N 09-05427 .....

## 3M™ SILVER CUT-OFF WHEEL



The 3M™ Silver Cut-Off Wheel is designed to deliver an unbeatable combination of performance and value in metal cutting applications. This long-lasting wheel uses 3M Precision-Shaped Grains to deliver a fast and consistent cut through pipes, tubes or flat sheets of stainless steel, mild steel, aerospace alloys and more. 3" x .035".....P/N 09-06468 .....


## 3M™ SCOTCH-WELD™ DP8507NS GRAY



3M™ Scotch-Weld™ Acrylic Adhesive 8507NS delivers long-lasting performance when bonding metal. Designed as a replacement for welding and mechanical fasteners, this non-sag adhesive delivers high-strength bonds on aluminum, cold-rolled steel, stainless steel, galvanized steel, copper, brass, and most plastics. Even in temperatures as low as -40 °F (-40 °C) and in powder coat and paint bake cycles up to 392 °F (200 °C) for 30 minutes. 45 ml. 45 ml Duo-Pak.....P/N 09-06564 .....

490 ml Duo-Pak.....P/N 09-06555 .....

## 3M™ SCOTCH-WELD™ DP190 TRANSLUCENT EPOXY ADHESIVE



3M™ Scotch-Weld™ Epoxy Adhesive DP190 is a two-part epoxy adhesive that delivers exceptional performance with high shear and peel strength. This epoxy adhesive is formulated to bond to a wide range of materials, such as metals, ceramics, wood, fiberboard, glass, rubber and many plastics. 48.5MI Duo-Pak.....P/N 02-00252 .....

200 MI Duo-Pak.....P/N 09-06478 .....

## 3M™ SCOTCH-WELD™ EPOXY ADHESIVE 2216 B/A



A flexible, two part, room temperature curing epoxy with high peel and shear strength. Scotch-Weld epoxy adhesive 2216 B/A is identical to 3M™ Scotch-Weld™ Epoxy Adhesive EC-2216 B/A in chemical composition. Scotch-Weld epoxy adhesive EC-2216 B/A has been labeled, packaged, tested, and certified for aircraft and aerospace applications if proper Certificates of Test have been issued and material meets all aircraft manufacturer's specification requirements. 24 month shelf life.

| Size  | Color | Description       | Part No. | Price |
|-------|-------|-------------------|----------|-------|
| 2 oz. | Gray  | Adhesive 2216 B/A | 02-00045 | .     |
| Pint  | Gray  | Adhesive 2216 B/A | 02-00113 | .     |
| Quart | Gray  | Adhesive 2216 B/A | 02-00114 | .     |

## 3M™ SCOTCH-WELD™ EPX 10 TO 1 MIXING NOZZLE



Designed to be used with 10:1, 45 mL Duo-Pak cartridges. It has a tapered tip that can be cut to adjust bead size for smooth even application. **Specifications:** • Typical Use: Mixing nozzle for 10:1 45 mL Duo-Pak cartridges, and the EPX Plus II applicator • Brand: Scotch-Weld • Color: Orange.....P/N 12-05508 .....

## 3M™ HI-STRENGTH 90 SPRAY ADHESIVE



3M™ Hi-Strength 90 Spray Adhesive is a fast-drying, transparent spray adhesive that bonds on concrete, wood, MDF, laminates, polyethylene and more. Its extremely strong bond gives you fast results to keep projects moving forward. This industrial grade formula is easy to dispense and apply directly to surfaces and materials and provides the added benefit of high heat and moisture resistance. 24 oz.....P/N 09-01376 .....



## 3M™ HI-STRENGTH SPRAY ADHESIVE 90 LOW VOC

3M™ Hi-Strength 90 CA Spray Adhesive - Low VOC <25% is an extremely versatile, fast-drying spray adhesive that bonds strongly to a wide range of materials. The spray formula is easy to dispense and offers a variable-width spray pattern, applying directly onto surfaces and materials where needed. This permanent bond provides fast results to keep projects moving ahead.....P/N 09-06162 .....



## 3M™ SCOTCH-WELD™ INSTANT ADHESIVE SURFACE ACTIVATOR

It is ideal for use with all 3M Cyanoacrylate Adhesives for a broad range of industrial and electronic applications. It is also ideal for use with CA-5, CA-9, or CA-50 Gel for many wire tacking and coil terminating applications. P/N 09-01407 .....

## 3M™ SCOTCH-WELD™ EPX PNEUMATIC MIXING NOZZLE



With consistent air pressure for easy uniform application, the Duo-Pak cartridge will give you the flow rate needed. Fast, convenient way to simultaneously meter, mix and apply two-part adhesives and potting compounds. A slight squeeze on the trigger advances the plunger into the cartridge. Accurate measurement and the mixing nozzle provides thorough mixing and precise placement of material. Ideal system for assembly, maintenance and in-field service. 50 mL Mixing Nozzle 9742. P/N 09-01372.....

## 3M™ SCOTCH-WELD™ EPX™ APPLICATOR NOZZLE

Applicator nozzle designed for both the 200 mL and 400 mL applicators.....P/N 09-01408 .....

## 3M™ SCOTCH-WELD™ INSTANT ADHESIVE CA40H



One-part, high strength, very fast setting adhesive cures at room temperature. Adheres to difficult to bond substrates such as EPDM rubber, aluminum, and flexible vinyl. Comes in a 1 oz. Bottle. Clear.....P/N 09-01368 .....

## 3M™ SCOTCH-WELD™ INSTANT ADHESIVE CA8



This instant adhesive has a fast set time of 5 to 40 seconds. Excellent adhesion on metal, plastic and rubber. Bonds resist shock and impacts. A cyanoacrylate adhesive. Comes in a 1 oz. bottle.....P/N 09-01366 .....

## 3M™ SCOTCH-GRIP™ CONTACT ADHESIVE



A brushable, neutral-colored contact adhesive for bonding many decorative laminates, aluminum, steel, plywood, panels, wood and wood veneer, masonry, rubber, canvas and other porous and non-porous materials to each other or to themselves.....P/N 09-01364 .....

## 3M™ PERFORMANCE MANUAL APPLICATOR



Provides fully portable application of 2-part adhesives for auto maintenance and repair jobs. Designed for use with 3M cartridges as small as 37.5 mL. P/N 03-00260 .....

## 3M™ SCOTCH-WELD™ EPX PLUS II 1 TO 1 OR 2 TO 1 PLUNGER



3M Scotch-Weld EPX Plus II Applicator is designed to be used with any 1:1, 2:1 and 10:1 ratio 50 mL duo-pak cartridges. Kit comes with 1 applicator and 2 plungers, one each for 1:1/2:1 and 10:1 ratios. P/N 03-00256 .....

## 3M™ SCOTCH-WELD™ EPX SQUARE GREEN 48.5ML MIXING NOZZLE



3M Scotch-Weld™ EPX Square Mixing Nozzle Green is used to mix urethane adhesives in 48.5 or 50 mL cartridges with the 3M Scotch-Weld EPX Plus II Applicator.....P/N 03-00257 .....