

SPRAY PAINTS – SUPERFLITE – PRIMERS



PREMIUM SELF-ETCHING PRIMER

Etches and primes in one easy step. Can be used under all today's automotive finishes. Perfect for spot repairs. Creates superior adhesion on most plastics, fiberglass, bare steel, aluminum and stainless steel. **Color:** Green
12oz. Spray CanP/N 09-02099



KRYLON AEROSOL HIGH HEAT PAINT

Krylon High Heat & Radiator Paint is ideal for mufflers, radiators, and engine blocks. Withstands temperatures to 600°F. Guards against rust. Available in three colors.
12 oz. aerosol cans.

AluminumP/N 15-05467
WhiteP/N 15-08254
BlackP/N 15-08255



VHT WRINKLE PLUS COAT

VHT Wrinkle Plus™ combines strong colors with a deep rich texture for a custom look. It is temperature resistant to 350°F (177°C) and is ideal for adding a touch of personal styling to almost any metal surface. VHT Wrinkle Plus™ resists color fading, grease, degreasers, and severe weather conditions. This tough, durable finish is extremely resistant to rust, corrosion, chipping and cracking. **Applications:** Valve Covers, Metal Dashboards, Glove Boxes, Starters, Door Panels, Shifters, Alternators, Firewalls Black SP201.

P/N 09-05684



VHT SP124 GLOSS BLACK ENGINE ENAMEL

VHT SP124 Gloss Black High Temp (500 degrees Fahrenheit) Engine Enamel has excellent durability and superior heat and chemical resistance. It is specially formulated to withstand corrosion, rust, salt spray, chemicals and additives of today's gasoline blends and degreasers. VHT's 550 degree engine enamel is a unique blend of urethane and ceramic resins, which produce a long-lasting finish for engines, engine accessories or wherever a tough durable heat and chemical resistant finish is neededP/N 09-06111

SUPERFLITE AIRCRAFT ENGINE ENAMELS

Superflite engine enamels are fast-drying enamels developed specifically for air-cooled aircraft engines used in light duty aviation industries. The Superflite enamels feature superior adhesion, heat resistance, and a gloss finish. Cure Schedule: Dry to touch: 15 minutes, Dry to handle: 60 minutes Dry through: 24 hours To recoat: Before 60 minutes , or after 72 hours Benefits: Topcoat - Air dry or low temperature cure, For use on bare metal or painted surfaces Specifications: Shelf Life: 12 months at recommended storage temperatures, Heat Resistance: Up to 400°F.

Lycoming Grey Paint QuartP/N 09-02558

Lycoming Grey Paint SprayP/N 09-02556

TCM Gold Paint QuartP/N 09-02557

TCM Gold Paint SprayP/N 09-02550

Attention: The current Continental engine color is more Silver than Gold.

Gloss Paint Black QuartP/N 09-02559



CAN-GUN

Can-Gun is an aerosol spray can trigger handle which makes painting, cleaning, and lubricating jobs safer and easier. The user-friendly form-fit handle and trigger eliminates finger fatigue and provides the user with accurate control over the amount, speed, and direction of spray.

The built-in safety shield insures no more messy hands or fingers. Sprays virtually all spray paints, lacquers, polishes, cleaners, lubricants, sealers, and adhesives and Can-Gun fits most spray cans.

P/N 09-14760 ea.

EXTEND-A-LUBE SUPER STRAWS (PACKAGE OF 3)



Super Straws reduce or eliminate messes from overspray. The high grade plastic is extremely chemical resistant and can be used with various lubricants, harsh degreasers, and compressed gases. Super Straws increase the range and utility of aerosol products by using a 16" high grade plastic tube to access those hard to reach places. Easily cut to any length using a knife or scissors, Extend-A-Lube Super Straws are proudly manufactured, packaged, and sold in the U.S.A.!P/N 09-02398



VHT SP652 SATIN BLACK EPOXY ALL WEATHER PAINT

VHT SP652 Satin Black Epoxy All Weather Paint is a one step epoxy coating which does not require use of primer. It has been formulated to give the appearance of a baked-on finish. It provides a porcelain-like finish that is chemical, corrosion, rust and salt resistantP/N 09-06108



VHT SP651 GLOSS WHITE EPOXY ALL WEATHER PAINT

VHT SP651 Gloss White Epoxy All Weather Paint is a one step epoxy coating which does not require use of primer. It has been formulated to give the appearance of a baked-on finish. It provides a porcelain-like finish that is chemical, corrosion, rust and salt resistantP/N 09-06110



DUPLIC-COLOR DA1670 GLOSS WHITE ACRYLIC ENAMEL

Dupli-Color® Premium Enamel offers exceptional quality in a general purpose enamel paint. A high-solids acrylic enamel formulation delivers the ultimate in protection, gloss and color retention while delivering maximum coverage on metal, wood, and fiberglass surfaces.P/N 09-06115



DUPLI-COLOR DA1605 GENERAL PURPOSE BLACK FLAT

Dupli-Color® Premium Enamel offers exceptional quality in a general purpose enamel paint. A high-solids acrylic enamel formulation delivers the ultimate in protection, gloss and color retention while delivering maximum coverage on metal, wood, and fiberglass surfaces.P/N 09-06114



DUPLICOLOR DAL1607 BLACK FLAT LACQUER

Dupli-Color® Premium Lacquer is a fast-drying, high-solids formula that provides quick coverage, excellent weatherability and superior adhesion. It delivers a rich glossy finish every time making it ideal for automotive trim and detail projects, as well as other general purpose applications.

P/N 09-06112



DUPLI-COLOR DA1600 BLACK GLOSS

Dupli-Color® Premium Enamel offers exceptional quality in a general purpose enamel paint. A high-solids acrylic enamel formulation delivers the ultimate in protection, gloss and color retention while delivering maximum coverage on metal, wood, and fiberglass surfacesP/N 09-06113



ZINC PHOSPHATE PRIMERS

Maximum adhesion to bare aluminum and steel Tempo's Zinc Phosphate Primers are recommended for priming bare metal. These primers provide maximum bonding to bare aluminum and steel. Tempo's Primers have been the workhorse in the aviation industry for many years.

The A-701 Yellow and A-702 Green Zinc Phosphate Primers meet the performance standards outlined in Federal Specification T-P-1757A. They also exceed the 800 hours of salt spray fog test (ASTM #B117). A-701 will replace A-901 Yellow and A-702 will replace A-902 Green.

YellowP/N 09-02128

GreenP/N 09-02127



AKZO FAST DRYING INTERIOR EPOXY PRIMER

AKZO interior epoxy primer #463.12-8 is a chemically cured 2-component epoxy primer designed to provide maximum protection from various chemicals, hydraulic fluids, aviation fuels, hydraulic fluids, and corrosive causing media. Drying time to touch is 15 minutes and to recoat is 1-24 hrs. Shelf life: 2yrs, Color: Green. Used extensively in military and aerospace applications and popular with aircraft builders. Uses 1 gallon of primer and 1 gallon of catalyst.

2 gal. kitP/N 09-24735

TR-19 ThinnerP/N 09-00439

CS